

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 31

T. S. R 2

R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 2181

Lwonaard Herzstein
S.F.S. - Deputy
Douglas Co. Surveyors
Office
Court Arciniega; Joe
Richey, Witnesses
Oct. 23, 1980
C.S. 61/11

South 1/16 Sec. 1; and Sec. 6 of T.31-1 214
Found - 2" diam. I.P. with 1967 brass cap properly marked facing
East and leaning easterly, firmly set, projecting 20"
above ground, set by Baughman. Ren. #133
W. Oak, 10", Bears S.9°44'W., 35.1 ft. (Rec. 32.3 ft.) with
healed blaze.
W. Oak clump with 2 trunks, the Easterly trunk 8" Diam. bears
N.24°14'W., 32.3 ft. (Rec. 35.3 ft.) with healed blaze.
Reset - Reset I.P. facing North, firmly set, projecting 8" above 2 ft.
mound of stone. 10/23/80

Bruce Shaner
For: U.S. Forest
Service
Feb. 1981
RM 3 - 44

Center 1/4 For Section 10 215
Set - Brass cap marked "T31S R2W WM C 1/4 S10 RLS 430 1981"
BT's - 8" Hemlock BT, I scribed "C 1/4 S10 BT" bears S.6°E., 2.0 ft.
14" D. Fir BT, I scribed "C 1/4 S10 BT" bears S.71°W., 32.1 ft.

1/4 Corner for Sections 10 and 15. 216
Found - 1966 County Brass cap properly marked. Ren. #85
26" D. Fir BT scribes visible, bears N.27°W., 8.4 ft.
New BT - 10" D. Fir BT, I scribed "1/4 S15 BT" bears S.64°W., 14.9 ft.
2/81

Leonard Herzstein
U.S.F.S. - Deputy
Douglas Co.
Surveyors Office
Witnesses: Jim
Landrum &
Tom Wolford
May 20, 1981
C.S. 61 / 24

1/4 Corner common to Sec's. 24, & 25. 217
Found - 1" I.P. set by John Powell, Deputy Co. Surveyor in 1966,
firmly set, projecting 4" above ground, with B.C. marked
properly. Ren. #63
Orig. BT:
A 17" Madrone snag, N65°E, 18.5-ft., with scribe marks
"BT" visible on previously opened blaze.
BT's marked by Powell in 1966:
A 17" D. Fir, S58°E, 37.3-ft., with healed double blaze.
A 14" D. Fir snag, N38°W, 21.0-ft., with scribe mark
"1/4 S24 CS BT" visible on partly healed blaze.
New Accessories - I mark new BT:
A 9" I. Cedar, N61°W, 70.3-ft., scribed "1/4 S24 CS BT"
on a double blaze.
* NOTE - B.C. is just outside fence corner; fence bears South & West.

Leonard Herzstein,
S.F.S., Deputy, Doug.
Co. Surveyors
Office. Witnesses:
Jim Landrum, Tom
Wolford
June 4, 1981
C.S. 61/27

CONDITION REPORT ONLY 218
1/4 Corner for Sections 34 and 35
Found - 1 1/4" I.P. firmly set, projecting 12" above ground with
1966 County brass cap properly marked. Ren. #65
Original stone set alongside with marks "1/4" on top.
A rotted D. Fir stump, size indeterminate, N.30°E., 11.2 ft.
with no marks visible.
A 24" I. Cedar, S.87°W., 9.9 ft. with healed blaze.
42" D. Fir stump, N.28°W., 18.6 ft. with scribe marks visible.
and BT of which there is no record: A 10" I. Cedar, N.18°E., 86.4 ft.
with scribe marks visible on partly healed blaze.
NOTE: BT Put on Record 9/16/81 - B. Shaner see c.s. 58/229 - T.R. 6/4/81

Gregory E. Quibell
Deputy Douglas Cou.
Surveyors Office
Terrie Plouff, and
Teresa Buley, witnesses
Oct. 22, 1981
C.S. 61 / 29

South 1/4 cor. for Sec.31 only, in T.30-2. 219
Found - Orig. 15" x 12" x 6", now 14" x 11" x 6" stone with 1/4 mkd. on
No. face, buried w/ top flush to ground.
BT's - Orig. 15", now 22" Fir snag, 20' high w/good scar bears N.12°W., 7.9-ft.,
(Rec. N.18°W.).
Poss. Orig. 6" Fir, down & rotted @ app. orig. position (root-hole undefin
Set - Orig. stone referenced; B.C. set in its place, mkd: Douglas Co.
Surveyor T30S 1/4 S31 R2W 1981 (Reset stone along No. edge of cap).
New BT's - 30" Fir, scbd. S1/4 31 CSBT (dbl. blaze) bears N.87 1/2°E., 35.4-ft.
10" Fir scribed S1/4 6 CSBT (dbl. blaze) bears S.69°E., 42.8-ft.
8" Madrone scrbd. S1/4 6 CSBT (dbl. blaze) bears S14°W., 21.0-ft.
42" Madrone w/PK nail in base, scribed S 1/4 6 CSBT in double
blaze, bears S.67°W., 2.9-ft. to nail.
Note - This corner is along the Southerly side of a future clear-cut.
10/22/81