

Douglas County Surveyor's Record of
Government Corners Renewed

T 31

T. S. R 2

R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21981

Loyd R. Moffit
LS No. 944
For: USFS
Oct. 1986
C.S. 62/30

South 1/4 Corner for Section 33 only of T.30-2
Found - 1966 County Surveyor's 2 1/2" brass cap on a 1" iron pipe in a mound of rock. (Ren. No. 166 and 129)
A 8" Hemlock (snag) which bears N.29 3/4°E., 26.2 ft. scribe visible.
A 28" Fir stump which bears S.01 3/4°W., 6.6 ft. scar visible.
A 22" Cedar (dead) which bears N.21 1/2°W., 12.4 ft. scribe visible.
New BTs - I marked a 28" Fir which bears N.31°E., 96.4 ft. scribed 1/4 S33 BT.
I marked a 24" Fir which bears N.43°W., 60.6 ft. scribed 1/4 S33 BT.
Both new BTs have LS 944 Brass washer nailed to BT scribe.

10/86

225

Section corner for Sections 5 and 4 only.

Found - 1966 County brass cap on a 1" iron pipe is on south side of corner tree. Ren. #130
A 42" Fir corner tree with scribe visible.
Remains of Fir BT, S.70 3/4°E., 17.8 ft. (steel fence post with signs stand where tree was.) Ren. #198
24" madrone which bears S.05 1/2°W., 18.7 ft. scribe visible.
New BT - I scribed a 8" fir which bears S.25°E., 20.1 ft. marked T31S R2W S4 BT with a LS 944 brass washer nailed to BT scribe.

226

10/86

1/4 Corner for Section 16 only. (west)

Found - 1961 County Surveyors brass cap (2 1/2") on 1" I.P. Ren. #26
Fir stump, S.32 1/2°E., 23.1 ft. (1908)
14" cedar N.30°E., 35.1 ft. scribe visible. Ren. #26
Fir stump, S.83°E., 31.4 ft. scribe visible. Ren. #137
Fir stump, S.21°W., 17.8 ft. (1908)
New BT - A 9" Fir which bears N.80 1/2°W., 4.7 ft. scribed 1/4 S16 BT, with L.S. washer No. 944 nailed to BT scribe.

10/86

227

Loyd R. Moffit
For: U.S.F.S.
C.S. 62/30
Nov. 1986

Section Corner for Secs. 13 and 24 only. T. 31-3

Found - 1966 County Surveyors 2 1/2" brass cap with 1" I.P. Ren. #37
60" Pine (dead) S.41 1/2°W., 16.5 ft. (Rec. S.44°W., 15.7 ft. Scar visible. (Original BT)
8" Madrone N.66°W., 27.1 ft. (Rec. N.64°W., 27.0 ft.) Scribe visible. Ren. No. 37
26" Fir N.71 1/2°E., 16.5 ft. (Rec. N.70°06'E., 15.9 ft.) Scar visible. (Orig.)
Hemlock, (down) S.32°22'E., 34.7 ft. Ren. No. 37
9" Madrone S.29°E., 18.6 ft. (Rec. S.28°23'E.,) Rotted face. (orig)
Note: Record bearings/dists. given are from survey M79-43.
New BT - A 6" Fir which bears S.84°W., 12.2 ft. scribed T31S R3W S24 BT, with L.S. washer No. 944 nailed to BT scribe.

11/86

228

1/4 Corner for Section 31 only.

Found - 1" galv. I.P. with 2 1/2" brass cap extended 9" above ground and mkd. 1966, County Surveyors Office. Ren. #115
14" D. fir snag bears N.76°29'E., 21.5 ft. (healed blaze. Ren. #9
19" Hemlock bears S.49°41'E., 7.2 ft. (healed blaze.) Ren. #19
New BT - A 20" W. fir bears N.43°E., 11.9 ft. scribed "T31S R2W S31 1/4" BT doubled blaze, set 1/2" brass washer in lower blaze.

229

Bearing tree signs and monument signs were placed on all bearing trees without them and a 6" red band and face blazes were painted on all bearing trees.

4/21/88

1/4 Corner for Sections 27 and 34

Found - 2" iron pipe with 1966 County brass cap from which an original stone sets alongside, marked 1/4. Ren. #62
18" D. fir stump bears N.31°W., 11.9 ft. (visible scribe) Orig.
20" D. fir stump bears South, 16.5 ft. (visible scribe) Orig.
15" D. fir snag bears S.71°E., 34.3 ft. (visible scribe) Ren.#62
19" D. fir snag bears N.76°W., 3.0 ft. (visible scribe) Ren.#62
12" D. fir bears S.69°W., 21.6 ft. (visible scribe) Ren. #212
New BT - 5" D. fir bears N.18°E., 31.6 ft. scribed "X" in small upper blaze and "BT" in small lower blaze. A 1/2" brass washer is nailed flush in lower blaze.

3/20/88

230

Gerald Nygren
March 20, 1988
C.S. 63/69