

Douglas County Surveyor's Record of
Government Corners Renewed

31 T. S. 3 R. W. W. M.

C. T. Roberts
September 20, 1909.

F.B. 10 P. 52-53
5 1/2

FB 10 Pg 51
CORNER BETWEEN SECTIONS 28 and 33
Set 1/2 section corner at boundary of section 33
as per original corner. Only one B.T. and it
is cut off and destroyed. I put in two new B.T.s in
Section 28 in other trees in 33.
A White Fir 32 In. bears N. 20° 15' W., 168 lks.
A Red Fir 30" dia. bears N. 15° 15' E., 144 1/2 lks.

RE-RENEWED, SEE CORNER NO. #219 & 225
FEB. 1966 - SEARCHED FOR, NOT FOUND. J.M.P. 10/20

CORNER TO SECTIONS 28, 29, 32 and 33.
Put in N.W. corner of 33. Old B.T. badly decayed.
Marked C.S.

A Fir 12" dia. S. 76 3/4° E., 31 lks.
A Fir 12" dia. S. 32 1/2° W., 59 lks.

FB 10 Pg 51 SEE # 82
NOTE: DO NOT BELIEVE ROBERTS
RENEW. SEE COR. DO NOT FIND
HIS B.T.s. BUT FIND ALL ORIG.
B.T.s. SEE CORNER NO. 82

CORNER TO SECTIONS 32, 33, 4 and 5, T. 31-3 and T. 32-3.

Found one B.T. standing 34" Fir S. 34° W., 34.0 ft.
also found scribe mark "T" on old rotted Laurel stump
N. 45° E., 39.6 ft. Set two new B.T.s.

A 28" Fir N. 72° 04' E., 30.5 ft.
A 15" Fir N. 31° 36' W., 63.2 ft.

Set a 1" x 33" Bolt.

C.S.
A6/133

CORNER BETWEEN SECTIONS 31 and 32.

Found Cedar B.T. S. 48° W., 29.7 ft. still standing and
Pine stump in place but rotted, no marks showing. Set
3/4" Iron Pipe for corner and mark new tree for B.T.

A 12" Cedar N. 79° 15' E., 38.6 ft.

CORNER TO SECTIONS 31, 32, 5 and 6, T. 31-3 and T. 32-3.

Found B.T. S. 22° E., 59.4 ft. standing also Pine
stump marked B.T. N. 80° E., 47 lks. instead of 117 lks.,
also Pine stump S. 30° W., approximately 30 lks. had been
rooted up no marks. Set 1" Iron rod 2 ft. long for
corner also new B.T.

A 14" Fir N. 57° 10' W., 140.8 ft.

CORNER ON SOUTH SIDE OF SECTION 32.

No B.T. found so run line between S.W. and S.E. corner
and set 3/4 corner equal distance from each. Set 1" Iron
Pipe 30" long and two new B.T.

A 7" Chinquapin S. 47° 24' E., 9.2 ft.
A 10" Fir N. 47° 40' W., 33.9 ft.

CORNER BETWEEN SECTIONS 33-34.

Find both original B.T.'s. bearings do not agree but
distances do.

Drive 1 1/2" pipe for corner. bend to the N.W. on account of
root.

A 22" Fir S. 50° 08' W. 13.2 Ft.
A 19" Fir S. 59° 12' E. 5.94 ft.

CORNER BETWEEN SECTIONS 27 - 34.

Find old B.T. a 36" Fir N. 46° 30' W. 5.94 ft.
Drive 2" pipe for corner.
Mark new B.T. A 28" Fir S. 24° 48' W. 53.8 ft.

CORNER TO SECTIONS 27 - 28 - 33 - 34.

Find three old B.T.'s.
Drive 1" pipe for corner.
Scrib A 20" Madrone S. 24° 30' E. 39.0 ft.

COR. 6-5, T 32 S & 31-32 T 31 S

Drive 1 1/2" I. Pipe
36" Fir S 22° E 59.4 ft. O.B.T.
12" Fir N 46° 45' E 33.8 ft.
15" Fir S 40° 24' W 223.2 ft.
14" Fir N 66° 47' W 140.3 ft.

COR. BET. 6 T 32 S & 31 T 31 S

Found 20" Fir N 47° W 16.5 ft.
16" Fir S 22° W 12.5 ft.
Drive 1 1/2" Pipe for corner.

Geo. J. Wenderoth - D.C.S.
Frank Loso - Witness
June, 1950

Geo. J. Wenderoth
Dep. Co. Surveyor.
November 1946.
Witness. Donald Snyder.

427-15

C.S. 45/229

1
2
3
4
5
6
7
8
9
10
11