

Douglas County Surveyor's Record of
Government Corners Renewed

31 T. S. 3 R. W. W. M.

SEC. COR. 34-35-2-3 (T 31 & 32) 12

Found 28" Hemlock bearing N 38° E 12.5 ft. and a
28" W. Fir S 31° W 14.5 ft.

✓ Set a 2" I. P. for the Cor. 169

Marked a 6" Hemlock bearing S 36° 10' E 33.0 ft.
and a 10" W. Fir bearing N 11° 18' W 11.5 ft.

1/4 COR. BETWEEN 34 & 3, T 31 & 32 13

Set halfway between Sec. Corners.

Set a 1" I. Pipe for the Cor. 168

✓ Marked a 12" Fir bearing N 39° 40' E 18.9 ft. dist.
10" Fir Bearing S 71° 24' E 12.3 ft. dist.

1/4 COR. BETWEEN SECS. 19 & 30. 14

Find both O. B. T's., one dead.

I drove a 2" I. P. for the corner, and marked a new B. T.

10" Fir bearing S 24° 35' W 28.8 ft. dist. (new B. T.)

28" Fir bearing N 79° 05' E 21.4 ft. dist. (old B. T.)

SEC. COR. 19-20-29-30 15

Find all 4 B. T. in good shape.

DDrive a 1 1/4" Pipe for the Corner. 151

13" Cedar bearing N 25° 15' E 22.1 ft. dist.

10" Fir bearing S 54° E 13.2 ft. dist.

10" Laurel bearing S 81° W 23.2 ft. dist.

11" Fir bearing N 29° 30' W 10.5 ft. dist.

SEC. COR. 29-30-31-32 16

Find all 4 B. T's. in good shape.

Drive 1 1/4" Pipe for Corner. 137

36" Fir bears S 35° E 11.8 ft. dist.

12" Cedar bears S 75° W 5.2 ft. dist.

14" Cedar bears N 67° 30' E 17.1 ft. dist.

16" Fir bears N 82° 30' W 10.5 ft. dist.

1/4 COR. BETWEEN SECS. 30, R 3 W, & SECS. 25, R 4 W. 17

Find old B. T. a 40" Fir bearing S 50° 30' E 47.8 ft. dist.

Drive a 1 1/2" I. P. for corner and mark B. T. 172

20" Madrone bearing N 29° 49' W 21.7 ft. dist.

1/4 COR. BETWEEN 29 & 30 18

Found both old B. T.'s in good shape

28" Cedar bearing N 44° E 15.5 ft. dist. 152

16" Cedar bearing N 68° W 33.6 ft. dist.

Drove a 1" I. P. for the Corner.

SEC. COR. BETWEEN 30-31 R. 3. W, 25-36 R 4 W. 19

Drive 1" Pipe for the Corner and find 2 O. B. T.

20" Fir bearing N 13° 30' E 22.7 ft. dist. 141

14" Fir bearing N 12° 50' W 19.4 ft. dist.

Marked 24" Cedar bearing S 7° 20' W 20.6 ft. dist.

18" Fir bearing S 19° 12' E 47.5 ft. dist.

1/4 COR. BETWEEN SECS. 30-31 20

All signs of the cor. gone, set cor. 2640 ft. west of Cor. 29-30-31-32

Drive 1" Pipe for the corner.

Marked 18" Fir bearing N 23° 05' E 8.0 ft. dist. 153

Marked 12" Fir bearing S 65° E 20.8 ft. dist.

SEC. COR. 26-27-34-35 21

Found 28" Fir N 39° 30' E 24.4 ft., other trees gone.

Drive 1" iron pipe for corner, and mark new B. T.

26" Fir N 12° 08' W 23.4 ft. 155

36" Fir S 31° 08' E 27.3 ft.

7" Fir S 52° 05' W 8.5 ft.

1/4 COR. BETWEEN 34-35 22

Found 14" Fir N 67 1/2° W 5.9 ft., Drive 1" iron pipe and mark B. T.

16" Fir N 31° 10' E 29.0 ft.

14" Fir N 32° 50' W 17.5 ft. 166

C.S. 45/229

George Wenderoth- Deputy County Surveyor

Probably 1946 or 1947

M 27-14

Geo. Wenderoth
Dep. Cnty. Surv.
Frank Loso
Witness
Dec. 1947
Feb. 1948

C.S. 45/229