

Douglas County Surveyor's Record of
Government Corners Renewed

31

T. S.

3

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

30

Section corner to secs. 22, 23, 26, and 27.

Determined at the record bearing and distance from the original SE. bearing tree; the stone and other bearing trees are gone.

At the corner point,

Set an iron pipe, 3 ft. long 2 ins. diam., 28 ins. in the ground, mkd. RS33; from which the extant original bearing tree:

A live Oak, 20 ins. diam., bears S.41 $\frac{3}{4}$ °E., 32 lks. dist., with partial scribe marks visible.

And new bearing trees:

A Madrona, 6 ins. diam., bears N.58 $\frac{3}{4}$ °E., 33 lks. dist., mkd. on bark T31S, R3W S23 RS33 BT. 156

A Madrona, 5 ins. diam., bears S.70 $\frac{1}{2}$ °W., 27 lks. dist., mkd. on bark T31S R3W S27 RS33 BT.

A Madrona, 6 ins. diam., bears N.49°W., 35 lks. dist., mkd. on bark T31S R3W S22 RS33 BT.

The geographic position of this corner is lat. 42°51'23"N., and long. 123°01'52"W. The observed magnetic declination is 22°00'E.

31

$\frac{1}{4}$ sec. corner to secs. 22 and 27.

Monumented by a basalt stone, 8x6x6 ins. above ground, firmly set, mkd.

$\frac{1}{4}$ on N. face; from which the original bearing trees:

A dead Douglas fir, 7 ins. diam., bears N.87°W., 5 $\frac{1}{2}$ lks. dist., with blaze healed.

A Douglas fir, 20 ins. diam., bears S.75 $\frac{1}{4}$ °E., 27 $\frac{1}{4}$ lks. dist., with blaze healed. 160

Set an iron pipe, 3 ft. long, 1 $\frac{1}{2}$ ins. diam., 28 ins. in the ground, mkd. RS33, against S. side of stone.

A Douglas fir, 12 ins. diam., bears N.57°W., 4 lks. dist., marked $\frac{1}{4}$ S22 RS33 BT. (New B. T.)

32

$\frac{1}{4}$ sec. corner to secs. 22 and 23.

Determined at the record bearing and distance from the original NW. bearing tree; all other evidence of the $\frac{1}{4}$ sec. cor. is gone.

At the corner point,

Set an iron pipe, 3 ft. long, 1 $\frac{1}{2}$ ins. diam., 28 ins. in the ground, mkd. RS33; from which the extant original bearing tree:

A sawed fir stump 15 ins. diam., bears N.53°W., 31 lks. dist., with section of tree marked $\frac{1}{4}$ S alongside. 90

And new bearing trees:

An incense cedar, 5 ins. diam., bears N.12 $\frac{1}{2}$ °E., 36 lks. dist., mkd. $\frac{1}{4}$ S23 RS33 BT.

A Douglas fir, 22 ins. diam., bears S.51 $\frac{1}{2}$ °W., 24 lks. dist., mkd. $\frac{1}{4}$ S22 RS33 BT.

33

Section corner to secs. 14, 15, 22 and 23.

Monumented with a basalt stone, 9x5x7 ins. above ground, firmly set, mkd. with 2 notches on E. and 3 notches on S. edge; from which the extant original bearing trees:

A madrona, 20 ins. diam., bears N.73 $\frac{1}{2}$ °E., 78 $\frac{1}{2}$ lks. dist., with blaze healed.

A burnt Douglas fir snag, 15 ins. diam., bears S.50°E., 70 $\frac{1}{2}$ lks. dist., with partial scribe marks.

A Douglas fir, 28 ins. diam., bears N.36 $\frac{1}{2}$ °W., 57 $\frac{1}{4}$ lks. dist., with blaze healed. 147

And new bearing trees:

A Douglas fir, 12 ins. diam., bears S.36 $\frac{1}{2}$ °E., 46 lks. dist., mkd. T31S R3W S23 RS33 BT.

An incense cedar, 24 ins. diam., bears S.4 $\frac{1}{4}$ °W., 36 lks. dist., mkd. T31S R3W S22 RS33 BT.

Against S. side of stone, set an iron pipe, 3 ft. long, 2 ins. diam., 28 ins. in the ground, mkd. RS33.

34

$\frac{1}{4}$ sec. corner to secs. 15 and 22.

Monumented with a basalt stone, 8x4x6 ins. above ground, firmly set, mkd. $\frac{1}{4}$ on N. face; from which the original bearing trees:

A madrona, 16 ins. diam., bears N.10 $\frac{3}{4}$ °W., 45 lks. dist., blaze healed.

An incense cedar, 22 ins. diam., bears S.7°W., 24 lks. dist., with blaze healed.

Against S. side of stone, set an iron pipe, 3 ft. by 1 $\frac{1}{2}$ " dia., 28 ins. in ground mkd. RS33.

Norman D. Price - RE No. 33. Work done for W. A. McKenzie, Tiller, Oregon.
April 5 - 18, 1955.
Filed in Co. S. File No. 41/372.