

Douglas County Surveyor's Record of
Government Corners Renewed

31 T. S. 3 R. W. W. M.

S. E. Corner Section 36.

as determined by O. B. T.'s:

- 40" White Fir bears N.55°W. 60.5 ft. O. B. T.
- 11" Cedar bears N.40°E. 68.5 ft. O.B.T., I remk. S1 B. T.
- 24" Fir bears S.14°E. 7.9 ft. O.B.T., I remk. S1 B.T.
- 15" White Fir bears S.16°W. 28.4 ft. O.B.T., I rescribed S1 T32S R2W B.T.

41

John H. Markham, Jr.
Wit: J.R. Markham
October 29, 1958
For Stomar Lbr. Co.
C. S. File 42/392

At Corner Point Set $\frac{3}{4}$ " x 60" Iron Pipe 36" in ground.

Road bears North 250.0 ft. distance.

S. W. Corner Section 31, bears N.441.0 ft.

189

$\frac{1}{4}$ Section Corner to Sections 2 & 3.

as determined by O.B.T.

6" Yew dead Snag bears N.25°W. 3.6 ft., fd. scribe O.B.T.

14" Fir bears S.39°E. 10.1 ft., fd. scribe.

At Corner Point found Stone mkd. $\frac{1}{4}$ from which:

- 15" Fir bears N.31°E. 68.0 ft. on slope mkd. $\frac{1}{4}$ S 2 B.T. on bark.
- 25" Alder bears S.57°W. 137.0 ft. on slope mkd. $\frac{1}{4}$ S3 T31S R3W B.T.
- 30" Hemlock bears S.75°W. 163.0 ft. on slope mkd. $\frac{1}{4}$ S3 B.T.

Stouts Creek bears South 145.0 ft.

The logging road will be built thru $\frac{1}{4}$ Corner, that is why I picked new trees at such distance.

42

John H. Markham, Jr.
Wit: R.G. Boyd
For Stomar Lbr. Co.
Dec. 16, 1958
C.S. File No. 42/392

N. E. Corner Section 6.

as determined by O. B.T.'s.

30" Fir bears S.64°E. 18.5 ft. O. B. T.

10" Maple bears S.33°W. 18.5 ft. O.E. T.

At Corner Point Set $1\frac{1}{2}$ " x 36" Iron Pipe from which:

- 7" Live Oak bears S.19°W. 70.0 dist. mkd. S6 B.T.
- 18" Fir bears N.54°E. 23.0 ft. dist. mkd. S32 B.T.
- 16" Fir bears S.78°W. 15.0 ft. dist. mkd. S6 X B.T.

South $\frac{1}{4}$ Corner Section 32 bears East 167.0 ft.

43

John H. Markham, Jr.
Wit: R. G. Boyd
For Stomar Lumber Co.
Jan. 16, 1959
C. S. File No. 42/392

$\frac{1}{4}$ Section Corner to Sections 5 & 6.

as determined by O.B.T.'s.

26" Fir bears S.12°E. 8.0 ft. dist. O.B.T.

22" Fir bears S.52°W. 27.2 ft. dist. O.B.T.

At Corner Point Set $1\frac{1}{2}$ " x 32" Iron Pipe from which:

- 7" Live Oak bears S.59°E. 25.5 ft. dist. mkd. $\frac{1}{4}$ S 5 B.T.
- 5" Laurel bears N.69°E. 23.8 ft. dist. mkd. $\frac{1}{4}$ S 5 B.T.

44

N. W. Corner Section 2.

As determined by O.B.T.'s:

32" La. S.36°W. 15.8 ft. dist. O.B.T.

32" Fir N.18°E. 28.4 ft., fd. scribe O. B.T.

24" La. S.67°E. 54.5 ft. dist. O.B.T.

At Corner Point Set $1\frac{1}{4}$ " x 30" Iron Pipe from which:

- 11" W. Fir S.48°E. 24.6 ft. mkd. S2 T31S R3W B.T.
- 12" La. N.84°E. 17.2 ft. mkd. S2 T31S R3W B.T.
- 12" La. N.60°E. 41.0 ft. mkd. S35 T30S R3W B.T.
- 6" W. Fir S.73°W. 13.0 ft. mkd. S3 T31S B.T.
- 6" W. Fir N. 4°W. 20.0 ft. mkd. S35 B.T.

Top bears East 100.0 ft.

South $\frac{1}{4}$ 35 bears East 480.0 ft.

45

John H. Markham, Jr.
Wit: R. G. Boyd
For Stomar Lumber Co.
April 28, 1959
C. S. File No. 42/392

N. W. Corner Lot 5, Section 2.

At Proportional Distance, I Set $\frac{1}{2}$ " x 36" Iron Pipe for Corner from which:

- 12" La. bears S.80°W. 5.5 ft. dist. mkd. 1/16 S3 T31S B.T.
- 10" La. bears N.37°W. 13.4 ft. dist. mkd. 1/16 SN 3 B.T.
- 12" La. bears N.86°W. 42.0 ft. dist. mkd. 1/16 S 3 R3W B.T.

Top bears North 620.0 ft.

N.W. Corner Section 2 bears North 1332.0 ft.

West $\frac{1}{4}$ Corner 2 bears South 2594.0 ft.

46