

Douglas County Surveyor's Record of  
Government Corners Renewed

31 T. S. 3 R. W. W. M.

KOKK-CHAPMAN CO., EUGENE, ORE. 21881

John H. Markham, Jr.  
For Stomar Lumber Co.  
Witnesses: R. G. Boyd - Vern Killian  
May 13, 1959  
C.S. File No. 42/392

Section Corner to Sections 2, 3, 10, & 11.  
as det. by O.B.T.'s:

- 10" Cedar S.25°E. 24.0 ft. O.B.T., fd. scribe.
- 30" Cedar S.60°W. 28.0 ft. O.B.T.
- 40" Fir Uproot N.59°W. 12.0 ft. O.B.T.

At Corner Point Set 2" x 2" Wood Post from which:

- 4" Fir bears S.62°E. 3.7 ft. dist. mkd. S11 B.T.
- 3" Fir bears S.84°W. 15.5 ft. dist. mkd. S10 B.T.
- 6" Fir bears S.10°W. 33.2 ft. dist. mkd. S3 T31S X B.T. 95
- 12" Ehip. " N.16°E. 62.0 ft. dist. mkd. S2 T31S R3W B.T.

1/4 Corner to Sections 2 & 11, as determined by O.B.T.'s.

- 30" Fir bears N.29°E. 25.4 ft. dist. O.B.T., found scribe.

At Corner Point Set 3" x 3" Wood Post from which:

- 20" Laurel bears S. 4°E. 74.5 ft. dist. mkd. 1/4 S11 B.T.
- 12" Laurel bears S.25°E. 44.0 ft. dist. mkd. 1/4 S11 B.T.
- 5" Fir bears S.77°E. 47.7 ft. dist. mkd. 1/4 S11 B.T.
- 10" Fir bears N.86°W. 73.0 ft. dist. mkd. 1/4 S 2 B.T.

Creek bears West 100.0 feet.

Section Corner to Sections 1, 2, 11, & 12.  
as determined by O.B.T.'s:

- 40" Fir N.45°E. 52.0 ft. O.B.T.
- 32" Fir S.60°E. 53.3 ft. O.B.T.
- 24" Cedar S.35°E. 35.6 ft., fd. scribe.
- 48" Fir N. 6°W. 31.4 ft. dist. O.B.T.

At Corner Point Found Stone from which:

- 8" Laurel bears N.69°W. 11.7 ft. dist. mkd. S2 T31S R3W B.T.
- 8" Laurel bears N.59°E. 19.4 ft. dist. mkd. S1 B.T.
- 8" Laurel bears S.75°E. 26.0 ft. dist. mkd. S12 B.T.
- 8" Laurel bears S.47°W. 22.0 ft. dist. mkd. S11 T31S B.T.

1/4 Corner to Sections 1 & 2, as determined by O.B.T.'s:

- 30" Pine Snag bears S.61°W. 22.8 ft. dist. O.B.T., fd. scribe.

At Corner Point Set 1/2" x 30" Iron Pipe from which:

- 9" Laurel bears S.85°E. 25.0 ft. dist. mkd. 1/4 S1 T31S R3W B.T.
- 12" Laurel bears N.21°E. 40.5 ft. dist. mkd. 1/4 S1 T31S R3W B.T.
- 20" Laurel bears N.13°W. 42.0 ft. dist. mkd. 1/4 S2 T31S R3W B.T.
- 9" Laurel bears S.81°W. 8.0 ft. dist. mkd. 1/4 S2 T31S R3W W.M.B.T.

N. E. Corner Section 2, as determined by O.B.T.:

- 14" W. Fir bears S.34°W.,
  - 12.8 ft. dist. O.B.T., found scribe.
- At Corner Point Set 1/2" x 30" Iron Pipe from which:
- 15" W. Fir bears N.22°E. 24.7 ft. dist. mkd. S36 T30S R3W W.M. B.T.
  - 12" Maple bears S.87°W. 49.0 ft. dist. mkd. S2 T31S R3W B.T.
  - 10" Chip. bears S.34°W. 34.8 ft. dist. mkd. S2 T31S R3W W.M.B.T.
  - 11" W. Fir bears S.35°E. 35.2 ft. dist. mkd. S1 T31S R3W B.T.

Creek bears East 30.0 feet. Ridge Top & Road bears West 420.0 feet.

1/4 Section Corner to Sections 12 & 13, as determined by O. B. T.'s.:

- 18" Fir bears N.25°W. 7.5 ft. O. B. T.
- 14" Fir bears S. 1/2°W. 38.2 ft. O. B. T.

At Corner Point found Original Stone & Set 2" x 24" Iron Pipe from which:

- 9" Fir bears S.59°E. 25.3 ft. dist. mkd. 1/4 S13 B. T.
- 8" Yew bears S. 2°E. 36.0 ft. dist. mkd. 1/4 S13 B. T.
- 8" Cedar " N.77°E. 35.0 ft. dist. mkd. 1/4 S12 B. T.
- 8" Fir bears S.54°W. 26.4 ft. dist. mkd. 1/4 S12 B. T.

Creek bears South 52.0 feet.

1/4 Section Corner to Sections 1 and 12.

At midpoint Set 2" x 30" Iron Pipe from which:

- 30" La. bears N.50°W. 31.0 ft. dist. mkd. 1/4 S 1 B.T.
- 18" Fir bears N.20°E. 23.0 ft. dist. mkd. 1/4 S 1 B. T.

SEE REN # 103

(continued over)

47

48

49

50

51

52

53