

Douglas County Surveyor's Record of  
Government Corners Renewed

31 T. S. 3 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21681

(continued)

12" Fir bears S.87°E. 31.0 ft. dist. mkd.  $\frac{1}{2}$ " SL2 B.T.  
N. W. Corner 12 bears West 2652 feet.  
N. E. Corner 12 bears East 2652 feet.

103

54

$\frac{1}{4}$  Section Corner to Sections 11 and 12, as determined by O. B. T.'s:  
40" Fir bears S.37°E. 38.0 ft., O. B. T.  
14" Laurel " S.61°W. 22.0 ft. dist., O. B. T., I rescribed  
 $\frac{1}{4}$ " SL2 B. T.  
At Corner Point found Stone and Set  $\frac{1}{2}$ " x 24" Iron Rod from which:  
24" Laurel bears N.36°E. 40.8 ft. dist. mkd.  $\frac{1}{4}$ " SL2 T31S B.T.  
14" Laurel bears N. 3°W. 43.5 ft. dist. mkd.  $\frac{1}{4}$ " S11 B.T.  
30" Fir bears S.-2°W. 45.0 ft. dist. mkd.  $\frac{1}{4}$ " SL2 R3 W B.T.  
30" Fir bears S.20°W. 21.7 ft. dist. mkd.  $\frac{1}{4}$ " S11 B.T.

104

55

N. E. Corner Section 12, as determined by O. B. T.'s:  
30" Fir N.24°E. 50.8 ft. dist. O. B. T.  
28" Fir S.16°E. 76.0 ft. dist. O. B. T.  
30" La. S.11°W. 25.0 ft. dist. O. B. T., I rescribed  
SL2 T31S R3W B.T.  
At Corner Point found Stone & Set Iron Pipe from which:  
6" Hemlock bears S.33°W. 8.5 ft. dist. mkd. SL2 B.T.  
9" Chip. bears N.55°W. 15.6 ft. dist. mkd. S 1 R3W B.T.  
7" Chip. bears N.66°E. 10.4 ft. dist. mkd. S 7 R2W B.T.

56

Section Corner to Sections 11 - 12 - 13 - 14, as det. by O.B.T.'s:  
30" Fir N. 8°E. 79.3 ft. O. B.T.  
26" Fir N.86°W. 59.3 ft. O. B. T.  
26" Fir S.55°W. 52.0 ft. O. B. T.  
At Corner Point Set  $\frac{3}{4}$ " x 30" Iron Pipe from which:  
12" La. bears N.89°E. 17.3 ft. dist. mkd. SL2 T31S R3W B.T.  
5" Fir bears N.13°E. 4.0 ft. dist. mkd. SL2 B.T.  
6" Fir bears N.49°W. 4.0 ft. dist. mkd. S11 B.T.  
6" La. bears S.21°W. 10.9 ft. dist. mkd. SL4 T31S R3W B.T.  
6" Fir bears S.18°E. 12.6 ft. dist. mkd. SL3 X B.T.  
Corner lies on Top of Main Ridge.

106

57

$\frac{1}{4}$  Corner to Sections 13 & 14, as det. by O.B.T.'s:  
14" Fir N.56°E. 15.8 ft. O.B.T., fd. scribe.  
12" Fir N.74°W. 8.6 ft. O.B.T.  
At Corner Point found 12" Fir mkd. on West face &  
Set  $\frac{3}{4}$ " x 30" Iron Pipe from which:  
36" Cedar bears S.13°E. 21.5 ft. dist. mkd.  $\frac{1}{4}$ " SL3 R3W B.T.  
12" Fir bears S.74°E. 24.0 ft. dist. mkd. on bark  $\frac{1}{4}$ " SL3 B.T.  
Corner lies on top of side ridge.

108

58

$\frac{1}{4}$  Corner to Sections 11 & 14, as det. by O. B. T.:  
50" Fir, uproot, bears N.72°E. 19.8 ft. O.B.T., found scribe.  
At Corner Point Set  $\frac{3}{4}$ " x 30" Iron Pipe from which:  
13" Fir bears S.67°W. 16.5 ft. dist. mkd.  $\frac{1}{4}$ " SL2 B.T.  
8" Fir bears N.38°W. 13.0 ft. dist. mkd.  $\frac{1}{4}$ " S11 B.T.  
8" Laurel " N.34°E. 13.5 ft. dist. mkd.  $\frac{1}{4}$ " S11 T31S R3W B.T.  
16" Alder " N.55°E. 46.0 ft. dist. mkd.  $\frac{1}{4}$ " S11 B.T.  
Creek bears East 40.0 feet.

#109

59

$\frac{1}{4}$  Corner to Sections 19 and 20, as det. by O.B.T.'s:  
40" Fir Snag S.57°E. 22.4 ft. O.B.T.  
At Corner Point Found 1" x 30" Iron Pipe from which:  
16" Laurel bears N.89°E. 21.7 ft. dist. mkd.  $\frac{1}{4}$ " S20 B.T.  
13" Fir bears N.10°E. 16.0 ft. dist. mkd.  $\frac{1}{4}$ " S19 B.T.  
32" Cedar bears S.5°W. 4.4 ft. dist. mkd.  $\frac{1}{4}$ " S19 B.T.  
5" Fir bears N.75°W. 13.8 ft. dist. mkd.  $\frac{1}{4}$ " S19 B.T.  
24" Fir bears West 43.8 ft. dist. mkd.  $\frac{1}{4}$ " S19 CS BT.  
Road bears North 210.0 ft. distance.

FO. 2/81  
H. J. Janssen  
M26-7E  
FD 8/85  
H. J. Janssen  
M26-7E

John H. Markham, Jr.  
Done for Stomar Lumber Co.  
Witness: R. G. Boyd  
August 18, 1959  
C. S. File No. 42/392

John H. Markham, Jr.  
For Stomar Lumber Co.  
Witness: R. G. Boyd  
October 7, 1959  
C. S. File No. 42/392