

Douglas County Surveyor's Record of  
Government Corners Renewed

31 T. S. 3 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

60

1/4 Corner Sections 20 and 29.  
At Corner Point Found 25" Fir Stump & scribed Wood Post.  
I Set 1 1/4" x 36" Iron Pipe from which: **CORNER NO. 150**  
14" Cedar bears S.53°E. 37.0 ft. dist. already scribed,  
1/4 S29 CS BT.  
22" Laurel bears S.62°E. 10.0 ft. dist. mkd. 1/4 S29 B.T.  
10" Laurel bears N.67°E. 26.0 ft. dist. mkd. 1/4 S20 T31S R3W B.T.  
4" Cedar bears N.5°E. 6.5 ft. dist. mkd. 1/4 S20 B.T.  
Road bears East 70.0 feet distance.

61

1/4 Corner to Sections 7 and 18, as det. by O.B.T.'s:  
7" Laurel Snag N.20°E. 19.8 ft. O.B.T.  
At Corner Point found 20" Fir chopped out North face & found scribe, from which: **FD. OK 2/81 H. JOHNSONE M 86-42**  
16" Fir bears N.42°W. 18.0 ft. dist. mkd. 1/4 S 7 B.T.  
8" Fir bears N.14°E. 6.0 ft. dist. mkd. 1/4 S 7 X BT.  
10" Fir bears N.40°E. 13.5 ft. dist. mkd. 1/4 S18 BT.  
14" Fir bears S.86°E. 14.5 ft. dist. mkd. 1/4 S18 BT.  
Corner lies on very steep North face approx. 120 ft. South of Creek.  
Section Corner bears S.82°45'W.  
Section Corner bears Due East(20°00'Var.)

62

Section Corner to Sections 7, 8, 17, and 18, as det. by O.B.T.'s:  
11" Laurel N.27°W. 44.0 ft. dist. O.B.T., fd. scribe.  
16" Laurel N.71°E. 5.3 ft. O.B.T. I rescribed R3W S8 T31S B.T.  
12" Laurel S.53°W. 9.3 ft. O.B.T. I remarked S18 B.T.  
At Corner Point found Stone & Set 3/4" x 30" Iron Pipe from which: **FD. 2/81 H. JOHNSONE M 86-42**  
8" Chip. bears N.11°W. 27.0 ft. dist. mkd. S 7 R3W B.T.  
12" Fir bears N.53°W. 17.9 ft. dist. mkd. S 7 R3W B.T.  
14" Fir bears S.60°E. 23.7 ft. dist. mkd. S17 B.T.  
12" Laurel " S.33°E. 17.0 ft. dist. mkd. S17 T31S R3W B.T.

63

**CMO** Section Corner to Sections 16, 17, 20, and 21, as det. by O. B.T.'s:  
30" Fir ~~S.44°E.~~ 36.3 ft. O.B.T.  
42" Fir S.75°E. 54.0 ft. O.B.T. **Rec'd N 44° E Vol 18 Pg 775**  
38" Fir Stump(logged) S.11°W. 13.5 ft. O.B.T.  
11" Laurel N.69°W. 18.5 ft. O.B.T.  
I rescribed S17 T31S R3W B.T.  
At Corner Point found Stone & Set 1 1/4" x 48" Iron Pipe from which: **FD. 2/81 H. JOHNSONE M 86-42**  
12" Laurel bears S.59°W. 3.5 ft. dist. mkd. S20 R3W B.T.  
7" Cedar bears S.79°E. 8.5 ft. dist. mkd. X S21 X B.T.  
7" Cedar bears N.12°E. 38.5 ft. dist. mkd. S16 R3W B.T.

64

1/4 Corner to Sections 17 and 20.  
At Corner Point Set 1 1/4" X 40" Iron Pipe from which: **CORNER NO. #239**  
5" Cedar bears S.34°E. 7.1 ft. dist. mkd. 1/4 S20 B.T.  
11" Fir bears North 26.9 ft. dist. mkd. 1/4 S17 R3W B.T.  
12" Maple bears S.6°W. 19.2 ft. dist. mkd. 1/4 S20 B.T.  
1/4 of Ridge bears West 121.0 feet.

1/4 Corner to Sections 18 and 19, as det. by O.B.T.  
15" Fir bears S.21°E. 32.4 ft. dist. O.B.T. I chopped out and fd. scribe. **FD. 2/81 H. JOHNSONE M 86-42**  
At Corner Point Set 3/4" x 30" Iron Pipe from which:  
30" Fir bears S.38°E. 42.0 ft. dist. mkd. 1/4 S19 T31S R3W B.T.  
9" Laurel " N.50°E. 15.8 ft. dist. mkd. 1/4 S18 T31S R3W B.T.  
3" Fir bears N.34°E. 14.0 ft. dist. mkd. 1/4 S BT.  
6" Laurel " S.50°W. 8.0 ft. dist. mkd. 1/4 S19 B.T.  
Section Line running West from 1/4 Corner 18 - 19 bears S.84°30'W.

66

Section Corner to Sections 17, 18, 19, and 20, as det. by O.B.T:  
13" dead Laurel Snag bears S.30°W. 18.5 ft. O.B.T.  
At Corner Point Set 1 1/4" x 36" Iron Pipe from which: **CORNER NO. #238**  
30" Fir bears S.20°E. 17.5 ft. dist. mkd. S20 R3W B.T.  
24" Fir bears S.9°W. 15.0 ft. dist. mkd. S19 B.T.

John H. Markham, Jr.  
Witness: R. C. Boyd, O. A. Keatley  
For Stomar Lumber Co.  
Nov. 17, 1959  
C. S. File No. 42/392

**RE-RENEWED CORNER NO. #239**

**RE-RENEWED CORNER NO. #238**

(continued over)