

Douglas County Surveyor's Record of
Government Corners Renewed

T31S T. S. R. 3 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORG. 21881

(continued)

RE-RENEWED, SEE CORNER NO. #238

6" Maple bears N. 82°W. 8.0 ft. dist. mkd. S18 B.T.
8" Fir bears N. 43°E. 18.5 ft. dist. mkd. S17 T31S B.T.

67

1/4 Corner to Sections 14 & 15, as det. by O. B. T's:

34" Fir Snag S. 34°E. 9.2 ft. O.B.T.
40" Cedar N. 67°W. 31.6 ft. O.B.T.

At Corner Point found large Stone & Set 1/2" x 24" Iron Pipe from which:

4" Fir S. 72°E. 25.0 ft. mkd. 1/4 S14 B.T.
6" Fir S. 54°W. 18.6 ft. mkd. 1/4 S15 B.T.
8" Fir N. 64°W. 19.1 ft. mkd. 1/4 S15X B.T.
9" Fir N. 28°W. 33.8 ft. mkd. 1/4 S15 B.T.

68

Section Corner to Sections 10-11-14-15, as det. by O.B.T's.

40" Fir S. 41°E. 38.3 ft. O.B.T., fd. scribe
36" Fir Snag N. 60°W. 6.6 ft. O.B.T.
16" La. N. 49°E. 31.4 ft. O.B.T. - I rescribe S11 B.T.

At Corner Point found Stone & Set 1/2" x 24" Iron Pipe from which:

4" Pine S. 4°E. 21.6 ft. S14 B.T.
5" Live Oak S. 37°E. 28.0 ft. S14 B.T.
4" Chip. S. 86°W. 10.1 ft. S15 B.T.
13" La. N. 15°E. 5.6 ft. S11 B.T.

69

S. E. Corner to Section 12, as det. by O.B.T.:

50" Fir N. 71°W. 26.0 ft. O.B.T.
22" Fir Snag S. 86°W. 30.5 ft., fd. scribe.
54" Fir S. 62°E. 23.1 ft. O.B.T.

At Corner Point Found Stone & Set 1/2" x 30" Iron Pipe from which:

7" Fir S. 80°E. 13.0 ft. S18 R2W B.T.
10" Fir N. 55°E. 25.2 ft. S18 X B.T.
5" Fir N. 39°W. 11.0 ft. S12 XX BT X.

Creek bears South 35.0 ft.

S.W. Corner 7 bears North 118.0 ft. (R2W).

70

East 1/4 Corner Section 12 only, as det. by O.B.T.

28" Fir S. 63°W. 5.3 ft. O.B.T.
At Corner Point found Stone & Set 1/2" x 40" Iron Pipe from which:

8" Hemlock S. 10°N. 10.0 ft. 1/4 S12 B.T.
6" Hemlock S. 33°E. 22.0 ft. S12 B.T.
8" Hemlock N. 74°E. 16.0 ft. S12 B.T.
6" Fir N. 62°E. 7.6 ft. 1/4 S12X B.T.

71

1/4 Corner Sections 23 and 24, as det. by O. B. T.:

14" La. N. 32°W. 32.3 ft. O.B.T. I rescribed 1/4 S23 T31S R3W B.T.

At Corner Point Found Stone & Set 1/2" x 30" Iron Pipe from which:

7" La. N. 52°E. 12.0 ft. 1/4 S24 R3W B.T.
15" Pine East 7.0 ft. 1/4 S24 B.T.
8" La. S. 67°E. 11.7 ft. 1/4 S24 B.T.
7" La. S. 35°W. 5.0 ft. 1/4 S23 R3W B.T.

72

Section Corner 13 - 14 - 23 - 24, as det. by O.B.T's:

15" La. N. 67°W. 24.4 ft. O.B.T., I rescribed S14 B.T.
30" Fir S. 31°W. 37.0 ft. O.B.T.
16" Fir S. 58°E. 12.5 ft. O.B.T.
20" Fir N. 65°E. 18.5 ft. O.B.T.

At Corner Point Set 1/2" x 30" Iron Pipe from which:

11" Fir N. 8°E. 45.7 ft. S13 T31S B.T.
14" La. N. 40°W. 35.2 ft. S14 T31S R3W B.T.
4" Cedar S. 42°W. 18.2 ft. S23 B.T.

73

Section Corner 23-24-25-26, as det. by O.B.T.:

56" Fir S. 78°W. 22.4 ft. O.B.T. - 10" Hemlock N. 29°E. 25.0' OBT.
12" Hemlock S. 79°E. 15.2 ft. O.B.T.

At Corner Point Found Stone & Set 1/2" x 30" Iron Pipe from which:

11" Hemlock N. 45°W. 10.4' S23 B.T. - 7" Hem. S7W 5.2' S26 B.T.
7" Hemlock S. 67°E. 15.0 ft. S25 R3W B.T.

John H. Markham, Jr.
Witness: O. A. Keatley
R. G. Boyd
For Stomar Lumber Co.
Nov. & Dec. 1959
C. S. File No. 42/392

Fd I. P. #181
Blm Admin
SEE GIS FILE
Survey