

Douglas County Surveyor's Record of
Government Corners Renewed

31 T. S. 3 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21001

1/4 Section Corner to Sections 14 and 23 81
as determined by O. B. T.:
24" Fir S.19°W. 10.6 ft. O.B.T.
At Corner Point Set 2X30" I. P. From which:
7" Fir N.51°W. 22.6 ft. 1/4 SL4 B.T.
6" Fir S.61°W. 12.3 ft. 1/4 S23 B.T.
15" Cedar N.82°E. 9.8 ft. 1/4 SL4 B.T.

C.S. File
42/392

Section Corner to Sections 28 - 29 - 32 - 33. 82
Found - 3 Orig. BT's.: Orig. 16", now 40" Fir bears S.60°E. 33.7 ft.
Shows good scar.
Orig. 10", now 14" Fir S.30°W. 14.5 ft., shows good
scribing "31".
Orig. 16", now 24" Fir Snag Shell only N.50°E. 24.4 ft.,
shows old scar.
Set Brass Cap at Corner Mkd: County Surveyor's Office, 1960 92
S29 | S28
S32 | S33 T31S R3W
New BT's: 19" R.Fir bears N.85°E. 24.8 ft. scribed S28T31S R3WCSBT.
17" R.Fir bears N.54°W. 27.7 ft. scribed S29T31SR3WCSBT
14" R.Fir bears S. 3°E. 13.6 ft. scribed S33T31SR3WCSBT.
(SEE REN. #2 PROBABLE ERRONEOUS COR.)

James W. Byron, Deputy County Surveyor
Milo Godfrey
Clete Putnam
December 22, 1960
C. S. File No. 52/63

1/4 Section Corner to Sections 29/28. 83
Found - Both Orig. BT's:
Orig. 10", now 12" Fir N.10°E. 13.9 ft., shows good
scribing "18". 149
Orig. 30", now 34" Laurel Shell of Snag, shows scribing.
Set Brass Cap at Corner Mkd: County Surveyor's Office, 1960
1/4 S29/S28 T31S R3W.
New BT: 17" Cedar bears N.53 1/2°W. Mkd: 1/4 S29 CS BT.
50 1/2 FT - M.L.C.

Section Corner to 4 - 5 - 8 - 9. 84
as determined by O. B. T's:
30" Cedar N.37°E. 26.4 O.B.T.
30" Laurel S.36°W. 30.0 ft. O.B.T.
36" Cedar N.17°W. 41.0 ft. O.B.T., fd. scribe
At Corner Point Set 1/2" x 30" Iron Pipe from which:
52" Fir bears S.30°E. 33.3 ft. dist. mkd. S 9 T31S R3W B.T.
8" Laurel bears N.87°W. 8.8 ft. mkd. S 8 B.T.
7" Laurel bears N.37°W. 26.6 ft. dist. mkd. S 5 T31S R3W B.T. 142

John H. Markham, Jr.
For Stomar Lbr. Co.
Jan. 19, 1961
C.S. File No.
42/392

1/4 Corner to Sections 24 - 25. 85
as determined by Old BT's: 35" Fir N.54°E. 44.9 ft. O.B.T.
48" Fir uproot S.27°E. 9.9 ft. O.B.T.
All other BT's gone. #230
At Corner Point found Stone & Set 1 1/2" x 30" Iron Pipe from which:
14" Fir bears N.6°E. 19.0 ft. Mkd: 1/4 S24 BT.
14" Fir bears N.52°E. 29.5 ft. Mkd: 1/4 S24 BT.
5" Fir bears S.47°E. 20.2 ft. Mkd: 1/4 S BT.
4" Fir bears S.19°E. 18.4 ft. Mkd: 1/4 S BT.

John H. Markham, Jr.
For Stomar Lumber Co.
June 28, 1961
C. S. File No. 42/392

1/4 Corner to Sections 26 - 35. 86
as determined by O.B.T's: 16" Dead La. N. 7°E. 19.8 ft. O.B.T.
22" Fir uproot S.11°W. 21.1 ft. O.B.T.
At Corner Point found 3/4" Iron Pipe from which: REN. #23
12" Fir bears N.35°W. 50.0 ft. Mkd: 1/4 S26 BT.
11" Cedar bears S.74°W. 85.0 ftm Mkd: 1/4 S35 BT.
10" La. bears N.66°E. 46.0 ft. Mkd: 1/4 S26 T31S R3W BT.
5" Fir bears S.26°E. 52.0 ftm Mkd: 1/4 S BT. 154
North end of 18" Steel Culvert under Main road bears S.74°E. 150.0 ft.