

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 31 S. T. S. R. 3 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21681

James W. Byron, Deputy County Surveyor  
Mike Darby and Wm. Stoffel  
March & April 1963  
C. S. File No. 52/138

May, 1963 C.S.No. 52/63

Milo E. Godfrey, Deputy  
Wm. Stoffel - M. Stone - M. Darby  
May 21, 1964  
C. S. File No. 52/63

Closing Corner Sections 1, 4W. & Sec. 6, R3W. 87  
Found - Orig. 14", now 24" Maple S.67°W. 42.5 ft., shows good scribing.  
Orig. 36", now 40" Fir S.55½°E. 22.6 ft., shows scribing.  
Orig. N.E. BT., shows scar & Find Corner Stone as recorded. T30S  
Set - Brass Cap alongside Cor. Stone & Mkd: County Surveyor's CC  
R4W S 1/S 6 R3W  
Rescribe, now 24" Maple T31S S.67°W. 43.0 ft. S1 CS BT CC. T31S

Renewed Corner 88  
R4W R3W  
S36/S31 T30S  
S 1 T31S  
Found - 1" I. Bar at Corner & BT's. as recorded by Markham, 1959.  
Orig., now 13" Laurel N.16°W. 33.0 ft., bark scribed, we  
rescribe(wood) T30S R4W S36 CS BT.  
Chinquapin to N.W. now dead.

South ¼ Corner to Section 31, T30-3W. N. Bdry. T31-3W. 89  
Found - Both Orig. BT's. & Stone, all as recorded.  
Orig. 10", now 18" Fir S.58°W. 18.1 ft., shows good wear.  
Orig. 11", now 16" Fir N.56°E. 9.5 ft., shows good scribing.  
Set - Brass Cap alongside Cor. Stone & Mkd: County Surveyor's Office, 1963  
S ¼ S31 T30S R3W.

¼ Corner to Sections 22 and 23. 90  
Found - 1½" I.P. at Cor. & both BT's. as recorded by Price. Ren. #32  
22", now 24" R.Fir S.51½°W. 15.8 ft., shows scribing on badly  
burned face. N.E. BT. now stump.  
New BT's: Rescribe 24" R.Fir S.51½°W. 15.8 ft. ¼ S22 CS BT.  
7" R.Fir bears N.61½°E. 43.7 ft. scribed ¼ S23 CS BT. SEE REN. #110  
Note - Road bears North 100 feet. - SET BRASS CAP Mkd. ¼ S22/S23 -Dec. '65.  
C. S. File No. 52/63

¼ Corner to Sections 27 and 34. 91  
Found - 2" I.P. at Cor. - 40" R.Fir N.46°30'W. 5.9 ft., now down, shows scribn  
30" R.Fir, now stump, - S. W., shows scribing. Ren. #8  
New BT's: 11" R.Fir bears S.3°E. 73.8 ft. scribed ¼ S34 CS BT. 130  
6" R.Fir bears N.69°E. 33.5 ft. scribed ¼ S27 CS BT.  
C. S. 52/63

Section Corner to Secs. 28 - 29 - 32 - 33. 92  
Found - C. S. Brass Cap set in 1960. See Ren. #82.  
14" D.Fir S.30°W. 14.5 feet, scribing visible.  
14" D. Fir S. 3° E. 13.6 feet, scribing visible.  
All other Bearing Trees, both renewals & originals, are now  
uprooted & down. 158  
New BT's: 12" D.Fir N.71°W. 47.3 ft. Mkd: T31S R3W S29 CS BT.  
11" D.Fir N.25°E. 32.7 ft. Mkd: T31S R3W S28 CS BT.  
Note - Corner lies in bottom of small draw.

Section Corner to Secs. 20 - 21 - 28 - 29. 93  
Found - Rock set in 1894; No marks visible on rock.  
Dead Cedar Snag approx. 15 ft. high N.48¾°W. 29.7 ft., previously  
opened, scribing visible on old face "31 "3" & "20".  
32" Madrone S.18½°W. 19.5 ft., scar visible.  
24" Madrone N.39°E. 34.5 ft., scar visible.  
Portion of rotted Madrone Stump, with small Madrone tree growing  
from one side, S.42¾°E. 38.6 ft.  
Set - Brass Cap at Cor. Mkd: County Surveyor's T31S R3W S20 | S21  
Set Rock alongside. Office, 1964 S29 | S28  
New BT's: 16" Hemlock N.12°E. 11.2 ft. Mkd: T31S R3W S21 CS BT.  
8" D. Fir N. 7° W. 10.3 ft. Mkd: S20 CS BT.  
12" D.Fir S.77°E. 32.3 ft. Mkd: T31S R3W S28 CS BT.  
Reblaze & Scribe - 32" Madrone S.18½°W. 19.5 ft. Mkd: T31S R3W S29 CS BT.

Fd OK  
9/85  
M90.36  
By Howard  
Johnstone