

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. E. 3 W. R. W. W. M.

HOKE-CHAPMAN CO., EUGENE, ORE., 31881

Milo E. Godfrey, Deputy Co. Surv.
Wm. Stoffel and Mike Stone
July 20, 1964
C. S. File No. 52/63

Section Corner to Sections 3 - 4 - 9 - 10. 97
Found - Stone as called for in Gov't. Notes.
18" Fir Snag S.24°E. 14.5 ft., prev. opened, good scribing vis. "R3W".
38" Fir S.65½°W. 12.9 ft., shows good lower scar. Tree in good cond.
12" Fir N.49°W. 25.1 ft., slope dist., very plain scars visible,
good condition.
The 48" Fir N.27½°E. 41.2 ft., uprooted & down, scars visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's T31S R3W S 4 | S 3
Office, 1964 S 9 | S 10
New BT's: 15" I. Cedar S14°E. 37.2 ft. Mkd: T31S R3W S10 CS BT.
36" D. Fir N.22°E. 56.8 ft. Mkd: T31S R3W S 3 CS BT.

¼ Corner to Sections 9 and 10. 98
Found - Both BT's., will not check for bearings & distances as given in
field notes. I found that by reversing distances to the two trees,
both bearings check. Also facings are better this way than using
any other solution.
I. Cedar, now 30", N.33½°E. 24.4 ft. (not 19.1 ft.) prev. opened,
good scribing visible "1/2 S". Tree in good condition.
27" Cedar Snag N.43½°W. 19.1 ft. (not 24.4 ft.) prev. opened,
good scribing visible "1/2 S".
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964
T31S R3W ¼ S 9/S 10
New BT: 12" Madrone N.86½°W. 21.0 ft. Mkd: ¼ S10 CS BT.

Burton W.
Holt
Wit: H. Sohn
August 1965
C. S. File
No. 51/320

¼ Corner to Sections 6 and 7. 99
Found - Orig. 12"x9"x5" Stone marked ¼ on N. face.
Set - ½" x 39½" Iron Pipe, from which
New BT's: 9" D. Fir bears N.24½°W. 5.2 ft. mkd: ¼ S6 BT.
21" D. Fir bears S.34½°E. 15.4 ft. (from face) mkd: ¼ S7 BT.
(Both trees bark scribed.)
Note - This corner lies on steep East Slope between two small gulches.

C. E. Roberts
Sept. 1909
Recorded
F.B. #10 -
Pgs. 52 - 53

Center ¼ Corner of Section 31. 100
Set - Post for center of section, from which:
20" Pine bears N.40°30'W. 80 lks.
35" Pine bears S.24°W. 84 lks.
30" Pine bears S.77°30'E. 133 lks.
12" Fir bears N.79°E. 103 lks.

September 1909

¼ Corner to Sections 2 and 11. 101
Found - 20", now 29" Laurel S. 4° E. 74.5 ft. scribing visible.
12" Laurel, now 14" S. 25° E. 44.0 ft., scribing visible.
5" Fir, now 8", S.77°E. 47.7 ft., shows good scar.
10" Fir, now 15", N.86°W. 73.0 ft. scribed
All BT's. recorded in Ren. 48, Markham.
Set - Brass Cap at ¼ Cor. Mkd: T31S R3W ¼ S 2 | S 11 1965 Co. Surv. Office

Section Corner to Sections 1 - 2 - 11 - 12. 102
Found - I. Pipe & Stone at Sec. Corner. (Ren. #49)
8", now 9" Laurel N. 69° W. 11.7 ft. scribe visible.
8", now 11" Laurel N. 59° E. 19.4 ft., scribe visible.
8", now 10" Laurel S. 75° E. 26.0 ft., scribe visible.
8", now 9" Laurel S. 47° W. 22.0 ft. scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's T31S R3W S 2 | S 1
Office, 1965 S 11 | S 12
All BT's. renewed by Markham in good shape.

John M. Powell
F. Jones & J. Brady
December 8, 1965
C. S. File No. 52/63