

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 3 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

108

$\frac{1}{4}$ Corner to Sections 13 and 14.
Found - $\frac{3}{4}$ " Iron Pipe as base of Corner Tree. See Ren. #57
14" Fir N. 56° E. 15.8 ft. O.B.T. opened for scribe.
36" Cedar S. 13° E. 21.5 ft., scribe visible, $\frac{1}{4}$ S13 R3W BT.
12" Fir S. 74° E. 24.0 ft., bark scribed.
12" Fir, down, N. 74° W. 8.6 ft.
Set - Brass Cap at $\frac{1}{4}$ Cor. Mkd: County Surveyor's Office, 1965
T31S R3W $\frac{1}{4}$ S 14/S 13
New BT's: 12" Fir S. 72° W. 37.6 ft. scribed $\frac{1}{4}$ S14 CS BT.
As noted corner lies on top of side ridge.

109

$\frac{1}{4}$ Corner to Sections 2 and 1.
Found - $\frac{1}{2}$ " Iron Pipe at Corner, See Ren. #50.
30" Pine Snag S. 61° W. 22.8 ft. is gone.
9", now 13" Laurel S. 85° E. 25.0 ft. Scribed $\frac{1}{4}$ S1 T31SR3W BT.
12", now 13" Laurel N. 21° E. 40.5 ft., bark scribed.
20", now 21" Laurel N. 13° W. 42.0 ft., bark scribed.
9", now 14" Laurel S. 81° W. 8.0 ft., bark scribed.
Set - Brass Cap at $\frac{1}{4}$ Cor. Mkd: County Surveyor's Office, 1965
T31S R3W $\frac{1}{4}$ S 2/S 1
New BT's: 5" Fir N. 61° W. 10.4 ft., scribed $\frac{1}{4}$ S2 CS BT.
Rescribe: 21" Laurel N. 13° W. 42.0 ft., scribed $\frac{1}{4}$ S2 CS BT.

110

$\frac{1}{4}$ Corner to Sections 22 and 23.
Found - $1\frac{1}{2}$ " Iron Pipe - See Ren. #90
24" R.Fir S. $51\frac{1}{2}^{\circ}$ W. 15.8 ft. scribed $\frac{1}{4}$ S22 CS BT.
7", now 10" R.Fir N. $61\frac{1}{2}^{\circ}$ E. 43.7 ft. scribed $\frac{1}{4}$ S23 CS BT.
Set - Brass Cap at $\frac{1}{4}$ Cor. Mkd: County Surveyor's Office, 1965
(alongside I. Pipe) T31S R3W $\frac{1}{4}$ S 22/S 23
All BT's. in good shape, did not mark new BT's.

111

C. C. to Sections 3 and 2.
Found - 1" I. Pipe at C. Corner, Ren. #45.
32", now 34" Laurel S. 36° W. 15.8 ft. (O. B. T.)
32", now 32" Fir N. 18° E. 28.4 ft. (O.B.T.), Had been opened for scrib.
24" Laurel S. 67° E. 54.5 ft. (O. B. T.)
11", now 12" Fir S. 48° E. 24.6 ft., scribed S2T31SR3W BT.
12", now 15" Laurel N. 84° E. 17.2 ft., bark scribed.
12", now 14" Laurel N. 60° E. 41.0 ft., bark scribed.
6", now 9" W.Fir S. 73° W. 13.0 ft., shows good scars.
6", now 7" Fir N. 4° W. 20.0 ft., shows good scars.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1965 T30S R3W
C C S 3 / S 2
As noted corner lies about 100.0 ft. from top of ridge. T31S. R3W

112

Corner to Sections 2 and Section 1 only, T31S R3W.
Found - $\frac{1}{2}$ " I. Pipe at Sec. Cor. See Ren. #51
Orig. 14", now 18" W.Fir S. 34° W. 12.8 ft. Opened, showing scribe.
15" W.Fir, down, N. 22° E. 49.0 ft.
11" W.Fir, down, S. 35° E. 35.2 ft.
10" Chinquapin Snag S. 34° W. 34.8 ft.
15", now 17" Maple, S. 87° W. 34.8 ft., scribe visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1965 T30S R3W
S 36
S 2 / S 1
T31S R3W
New BT: 12" W.Fir N. $27\frac{1}{2}^{\circ}$ E. 85.3 ft. scribed T30S R3W S36 CS BT.

113

South $\frac{1}{4}$ Corner to Section 36 only, T30-3W.
Found - No trace of Stone - 6", now 9" Cedar N. $77\frac{1}{2}^{\circ}$ E. 19.1 ft.
Had been opened for scribe " $\frac{1}{4}$ ".
6", now 12" Fir S. $47\frac{1}{4}^{\circ}$ E. 12.5 ft., shows good scar.
Set - Brass Cap at $\frac{1}{4}$ Cor. Mkd: County Surveyor's Office, 1965
T30S R3W $\frac{1}{4}$ S 36
Both Trees Original and in good shape. No need for new BT's.

John M. Powell
Frank Jones and Joe Brady
December 1965
C. S. File No. 52/63