Douglas County Surveyor's Record of Government Corners Renewed

T. 31 S. T. S. R. 3 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21681

119

North
¼ Corner to Section 6 only, T31-3W.
Found - I. Pipe at ¼ Corner, See Ren. #78.
8" Chinq., now 9", N. 18° E. 20.0 ft. scribed ¼ S6 BT.
6" Chinq., now 7" S. 24° E. 25.0 ft. scribed ¼ S6 BT.
4" D. Fir, now 5" S. 43° E. 23.8 ft. scribed ¼ S6 BT.
Set - Brass Cap alongside Iron Pipe Mkd: County Surveyor's Office, 1966

T 30 S
¼ S 6 R3W
T 31 S

All BT's. in good condition.
Corner is at Cutting Corner.

- - - - - - - - - - - -

120

Corner to Sections 5 & 6 only, T31-3W.
Found - I. P. at Sec. Cor., See Ren. #43, T31-3W.
Orig. 30", now 30" Fir S. 64° E. 18.5 ft., shows good scar.
Orig. 10", Maple S. 33° W. 18.5 ft., partly rotted but still standing.
7" Live Oak, now 14" S. 19° W. 70.0 ft. scribed S 6 BT.
18" Fir, now 18", N. 54° E. 23.0 ft. scribed "BT S32".
16" Fir, now 18", S. 78° W. 15.0 ft., shows good scar & "BT".
Set - Brass Cap alongside I. Pipe & Mkd: County Surveyor's Office, 1966

T 30 S
S 32
T31S S 6 / S 5 R3W

All Trees in good condition. Best way to corner, walk up ravine until you come to East-West line, then East uphill.

- - - - - - - - - - - -

121

Corner to Sections 4 & 3 only, T31-3W.
Found - I. Pipe at Corner, See Ren. #40.
Orig. 16" Fir Snag S. 44° W. 4.6 ft., gone
Orig. 16" Fir N. 57° E. 27.4 ft., stump.
10" Fir, now 12", S. 59° W. 21.0 ft., good scars, parts of scribing.
6" Fir, now 8", N. 45° E. 16.0 ft., good scars.
6" Fir, now 8", S. 81° E. 26.6 ft., good scars.
Set - Brass Cap alongside I. Pipe & Mkd: County Surveyor's Office, 1965

T30S R3W
S 34
S 4 / S 3
T31S R3W

- - - - - - - - - - - -

122

Corner to Sections 5 & 4, T31-3W.
Found - I. Pipe at Sec. Cor., See Ren. #24.
8" Laurel, now 13", S. 23° W. 12.0 ft., bark scribed.
15" D. Fir, now 20" N. 11° W. 24.4 ft. (Orig. BT.) Opened, parts of scribing visible.
Set - Brass Cap alongside I. Pipe & Mkd: County Surveyor's Office, 1966

T30S R3W
S 33
S 5 / S 4
T31S R3W

New BT's: 19" D. Fir North 31.8 ft. scribed T30S R3W S33 CS BT.
13" Laurel S. 23° W. 12.0 ft. scribed T31S R3W S5 CS BT.

- - - - - - - - - - - -

123

Section Cor. to Sections 31 & 32 only, T30-3W.
Found - I. Pipe at Sec. Cor., See Ren. #82, T30-3W.
24" D. Fir S. 72° E. 29.9 ft. (Orig. BT) Tree had been opened showing faint scribing.
14" Laurel N. 88° E. 49.0 ft., bark scribed.
9" Laurel N. 58° W. 19.0 ft., bark scribed
14" Laurel S. 17° W. 26.0 ft., bark scribed T31S R3W S6 BT.
Set - Brass Cap alongside I. Pipe Mkd:

T30S R3W
S 31 / S 32
S 6
T31S R3W

Fd OK 11/88 H. Johnstone M 107-9

New BT's., rescribed:
14" Laurel S. 16°W. 27.2 ft. scribed T30S R3W S31 CS BT.
9" Laurel N. 58½°W. 19.0 ft. scribed T31S R3W S6 CS BT.

- - - - - - - - - - - -

John M. Powell
Frank Jones & Joe Brady
Dec. 1965 and January 1966
C. S. File No. 52/63