

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 31 S. T. S. R. 3 W. R. W. W. M.

HOKE-CHAPMAN CO., EUGENE, ORE. 97101

135

Sec. Cor. to Secs. 32 & 33, T31-3W. & Secs. 5 & 4, T32-3W.

Found - I. Bolt at Sec. Cor., See Ren. #3.

28" Fir, now 42", N. 72° E. 30.5 ft., shows good scar. #221

16" Fir, now 22", N. 31½° W. 63.2 ft., shows good scar,  
opened for scribing "S2".

34" Fir, now 38", S. 34° W. 34.0 ft., shows good scar.

Set - Brass Cap at Sec. Cor. Mkd: County Surveyor's Office, 1966

T31S	S 32	S 33
R3W	S 5	S 4
	T32W	

New BT: 8" D. Fir N. 64° W. 15.0 ft. scribed T31S R3W S32 CS BT.

**RE-RENEWED**

136

¼ Corner to Sections 31 and 32.

Found - 2" I. Pipe at ¼ Cor., See Ren. #4.

38" Cedar, now stump, S. 48° W. 29.7 ft., scribe visible.

12" Cedar, now 16", N. 79° E. 38.6 ft. scribed "½ SBT" visible.

Set - Brass Cap alongside I. Pipe & Mkd: County Surveyor's Office, 1966

½ S 31 / S 32

New BT: 17" Cedar S. 69° W. 51.2 ft. scribed ½ S31 CS BT.

FD. BC. & BTs  
8/9/91 G. NYGREN  
M 114-7

137

Sec. Cor. to Section 29 - 30 - 31 - 32.

Found - 1½" I. Pipe at Sec. Cor., See Ren. # 16.

36" Fir, now 46", S. 35° E. 11.8 ft., shows good scar.

12" Cedar, down, S. 75° W. 5.2 ft.

14" Cedar, now 26", N. 67½° E. 17.1 ft., part of scribng vis.

16" Fir Windfall N. 82½° W. 10.5 ft., shows good scar.

Set - Brass Cap alongside I. Pipe & Mkd: County Surveyor's Office, 1966

S 30	S 29
S 31	S 32
T31-3W	

New BT's: 15" D. Fir S. 87° W. 14.0 ft. scribed T31S R3W S31 CS BT.

13" D. Fir N. 4° W. 82.0 ft. scribed T31S R3W S30 CS BT.

FD. BK  
L. MONROE  
Doug. Co. S. Envelope  
Office 12/29/01  
C.S. 6/1/30  
FD. BC. & BTs  
AUG. 1991 G. NYGREN  
M 114-7

John M. Powell  
Frank Jones & Joe Brady  
January 1966  
C. S. File No. 52/63

138

¼ Corner to Sections 6 and 7.

Found - I. Pipe at ¼ Cor., See Ren. #99.

9" D. Fir N. 24½° W. 5.2 ft. bark scribed ¼ S6 BT.

21" D. Fir S. 34½° E. 15.4 ft., bark scribed ¼ S 7 BT.

(Distance to face on above trees)

Set - Brass Cap alongside I.P. & Mkd: County Surveyor's Office, 1966

¼	S 6
	S 7

New BT's: Reblazed & Rescribed Trees;

9" D. Fir N. 24½° W. 5.5 ft. scribed ¼ S6 CS BT.

21" D. Fir S. 34½° E. 16.5 ft. scribed ¼ S7 CS BT.

139

¼ Corner to Sec. 32, T31-3W. & Sec. 5, T32-3W.

Found - Iron Pipe at ¼ Cor. See Ren. #6.

7" Chinq., now 10", S. 47° E. 9.2 ft., opened for scribe, "BT".

10" Fir, now 14", N. 47½° W. 33.9 ft., shows good scars.  
(Dist. Should Be. 34.9 ft.)

Set - Brass Cap at Cor. alongside I.P. & Mkd: County Surveyor's Office, 1966

T 31 S	
¼	S 32
	S 5
	T 32 S
	R3W

New BT: 8" D. Fir S. 60° W. 33.0 ft. scribed ¼ S5 CS BT.

FD. BC & BTs  
8/9/91 G. NYGREN  
M 114-7

140

Township Cor. to Sec. 31, T31-3: Sec. 6, T32-3: Sec. 36, T31-4:

and Sec. 1, T32-4W.

Found - I.P. at Corner but out of ground, See Ren. No. 29.

8" Thorn, S. 77° E. 48.8 ft. scribe visible "S6 CS BT".

10" Hemlock, now 12", S. 33½° W. 185.5 ft., scribe visible.

24" Fir Stump N. 12° W. 142.0 ft.

Set - Brass Cap at Cor. Mkd:

County Surveyor's Office, 1966

	T 31 S	
R	S 36	S 31
4	S 1	S 6
W	T 32 S	W

BY R. BROWN  
4-93 M 112-72

(continued next page)