

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 31 S. T. S. R. 3 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

(continued Township Corner)

New BT's: 6" D. Fir N. 2° E. 120.3 ft. scribed S31 CS BT.  
11" Hemlock S. 75° E. 62.9 ft. scribed T32S R3W S6 CS BT.  
Note - Corner best reached by wading Cow Creek in the summer.

Sec. Cor. to Sec. 30, T31-3: Sec. 31, T31-3: Sec. 25, T31-4: Sec. 36, T31-4W.  
Found - 24" Cedar, now dead snag, S. 7° W. 20.6 ft., scribe visible.  
18" D. Fir S. 49° E. 47.5 ft., gone. *REN #19*  
20" D. Fir, now 25", N. 13½° E. 22.7 ft. Tree in slope bank of road.  
14" D. Fir, now 17", N. 13° W. 19.4 ft., shows good scar. See *Ren. #19*.  
Set - Brass Cap at Sec. cor. Mkd: County Surveyor's Office T 31 S

R S 25 | S 30 R  
4 S 36 | S 31 3  
W 1966 W

Note - This corner is on edge of new Road.  
New BT's: 19" D. Fir S. 16° E. 80.1 ft. Mkd: T31S R3W S31 CS BT  
8" D. Fir S. 83° W. 17.5 ft. Mkd: T31S R4W CS BT.

Sec. Corner to Sections 4 - 5 - 8 - 9.

Found - ½" I. Pipe, See *Ren. #84*.  
52" Fir S. 30° E. 33.3 ft., bark scribed "T31S R3W S9 BT."  
8" Laurel, now 11", N. 87° W. 8.8 ft., scribe visible "S8".  
7" Laurel, now 8", N. 37° W. 26.6 ft., bark scribed.  
Orig. 30" Cedar, now 34", N. 30° E. 26.4 ft. scribe visible.  
Orig. 30" Laurel, now 33", S. 36° W. 30.0 ft., shows scar.  
Orig. 36" now 39", N. 17° W. 41.0 ft., shows scar.

Set - Brass Cap at Sec. Cor. Mkd: County Surveyor's Office, 1966 T31S S 5 | S 4  
R3W S 8 | S 9

New BT's: Reblazed & Rescribed 39" Cedar N. 17° W. 41.0 ft.  
scribed T31S R3W S5 CS BT.

¼ Corner to Sections 5 and 8.

Found - 11" D. Fir, now 20", N. 50° E. 13.2 ft., opened tree for scribe "S".  
24" Fir snag, tree rotted out, S. 22° E. 34.6 ft.

Set - Brass Cap at ¼ Cor. Mkd: County Surveyor's Office, 1966 T31S ¼ S 5  
R3W ¼ S 8

New BT's: 10" Laurel S. 33° E. 30.4 ft. scribed ¼ S8 CS BT.  
10" Laurel N. 59½° W. 10.0 ft. scribed ¼ S5 CS BT.

Section Corner to Sections 5 - 6 - 7 - 8.

Found - Axle at Corner, See *Ren. #76*.  
7" Fir N. 50° E. 5.3 ft., shows good scars.  
6" Fir S. 47° E. 6.7 ft., shows good scars.  
20" Fir, now 22", S. 16° W. 8.8 ft., shows good scars.  
15" Fir, now 17", N. 88° W. 26.0 ft., scribe visible "BT".  
Orig. 35" Fir, now 36" N. 6° E. 60.7 ft., shows scar.  
Orig. 30" Fir, now 35", S. 37° W. 80.5 ft., shows scar.  
Orig. 18" Fir, now 22", N. 40° W. 26.7 ft., shows scar.

Set = Brass Cap alongside Axle Mkd: County Surveyor's Office, 1966 S 6 | S 5  
T31S S 7 | S 8 R3W

Did not mark new BT's. as all BT's. in good condition.

¼ Corner to Sections 4 and 3.

Found - Iron Pipe as recorded in *Ren. #75*.  
9" Laurel, now snag, S. 51° W. 14.0 ft. scribe visible, "¼ S4".  
10" Laurel, now stump, S. 16° W. 30.5 ft., scribe visible, "BT".  
30" Fir S. 2° E. 14.0 ft., scribe visible, "¼ S 3 BT", bark scribed.  
Orig. 30" Fir N. 40° E. 11.2 ft., shows good scar.  
Orig. 24" Cedar, now 25", N. 35° W. 25.7 ft., shows good scar.

Set - Brass Cap alongside Iron Pipe & Mkd: County Surveyor's Office, 1966 T31S R3W ¼ S 4/S 3

Reblazed & Rescribed - 30" Fir S. 2° E. 14.0 ft. scribed ¼ S3 CS BT.

¼ Corner to Sections 5 and 4.

Found - Stone at Corner, See *Ren. #74*.

John M. Powell  
Frank Jones & Joe Brady  
January 1966  
C. S. File No. 52/63

*RE-RENEWED, SEE CORNER NO. #245 141*  
*RE-RENEWED, SEE CORNER NO. #248 142*

141

142

143

144

145