

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 3 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

146

$\frac{1}{4}$ Corner to Sections 5 and 4.
Found - Stone at $\frac{1}{4}$ Corner, See Ren. #74.
38" Fir N. 68° W. 25.7 ft., bark scribed " $\frac{1}{4}$ S5BT".
3" Chinq., now 5", N. 61° W. 12.2 ft., scribe visible " $\frac{1}{4}$ S5 BT".
6" Laurel, now 7", N. 6° W. 5.5 ft., scribe visible " $\frac{1}{4}$ S BT".
Orig. 12" Laurel S. 72° E. 19.8 ft., bark scribed.
Orig. 16" Fir S. 15° W. 10.6 ft., shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's T31S R3W
Office, 1966 $\frac{1}{4}$ S 5/S 4

All BT's. in good condition.
Note - This corner is now cutting corner on steep, north hillside.

147

Section Corner to Sections 14 - 15 - 22 - 23.
Found - I. Pipe & Stone at Sec. Cor., See Ren. #33.
Orig. 20" Laurel, down, N. 73 $\frac{1}{2}$ ° E. 51.8 ft.
Orig. 28" D. Fir, down, N. 26 $\frac{1}{2}$ ° W. 37.6 ft.
12" D. Fir, down, S. 36 $\frac{1}{2}$ ° E. 30.4 ft.
24" Cedar, now 30" S. 4 $\frac{1}{2}$ ° W. 23.8 ft., scribe visible.
Set - Brass Cap alongside Iron Pipe Mkd: Co. Surveyor's S 15 | S 14
Office, 1966 T31S R3W S 22 | S 23

New BT's: 8" Laurel North 5.0 ft. scribed T31S R3W S15 CS BT.
7" Laurel N. 50° E. 9.7 ft. scribed T31S R3W S14 CS BT.
12" D. Fir S. 67° E. 28.6 ft. scribed T31S R3W S23 CS BT.

148

$\frac{1}{4}$ Corner to Sections 15 and 22.
Found - Iron Pipe & Stone, mkd. $\frac{1}{4}$, See Ren. #34.
Orig. 16" Laurel Snag N. 10 $\frac{3}{4}$ ° W. 29.7 ft., opened for faint
scribing, rotten, not legible.
Orig. 22" Cedar, now 27", S. 7° W. 15.8 ft., shows scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's T31S $\frac{1}{4}$ S 15
(Alongside Iron Pipe) Office, 1966 R3W $\frac{1}{4}$ S 22

Reblaze & Rescribe: 27" Cedar S. 7° W. 15.8 ft. scribed $\frac{1}{4}$ S22 CS BT.
New BT: 13" Laurel N. 46° E. 23.0 ft. scribed $\frac{1}{4}$ S15 CS BT.

149

$\frac{1}{4}$ Corner to Sections 29 and 28.
Found - Brass Cap at $\frac{1}{4}$ Corner, Co. Surv., 1960, See Ren. #83.
17" Cedar, now 19", N. 54° W. 50.4 ft. scribed $\frac{1}{4}$ S29 CS BT.
Laurel Snag N. 40° W.
10" D. Fir, now 12", N. 10° E. 13.9 ft. scribed "S 4". This
trees face had been badly cut up.
New BT: 8" Cedar N. 28° E. 15.7 ft. scribed $\frac{1}{4}$ S28 CS BT.

150

$\frac{1}{4}$ Corner to Sections 20 and 29.
Found - Iron Pipe out of ground, See Ren. #60.
14" Cedar, now 16", S. 53° E. 37.0 ft. scribe visible "BT $\frac{1}{4}$ S".
22" Laurel, S. 62° E. 10.0 ft., bark scribed.
10" Laurel, now 12", N. 67° E. 26.0 ft., bark scribed.
4" Cedar, now 7", N. 5° E. 6.5 ft., scribe visible "S".
Set - Brass Cap at $\frac{1}{4}$ Cor. Mkd: County Surveyor's T31S $\frac{1}{4}$ S 20
(Alongside Iron Pipe) Office, 1966 R3W $\frac{1}{4}$ S 29

Reblazed & Rescribed: 22" Laurel S. 62° E. 10.0 ft. scribed $\frac{1}{4}$ S29 CS BT.
12" Laurel N. 67° E. 26.0 ft. scribed $\frac{1}{4}$ S20 CS BT.

151

Section Corner to Sections 19 - 20 - 29 - 30. See Ren. #15.
Found - 13" Cedar, now 24", N. 25° E. 22.1 ft., scribing visible.
10" Fir Stump S. 54° E. 13.2 ft., fd. scribng., very rotten.
10" Laurel, now 13", S. 81° W. 23.2 ft., scribing visible.
11", now 36" Fir N. 29 $\frac{1}{2}$ ° W. 10.5 ft., shows good scar.
Set - Brass Cap at Sec. Cor. Mkd; County Surveyor's S 19 | S 20
Office, 1966 S 30 | S 29
T.31S R3W

New BT: 10" Cedar S. 10° W. 32.3 ft. scribed T31S R3W S30 CS BT.
Note - This corner lies in skid road about 800 ft. north from
Jeep Road.

John M. Powell
Frank Jones and Joe Brady
January 1966
C. S. File No. 52/63

FD. OK
9/85
BY HOWARD
JOHNSTONE
M99-36

FD. OK
9/85
BY HOWARD
JOHNSTONE
M99-36

RENEWED FILED COPY NO #252