

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 3 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21081

158

Sec. Cor. to Sections 28 - 29 - 32 - 33.
Found - 14" D. Fir S. 30° W. 14.5 ft., shows good scar, pitched over.
14" D. Fir S. 3° W. 13.6 ft., shows good scar, pitched over.
12" D. Fir N. 71° W. 47.3 ft. scribe visible "R3W S29 BT".
11" D. Fir N. 25° E. 32.7 ft. scribe visible "T31SR3WS28 CS BT".
No trace of C. S. Brass Cap set in 1960, See Ren. #92.
Set - Brass Cap at Sec. Cor. Mkd: County Surveyor's Office, 1966 T31S R3W S 29 | S 28
S 32 | S 33
All Bearing Trees in good condition.

FD. 8c 1/81
AUG. 1991
S. NYGREN
M 114-7

159

1/4 Corner to Sections 28 and 27.
Found - 16" Laurel, dead, S. 27 1/2° W. 28.5 ft.
48" Fir, now 50", N. 51° E. 40.9 ft., opened for scribe, "BT".
Set - Brass Cap at 1/4 Cor. Mkd: County Surveyor's Office, 1966 T31S R3W 1/4 S 28/S 27
New BT's: 17" D. Fir S. 78° W. 65.5 ft. scribed 1/4 S28 CS BT.
12" Pine N. 76° E. 25.4 ft. scribed 1/4 S27 CS BT.

RE-RENEWED, SEE CORNER NO. #223

160

1/4 Corner to Sections 22 and 27.
Found - Iron Pipe & Stone at 1/4 Corner, See Ren. #31.
20" D. Fir, now 24", S. 75 1/2° E. 17.9 ft., shows good scar.
12" D. Fir, now 14", N. 57° W. 2.6 ft., opened for scribe "1/4".
Set - Brass Cap at 1/4 Cor. Mkd: County Surveyor's Office, 1966 T31S R3W 1/4 S 22
S 27
New BT: 27" Laurel N. 6° W. 18.0 ft. scribed 1/4 S22 CS BT.

FD. 8c 4/81
BLM ADMIN. SURVEY
SEE GIS FILE

161

Sec. Cor. to Sections 21 - 22 - 27 - 28.
Found - Stone at Sec. Corner. Set - Brass Cap Mkd: T31S R3W S 21 | S 22
S 28 | S 27
Orig. 4" Fir, dead, N. 23 1/2° E. 14.5 ft. 1966
Orig. 15" Fir, blow down, S. 45 1/2° E. 22.4 ft.
Orig. 16" Laurel, now 24", S. 80 1/2° W. 19.1 ft. scribe visible.
Orig. 16" Fir, now 22", N. 85° W. 30.4 ft., shows good scar.
New BT's: 9" D. Fir N. 33 1/2° E. 20.0 ft. scribed T31S R3W S22 CS BT.
No other suitable trees available.

FD. 8c 4/81
BLM ADMIN. SURVEY
SEE GIS FILE

JOHN M. POWELL
Frank Jones & Joe Brady
January and February 1966
C. S. File No. 52/63

162

Sec. Cor. to Sections 15 - 16 - 21 - 22.
Found - 14X8X5 Stone at Sec. Corner.
Orig. 7" W. Fir, now 13", N. 26° E. 16.0 ft., shows good scar.
Orig. 36" Fir, now Snag, S. 34 1/2° E. 56.8 ft., shows good scar.
Orig. 10" W. Fir, now 14", S. 60° W. 11.9 ft., shows good scar.
Set - Brass Cap at Sec. Cor. Mkd: County Surveyor's Office, 1966 T31S R3W S 16 | S 15
S 21 | S 22
New BT's: 7" Pine S. 20 1/2° E. 38.4 ft. scribed T31S R3W S22 CS BT.
BT. found - 10" W. Fir, now 14", N. 16° W. 9.8 ft., opened for scribe "T31".

163

1/4 Corner to Sections 21 and 22.
Found - 15" Fir, 1/4 S on W. face, Corner Tree, opened for scribe "S".
Orig. D. Fir, blown down & out, East 16.5 ft.
Orig. 15", now 30" D. Fir S. 45 1/2° W. 14.0 ft., shows scar
low on tree.
Set - Brass Cap at 1/4 Cor. Mkd: County Surveyor's Office, 1966 T31S R3W 1/4 S 21 / S 22
New BT: 12" D. Fir N. 55° E. 33.0 ft. scribed 1/4 S22 CS BT.

164

1/4 Corner to Sections 21 and 28.
Found - 12"x12x4 Stone, 1/4 on N. face.
Orig. 12", now 20" Laurel S. 9 1/2° W. 23.1 ft., shows good scar.
Orig. 11", now 18" Laurel N. 41° E. 16.1 ft., faint scribe
visible, "BT 4", badly rotted.
Set - Brass Cap at 1/4 Cor. Mkd: County Surveyor's Office, 1966 T31S R3W 1/4 S 21
S 28
New BT's: 6" D. Fir S. 40° E. 18.5 ft. scribed 1/4 S28 CS BT.
9" D. Fir N. 10° E. 47.0 ft. scribed 1/4 S21 CS BT.