

**RE-RENEWED, SEE CORNER NO. #206**

1/4 Corner to Sections 32 and 33.  
 Found - 10" W. Fir N. 8° E. 26.4 ft. Tree down & dead, fd. scribing "1/4 S BT".  
 No trace of S. W. BT.  
 Set - Brass Cap at 1/4 Cor. Mkd: County Surveyor's Office, 1966  
 T31S R3W 1/4 S 32 / S 33  
 New BT's: 9" D. Fir S. 39° W. 13.2 ft. scribed 1/4 S32 CS BT.  
 14" D. Fir S. 28° E. 17.1 ft. scribed 1/4 S33 CS BT.

1/4 Corner to Sections 34 and 35.  
 Found - Orig. 14", now 15" Fir N. 67 1/2° W. 5.9 ft. Tree had been opened, scribe visible "S".  
 16" Fir, blow down, N. 31° E. 29.0 ft. See Ren. #22.  
 14" Fir, now Snag, N. 33° W. 17.5 ft., shows good scar.  
 Set - Brass Cap at 1/4 Cor. Mkd: County Surveyor's Office, 1966  
 T31S R3W 1/4 S 34 / S 35  
 New BT: 12" D. Fir N. 20° E. 46.0 ft. scribed

Sec. Cor. to Secs. 33 & 34, T31-3W. & Secs. 4 & 3, T32-3W.  
 Found - 1" Iron Pipe at Section Corner, See Ren. #25.  
 30", now 34" Fir S. 43° E. 15.2 ft. Opened but pitched over. Distance to the face.  
 10" Chinq., now dead, S. 26 1/2° W. 14.1 ft., scribe visible.  
 12", now 14" Fir N. 75° W. 20.7 ft., shows good scar.  
 12" Hemlock, now blow down, N. 59° E. 29.4 ft., scribe visible.  
 Set - Brass Cap at Sec. Cor. Mkd: County Surveyor's Office 1966  

T 31 S	R
S 33	S 34
S 4	S 3
W	W

 New BT's: 8" D. Fir S. 60 1/2° W. 42.9 ft. scribed T32S R3W S4 CS BT. # 32 S  
 13" D. Fir N. 35° E. 52.0 ft. scribed T31S R3W S34 CS BT.  
 Note - This corner lies on top of small side ridge in bottom of ravine.

FD OR 10/24- 1121-13

**RE-RENEWED, SEE CORNER NO. #244**

1/4 Corner to Sec. 34, T31-3W. & Sec. 3, T32-3W.  
 Found - Iron Pipe at 1/4 Corner, See Ren. #13.  
 12" Fir, now dead, N. 39 1/2° E. 18.9 ft. scribe visible "1/4".  
 10" Fir, now blow down, S. 71 1/2° E. 12.3 ft.  
 Set - Brass Cap at 1/4 Cor. Mkd: County Surveyor's Office 1966  

T 31 S	R
1/4 S 34	3
S 3	W
T 32 S	

 New BT's: 18" D. Fir N. 28° W. 23.0 ft. scribed 1/4 S34 CS BT.  
 7" W. Fir S. 71 1/2° W. 18.8 ft. scribed 1/4 S 3 CS BT.

**RE-RENEWED, SEE CORNER NO. #235**

Sec. Cor. to Secs. 34 & 35, T31-3W. & Secs. 2 & 3, T32-3W.  
 Found - 28" Hemlock, now 28", N. 38° E. 12.5 ft. Tree almost dead.  
 28" W. Fir Snag S. 31° W. 14.5 ft. scribe visible "T32S"  
 6" Hemlock, down, S. 36° E. 33.0 ft. scribe visible "S2 CS BT".  
 No trace of N. W. BT.  
 No trace of Iron Pipe as recorded in Ren. #12.  
 Set - Brass Cap at Sec. Cor. Mkd: County Surveyor's Office 1966  

T 31 S	
S 34	S 35
S 3	S 2
T 32 S	

 New BT's: 49" D. Fir West 66.3 ft. scribed T31S R3W S34 CS BT.  
 10" Hemlock S. 9° W. 27.0 ft. scribed T32SR3W S3 CS BT.  
 20" Hemlock N. 86° E. 25.2 ft. scribed T31S R3 W S35 CS BT.

**RE-RENEWED, SEE CORNER NO. #255**

Corner to Sections 13 and 24 only, T31-3W.  
 Found - 10", now 22" Fir N. 71 1/2° E. 16.5 ft. shows good scar.  
 7", now 10", Laurel S. 29° E. 16.5 ft. opened tree, rotten.  
 48", now 54" Pine S. 41 1/2° W. 16.5 ft. shows good scar.  
 8" Chinq., now down, N. 15 1/2° W. 27.1 ft., scribe visible "R3WS13".  
 Set - Brass Cap at Sec. Cor. Mkd: County Surveyor's Office, 1966  

T31S	1/4 S 13	
R3W	S 24	R2W

 New BT's: 8" Hemlock S. 32° E. 34.4 ft. scribed T31S R2W S19 CS BT.  
 7" Laurel N. 66° W. 27.1 ft. scribed T31S R3W S13 CS BT.

JOHN M. POWELL  
 Frank Jones & Joe Brady  
 January and February 1966  
 C. S. File No. 52/63