

**Douglas County Surveyor's Record of
Government Corners Renewed**

T. 31 S. T. S. R. 3 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, OR., 31881

178

$\frac{1}{4}$ Corner to Sections 8 and 17.
Found - No trace of Corner Stone.
29" Fir, now 35", N. 44° W. 18.4 ft., opened for scribe "8".
30" Fir, now 36", S. 42 $\frac{1}{2}$ ° E. 11.5 ft., shows good scar.
Set - Brass Cap at $\frac{1}{4}$ Cor. Mkd: County Surveyor's Office, 1966
T31S R3W
 $\frac{1}{4}$ $\frac{S\ 8}{S\ 17}$
New BT: 6" Laurel N. 28° E. 14.5 ft. scribed $\frac{1}{4}$ S8 CS BT.

179

$\frac{1}{4}$ Corner to Sections 8 and 9.
Found - 8" Cedar, now 20", at $\frac{1}{4}$ Corner.
40" Fir, now 47", S. 24 $\frac{1}{2}$ ° E. 22.1 ft. Opened Fir for scribe "4".
Orig. S. W. BT. not found.
Set - Brass Cap at $\frac{1}{4}$ Cor. Mkd: County Surveyor's Office, 1966
T31S R3W
 $\frac{1}{4}$ S 8 / S 9
New BT: 17" D. Fir N. 88° W. 9.8 ft. scribed $\frac{1}{4}$ S 8 CS BT.

180

Sec. Cor. to Sections 8 - 9 - 16 - 17.
Found - 28" Cedar, now 36", S. 23 $\frac{1}{2}$ ° W. 28.4 ft., burnt face & scribe visible.
28" Cedar, now 37", N. 8° E. 15.2 ft., shows good scar.
28" Cedar, now 35", S. 21° E. 38.9 ft., shows good scar.
16" Fir, now 26", N. 23 $\frac{3}{4}$ ° W. 5.9 ft., shows good scar.
No trace of Corner Stone.
Set - Brass Cap at Sec. Cor. Mkd: County Surveyor's Office, 1966
T 31 S R 3 W
S 8 | S 9
S 17 | S 16
Rescribed & Reblazed: 36" Cedar S. 23 $\frac{1}{2}$ ° W. 28.4 ft. Mkd: T31S R3W S17 CS BT.

181

$\frac{1}{4}$ Corner to Sections 16 and 21.
Found - Orig. 20" Cedar, now 36", N. 45 $\frac{1}{2}$ ° E. 20.5 ft., opened for scribe "S".
Orig. 32" Fir, now 38", S. 27 $\frac{3}{4}$ ° W. 5.3 ft., shows good scar.
Set - Brass Cap at $\frac{1}{4}$ Cor. Mkd: County Surveyor's Office, 1966
T 31 S R 3 W
 $\frac{1}{4}$ $\frac{S\ 16}{S\ 21}$
New BT: 11" Laurel North 42.3 ft. scribed $\frac{1}{4}$ S16 CS BT.
Note - This corner lies about 125.0 ft. E. of ridge top; location tag on top of ridge on N. side of Laurel.

182

$\frac{1}{4}$ Corner to Sections 16 and 17.
Found - No trace of Corner Stone.
10" Laurel, now 16", S. 69° E. 24.1 ft. Opened this tree for $\frac{1}{4}$ " done with axe. By ring count, it is done about the time of Original survey. Good distance on call from top of ridge. Also very old cruising marks around corner.
No trace of 8" Laurel N. 70° W. 29.7 ft.
Set - 5/8" Iron Rod at $\frac{1}{4}$ Corner.
New BT's: 8" Cedar N. 31° E. 11.3 ft. scribed $\frac{1}{4}$ S16 CS BT.
11" D. Fir S. 54° W. 9.0 ft. scribed $\frac{1}{4}$ S17 CS BT.

183

Sec. Cor. to Secs. 35 & 36, T31-3W. & Secs. 2 & 1, T32-3W.
Found - No trace of Corner Stone.
30" Pine, now 53", N. 42° W. 75.9 ft., scribe visible "35".
10" Laurel S. 50° W. 37.6 ft., no trace of this tree.
12" Pine, now 38", S. 12 $\frac{1}{2}$ ° E. 178.2 ft., shows scar.
14", now 31" Pine S. 31° W. 105.6 ft., scribe visible "2".
Set - Brass Cap at Sec. Cor. Mkd: County Surveyor's Office, 1966
T31S
S 35 | S 36
S 2 | S 1 R3W
New BT's: 8" Laurel S. 42° E. 26.9 ft. scribed T31S R3W S1 CS BT.
6" Laurel N. 68° E. 5.2 ft. scribed T31S R3W S36 CS BT.
Reblazed & Rescribed - 53" Pine N. 42° W. 75.9 ft. scribed T31S R3W S35 CS BT.

John M. Powell
Frank Jones - Joe Brady
Mike Stone - Jack Heritage
April 1966 - C. S. File No. 52/63