

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 3 W. R.W.W.M.

KOKS-CHAPMAN CO., EUGENE, ORE. 97101

John M. Powell
Frank Jones & T. Connell
August, 1966
C. S. File No. 54/28

1/4 Corner to Section 31 only, T31-2W.

Found - 1" I. Pipe at Corner, See Ren. #19, T31-2W.
13", now 14" Fir N. 75° E. 21.5 ft., shows good scar.
5", now 11" Hemlock S. 51° E. 7.0 ft. scribe visible "BT".

Set - Brass Cap at Cor. Mkd: County Surveyor's R T 31 S R
Office 3 1/4 S 31 2
1966 W 1/4 S 31 W

Bearing Trees all O. K., This corner is north of rock pit in small draw.

1/4 Corner of Sec. 36 only is gone. It lies in Rock Pit 435.0 ft.
South of 1/4 S 31 only.

190

S. W. Corner Sec. 31 only, T31-2W.

Found - 1" Iron Pipe at Corner, See Ren. #20, T31-2W. I.P. in good condition.
Orig. 36" D. Fir, now 40", N. 43° E. 23.0 ft.
8" Hemlock, Tree dead, S. 44° E. 28.0 ft., scribe visible, "S1" T32S".
16" D. Fir, now Snag, S. 64° E. 15.4 ft., bark scribed.
13", now 15" W. Fir N. 49° E. 45.0 ft. scribe visible.

New BT: 27" D. Fir S. 32 1/2° E. 34.7 ft. scribed T32S R2W S1 CS BT.

Note - Road bears E. 79.0 ft., however, it lies in an old unit & grown over with small alder. Best way to reach corner is by walking down same from main road.

191

MICROFILM TO HERE 10/67

192

Section Corner to Sections 1 & 12 only, T31-3W.

Found - No trace of I. Pipe, See Ren. #55, falls in skid road.

Orig. 32" D. Fir N. 24° E. 50.8 ft., shows good scar.
Orig. 29" D. Fir S. 16° E. 76.0 ft., shows good scar.
Orig. 31" Laurel N. 11° W. 25.0 ft., scribe visible.
7" Chinquapin, now 10", N. 66° E. 10.4 ft., scribe visible.
6" Hemlock, now 8", S. 33° W. 8.5 ft., scribe visible.
9" Chinquapin, now 12", N. 55° W. 15.6 ft., scribe visible.

Set - Brass Cap at Cor. Mkd: County Surveyor's R T 31 S R
Office 3 S 1 S 7 2
1970 W S 12 S 7 W

This cor. lies 215.2 ft. S. of Closing Cor. Sec.s 6 & 7, T31-2W.

3/25/70

Closing Corner to Sections 6 & 7, T31-2W.

Found - 14x10x6 Stone at corner, no marks visible.

30" Cedar, now stump, N. 49° E. 48.8 ft., scribe visible.
24", now 36" Fir, S. 69° E. 22.4 ft., shows scar.

Set - Brass Cap at Cl. Cor. Mkd: County Surveyor's R T 31 S R
Office, 1970 3 S 6 2
1970 W S 7 S 7 W

New BT: 12" W. Fir N. 7° E. 40.3 ft. mkd: T31S R2W S6 CC CS BT.

Reblzd. & Rescribed: 36" D. Fir S. 69° E. 22.4 ft. mkd: T31S R2W S7 CC CS BT.

This cor. lies 215.2 ft. N. of Sec. Cor. 1 & 12, T31-3W.

3/25/70

1/4 Corner to Section 1 only, T31-3W.

Found - Unrecorded 1" I. Pipe N. 48° W. 2.8 feet.

30" D. Fir, now Snag, S. 50° W. 17.8 ft., tree opened, burnt face.
8", now 12" Laurel, N. 41 1/2° W. 27.1 ft., opened for scribe, "S" & other marks, rotted face.

Set - Brass Cap at Cor. Mkd: County Surveyor's R T 31 S R
Office 3 1/4 S 1 2
1970 W S 1 W

New BT's: 12" D. Fir N. 12° W. 52.0 ft. mkd: 1/4 S 1 CS BT.

16" Laurel N. 87° W. 17.0 ft. mkd: 1/4 S1 CS BT.

3/25/70

1/4 Corner to Sec. 35, T31-3 and Sec. 2, T32-3

Orig. Survey by W.H. Byars, Dep. Co. Surv., 1871, Resurveyed by Wm. Bushey, 1893. No evidence found.

Set - 2"x30" galv. Iron Pipe with Brass Cap 26" in the ground

OLS 536

Scribed: 18" D. Fir "1/4 S35 BT" bears N. 46 1/2° E. T31S R3W 1/4 S35
27.7 ft. placed BT Tag. T32S 1969 S 2

Scribed: 10" D. Fir "1/4 S 2 BT" which bears S. 20° E. 45.1 ft., placed BT tag.

195

Glenn S. Baughman
For Forest Service
April 1969
C.S. 55/114
M 37 - 60