

Douglas County Surveyor's Record of
Government Corners Renewed

T 31 T. S. R 3 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

201

Section corner for Secs. 7 and 18; and Secs. 12 and 13 of T31-4.
Found - A Fir stump, 46" now 38" (barked) bears N.26 1/2°E., 47.5 ft. with well healed blaze . (O.B.T.)
28" now 30" Fir stump bears S.8°E., 85.6 ft. (Rec. 89.8 ft. possible O.B.T.) See Ren. #79 in T.31-4

I reset corner from references set April 19, 1974 by G. Langlitz attached to field notes and filed in C.S. 59/40. References intersect within 0.07 ft.

Set - A 5/8" x 30" Iron rod with 1 1/2" Alum cap set 9" below ground, marked: "Douglas Co.

R	T 31 S	R
4	12 7	3
W	13 18	W

Surveyor

Set - A 3/4" x 30" Bent iron pipe 21" in ground at edge of alum. cap, in a 24" mound of stone to top of I.P.

New BT's- A 30" Incense cedar (used to reference corner in 1974) bears N.73 3/4°W., 200.2 ft. double blazed and scribed "T31S R4W S12 C.S. BT".

A 12" D. Fir bears N.87°E., 92.4 ft. double blazed and scribed T31S R3W S7 CS BT"

A 5/8" x 30" Iron rod with 1 1/2" alum. cap set 9" above ground mkd. "Douglas Co." B.O. Surveyor" bears N.35 1/4°W., 108.27 ft. (used to reference corner in 1974)

Note: Corner lies at end of road #31-4-13 in landing of a clearcut unit. 10/27/77

202

1/4 Corner for Sec. 12 only. East boundary

Found - 1/2" Pipe with stone scribed, 1/4, laying beside it. Ren. #70

Set - 2" pipe with 3" brass cap stamped T31S R3W R2W 1/4 S12 PLS 944 1978.

From which-A 10" Hemlock bears N.74°E., 16.4 ft. scribe visible.

A 30" Cedar bears S.48°E., (Rec. S.51°E.) 45.21 ft. bark scribe visible.

A 10" Fir bears S.54°W., 25.8 ft. scribed 1/4 S12 BT.

203

SE corner for Sec. 12.

Found - 3/4" Pipe with orig. corner stone laying beside it. Ren. #69

Set - 2" pipe with 3" brass cap stamped T31S S12 S13 T31S R2W S18 R3W PLS 944 1978.

From which:A 16" Fir bears N.54°E., 25.2 ft. shows scars

A 7" Fir bears S.80°W., 21.3 ft. scribed T31S R3W S12 BT.

A rotten Fir snag bears S.86°W., 30.03 ft. BT scribe visible.

A 5 ft. Fir bears N.71 1/2°W., 25.41 ft. shows scars.

204

Section corner for Secs. 7 and 18 only - T.31-2.

Found - 1/2" Pipe and orig. corner stone. See Ren. #22 in T.31-2

Set - 2" Pipe with 3" brass cap stamped: T31S R3W S12 T31S S7 S18 CC R2W PLS 944 1978.

From which:

A 42" Fir bears N.68°E., 42.9 ft. shows scars.

A 36" Cedar bears S.45°E., 3.3 ft. scribe visible.

8/78

205

1/4 Corner for Secs. 7 and 8.

Found - A 10" x 6" x 7" stone marked "1/4".

A 9" Fir, now 10" snag bears N.20°W., 7.9 ft. with chopped out blaze visible "BT". (Rec. N.30°W.). Orig. tree.

A 10" Hemlock, now 18" bears N.46°E., 6.6 ft. wellhealed single blaze. Orig. tree.

Set - A 1" x 36" I. pipe with brass cap marked "Douglas Co. Surveyor" T31S 1/4 S7 S8 R3W 1979" at proper dist. and brg. from Hemlock and dist. from Fir. Placed stone west side of cap 8" underground.

BT's - A 19" D. Fir bears S.52 1/2°W., 16.7 ft. with double blaze scribed "1/4 S7 CS BT".

A 15" D. Fir bears S.43 1/2°E., 24.9 ft. with double blaze scribed "1/4 S8 CS BT".

A 13" Hemlock bears N.61 3/4°W., 26.0 ft. double blaze scribed "1/4 S7 CS BT".

5/22/79

R. B. Kimberling
M. W. Cline
Doug. Co. Surveyors
Office
Oct. 27, 1977'
C.S 59/40

JAN 78

Loyd R. Moffit RLS No. 944
For: Umpqua National Forest
August 1978
M 72 - 76

L-79

Ken Reed
F. Silagy
Doug. Co. Surveyors
Office
Burt Holt - Sun Studs
May 22, 1979
C.S. 60/24