

Douglas County Surveyor's Record of
Government Corners Renewed

T 31 T. S. R 3 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

206

1/4 Corner for Secs. 32 and 33.

Ren. #165

Found - Brass capped iron pipe set by County Surveyor's office in 1966 is firmly set in place & marked: County Surveyors Office T31S R3W 1/4 S32 S33 1966. This brass cap was erroneously set. Record bearing from the original remaining BT is N.80°E. This 1966 brass cap was set S.8°W. from the BT. Orig. 10" Fir, now 18" is down & decayed. Previously opened face shows scribing "S" on upper blaze & fragmentary scribing on lower blaze. Root hole for the BT is easily identifiable & bears N.80°E., 26.4 ft. from the corner point.

A depression surrounded by fir roots bears S.62°W., 18.48 ft. Nothing else remains of the SW BT.

A 14" D. Fir with double healed blazes which face the true corner location bears S.39°E., 44.9 ft.

A 10" D. Fir bears S.21°E., 32.6 ft. & has double healed blazes. The blazes on this tree do not face the true corner location. These last two BT's were set by the county surveyor in 1966.

Set - A 1" iron pipe with a 2 1/2" brass cap marked "County Surveyors Office T31S R3W 1/4 S32 S33 1979", by reference from the above described original BT evidence.

I remove all marks from 1966 brass cap & leave in place.

New BT - A 13" D. Fir bears N.7°W., 10.7 ft. scribed "1/4 S32 CS BT" on double blazes.

FO. OC: BT's
8/91 G. NYGREN
M114-7

Dennis Gaylord,
U.S.F.S.
Deputy, Doug.
County Surveyor
Office.
Witness: Tony
Flores
Sept. 20, 1979
C.S. 60/34

9/20/79

207

Section corner for Secs. 28, 27, 33 and 34.

Found - A 1" iron pipe, firmly set, projecting 12" above the ground with a 2 1/2" brass cap properly marked by County surveyor in 1966. Ren. #157

A 26" laurel with center rotted out, bears S.6°E., 21.1 ft. to face (Rec. S.10°E.) (original)

A 15" fir, with healed blaze, bears S.39°W., 17.2 ft. to face (Rec. S.35°W.) (original)

A 35" rotted sugar pine stump, with healed blaze, bears N.15°E., 63.4 ft. (Rec. 61.7 ft.)

A 22" laurel stump with scribe marks "R 3 S 28" vis. bears N.49°W., 51.8 ft.

A 22" laurel with scribe marks "S 34 BT" vis. bears S.24 1/2°E., 39.0 ft.

New BT's- A 12" D. Fir bears N.42°E., 122.1 ft. marked: "T31S R3W S27 BT" on a double blaze and nailed a brass washer, stamped "LS 536" into lower blaze.

A 8" D. fir, bears N.8°W., 68.7 ft. marked: "T31S R3W S28 BT" on a double blaze and nailed a brass washer, stamped "LS 536" into lower blaze.

Glenn S. Baughman LS #536
For: U.S. Forest Service
October, 1979
C.S. 58/176

10/79

208

1/4 Corner for Secs. 13 and 24.

Found - 1965 County Surveyor brass cap on 1" iron pipe firmly set, flush with the ground properly marked. Ren. #131

A 16" laurel, stob, with center of tree burnt out and face visible bears S.73°E., 16.5 ft. to face.

A 34" D. Fir, snag with scribe marks "4S" visible on an opened blaze, bears N.29°E., 41.6 ft.

A 11" D. Fir high cut stump, with scribe marks "1/4 S24 CS BT" visible on an open blaze bears S.86°E., 9.9 ft.

New BT's- A 6" D. fir, bears N.59°E., 29.3 ft. marked "1/4 S 13 BT" on a double blaze and nailed a brass washer stamped "LS 536" into lower blaze.

A 14" D. fir, bears S.89°W., 114.0 ft. marked "1/4 S 24 BT" on a double blaze and nailed a brass washer stamped "LS 536" into lower blaze.