

Douglas County Surveyor's Record of
Government Corners Renewed

31 T. S. 3 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

209

Terrence O. Nickerson
For: B.L.M.
October 1979
M 80 - 71

1/4 Corner Sec. 31 and Sec. 6, T.32S.,R3W.
Set - 5/8" Iron Rod 24 ins. long, 20 ins. in the ground.
BT's - A fir, 10 ins. diam., bears N.30 1/4°E., 198.0 ft.
dist., with spike at base.
A fir stump, 32 ins. diam., bears S. 12°E., 327.7 ft.
dist., with spike at base.
Note - This corner set by proportionate distance, there is
no remaining evidence of the original corner or the
perpetuation by Wenderoth and the Douglas County Ren. #381
Surveyor's Office. This area is now a cultivated
field with all trees and stump removed.

210

Section corner for SEcs. 26, 25, 35 and 36.
Found - A 1" iron pipe, firmly set, projecting 14" above the ground
with a 2 1/2" brass cap, 1966 County Surveyor properly marked
From which an original bearing tree: Ren. #177
A D. fir, 19", with scribe marks visible on a partially healed
blaze bears N.37 1/2°W., 23.4 ft. to face.
and a bearing tree marked by Wenderoth:
A D. Fir, 30", rotted stump, bears S.75°50'E., 24.0 ft. Ren. #27
and bearing trees marked by Powell:
A 28" D. Fir with scribe marks visible on a partially healed blaze
bears N.26°E., 30.0 ft.
A 18" D. Fir with scribe marks visible on a partially healed
blaze, bears S.68°W., 25.6 ft.
New BT - A 16" Cedar bears S.56°E., 106.4 ft. marked "T31S R3W S36 BT" on a
double blaze and nailed a brass washer stamped "LS 536" into
lower blaze.

211

1/4 Corner for Secs. 35 and 36.
Found - 1" I.P. firmly set, 15" above the ground, with a 1966 County
brass cap properly marked. Ren. #176
From which an original bearing tree:
A 34" D. Fir snag, with scribe marks "1/4 S35 CS BT" visible,
bears S.81°W., 20.4 ft.
and a bearing tree marked by Powell:
A 24" D. Fir, with scribe marks "14/ S35 CS BT" visible, bears
N.7°W., 75.2 ft.
New BT - A 6" D. Fir, bears S.38°E., 32.5 ft. marked "1/4 S36 BT" on a
double blaze and nailed a brass washer stamped "LS 536" into
lower blaze.

212

Section corner for Secs. 27, 26, 34 and 35.
Found - 1" I.P. firmly set, 10" above the ground with a 2 1/2" 1966
County Surveyor brass cap properly marked. Ren. #155
From which an original bearing tree:
A 28" D. Fir, with opened blaze, brars N. 39 1/2°E., 24.4 ft. to
face.
and bearing trees marked by Wenderoth: Ren. #21
A 26" D. Fir snag, with scribe marks visible, bears N.12°W., 23.4 f
A 42" D. Fir, with healed blaze, bears S.31°E., 27.3 ft. to face
A 14" D. Fir, with healed double blaze, bears S.52°W., 8.9 ft.
(Rec. 8.5 ft.)
and bearing trees marked by Powell:
A 6" D. fir stob, bears N.26°W., 19.0 ft. Ren. #155
New BT - A 12" D. fir, bears N.53°W., 35.8 ft. marked "T31S R3W S27 BT"
on a double blaze and nailed a brass washer stamped "LS 536"
into lower blaze.

213

1/4 Corner for Secs. 27 and 26
Found - A 1" iron pipe firmly set. Ren. #174
from which bearing trees marked by Thompson:
A D. fir, 16" with healed double blaze, bears S.33 1/4°W., 14.5 ft.
(Rec. 14.1 ft.)
A Twin D. fir, 16" with healed double blaze, bears N.64 3/4°E.,
18.4 ft.
Set - A 2"x32" I.P. 20" in the ground with a 3" brass cap marked:
T.31S R3W 1/4 S27 S26 1979 PLS 536.

FD. OK
3/91 M111-67

GLENN S. BAUGHMAN, PLS #536
For: U.S. Forest Service
November, 1979
C.S. 58/176