

**Douglas County Surveyor's Record of
Government Corners Renewed**

31 T. S. 3 R. W. W. M.

KOIKE-CHAPMAN CO., EUGENE, ORE. 97401

214

Romanso E. Ware
For: Roseburg Lbr.
January 1980
M 82 - 4

1/4 Corner for Secs. 15 and 16
Found - Original 30" D. Fir with scribes and possible corner stone.
Set - 5/8" Iron rod with alum. cap at record distance from Bt's 1/80

215

1/4 Corner for Sections 9 and 16
Found - Original 40" Cedar and 18" Madrone with visible scribing
Set - 5/8" Iron rod with aluminum cap at record distance.

216

1/4 Corner for Secs. 12 and 13
Found - 2 1/2 Brass Cap on 1" Galv. Iron Pipe Ren. # 106
10" Yew bears S.3°E., 35.4 ft. "1/4 S13 BT" (Record 9" S.2°E., 36.0 ft.)
12" D. Fir bears S.61°E., 25.4 ft., good scar. (Record 10" Fir S.59°E. 25.3 ft.)
18" D. Fir bears N.53 3/4°W., 4.9 ft., uproot. (Record 18" Fir, N.25°W., 7.5 ft.)
New Bt - 10" Cedar bears N.58°E., 38.5 ft., "S 1/4 S12 BT"

217

Center 1/4 Corner Sec. 12
Set - 2 1/2" Aluminum pipe, 30" long, 28" into ground, magnet under aluminum cap, mound of stones at corner.
BT's - 6" D. Fir bears N.87°30'W., 7.0 ft., "C 1/4 S12 BT"
10" D. Fir bears N37°03'E., 8.6 ft., "C 1/4 S12 BT"

218

Center 1/4 Corner Sec. 8
Set - 5/8" x 30" Iron Rod
BT's - A 12" D. Fir bears S.21°E., 20.5 feet marked "C1/4 S 8 BT".
A 15" D. Fir bears N.35°W., 29.8 feet marked "C1/4 S 8 BT".
Note: Corner lies on steep N.E. slope, 40' feet east of spring, course N.E.

219

1/4 Corner Sec. 33 only (N.)
Found: 38" D. Fir stump bears N.47°30'E., 47.5 feet "1/4" visible scribe on face.
Set: 2" x 30" Aluminum pipe with 2 1/2" magnetised cap marked
New BT'S: 18" D. Fir bears S.14°43' E., 75.4 ft. and scribed "1/4 S33 BT"
7" D. Fir bears S.46°00'W., 8.3 ft. and scribed "1/4 S33 BT".
Note: This corner re-established from original bearing tree set in 1894 by William M. Bushey.

T315 R3W
S33
PLS 866
1980

220

Center 1/4 Corner Sec. 33
Set: 2" x 30" Aluminum Pipe with 2 1/2" magnetised alum. cap marked: T315 R3W
C1/4 S33
PLS 866
1980
New BT's: 38" D. Fir bears N.14°03'W., 27.0 ft., scribed "C 1/4 S33 BT".
17" Pine bears S.36°18'W., 62.7 ft., scribed "C 1/4 S33 BT".

221

Ren. #135
~~Section~~ Corner for Sections 32,33; and Sec. 4 & 5 T. 32 S. R.3W.
Fd: 1" galvanised iron pipe with 2 1/2" brass cap stamped:
1" Iron Bolt alongside and North
42" D. Fir bears S.34°42'W., 34.5 ft. with good scar
10" D. Fir bears N. 63°20'W., 14.7 ft. with good scars
28" D. Fir bears N.32°19'W., 62.9 ft. with good scars
50" D. Fir stump bears N.72°42'E., 31.9 ft. with good scar
38" Fir snag bears S.43°46'E., 46.1 ft., 12' high and rotted
3' High Pine snag bears N.44°37'W., 44.2 ft.
New BT's: 10" D. Fir bears N.56°16'E., 62.9 ft. scribed "T31S R3W S33 BT"
7" D. Fir bears S.32°52'E., 13.3 ft. scribed "T32S R3W S4 BT".

T315
632 | 533 R
55 | 54 3
T32S
1966

William J. Ruppert LS#866
For: U.S. Forest Service
January 1980
M 79 - 20

LS# 418
Burton W. Holt
For: Suns Studs
and Rsbg. Lmbr.
March 1980
M 82 - 45

William J. Ruppert LS# 866
For: U.S. Forest Service
March 1980
M 79 - 28

FD OC - BT's
8/19 G. Nygren
Mitt-7

M 79 - 29