

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31S. T. S. R. 3W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97401

William J. Ruppert
LS #866
For: U.S. Forest
Service
April 1980
M 79 - 43 and
C.S. 58/143N

230
1/4 Corner for Secs. 24 and 25. See Ren. #85
FD. - 1 1/4" Iron pipe with 11" x 7" x 9" stone next with no apparent markings.
18" broken top D. Fir^{SNAG} bears N.01°42'E., 18.7 ft. with good sca .
20" D. Fir bears N.51°48'E., 22.1 ft., with scars.
44" D. Fir bears N.54°E., 43.5 ft. previously opened and rehea i.
12" D. Fir bears S.48°20'E., 18.9 ft. with good scar.
12" D. Fir bears S.19°51'E., 18.2 ft. with good scar.
Set - Replaced iron pipe with 2" x 30" aluminum pipe with 2 1/2" alum. cap mkd: "T31S R3W 1/4 S24 and S25 PLS 866 1980."
Buried 1 1/4" iron pipe along side of aluminum pipe.

William Ruppert
For: U. S. Forest
Service
June 1980
C.S. 58/229

FD. OK 3/91
M III - 67

231
1/4 Corner for Section 36 only. (south)
Found - 4" x 10" x 14" stone with "1/4" plainly visible on north face
45" Ponderosa Pine bears S.23°34'E., 83.8 ft. with a good scar.
Set - A 2" x 30" Alum pipe into the ground and constructed a mound of stones around it. I marked the attached 2 1/2" alum. cap as "T31S R3W 1/4 S36 PLS 866 1980".
New BT's- 26" D. Fir bears N.71°12'E., 29.8 ft. scribed "1/4 S36 BT"
26" D. Fir bears N.21°35'E., 11.5 ft. scribed "1/4 S36 BT"
with a brass washer marked "LS 866" nailed to each lower blaze.

232
S.E. corner for Section 36 only.
Found - 1" galv. I.P. with 1966 County brass cap. Ren. #189
15" Incense cedar N.40°20'E., 68.4 ft. "T32S R3W S1 CS BT" visible.
16" rotten stump S.15°56'W., 28.5 ft., two faces one face has shopped scribing visible.
31" Fir uproot N.59°24'W., 60.6 ft. hollow face.
New BT - 13" Yew N.64°24'W., 67.6 ft. scribed "T31S R3W S36 BT". Attach 3/4" brass washer marked "LS 866 to lower blaze.

William Ruppert
For: U.S. Forest
Service
May 1980
M 84 - 4
C.S. 58/143 (n)

233
S.W. section corner for Sec. 31 only of T.31-2.
Found - 1 1/2" I.P. Ren. #191
36" D. Fir, N.41°26'E., 23.1 ft. good scars
14" W. Fir, N.47°42'E., 44.5 ft. scribing partly visible.
10" Hemlock snag, S.42°50'E., 27.5 ft.
31" D. Fir, S.31°30'E., 34.3 ft. bark scribe "7 1/8" good scar.
18" D. Fir snag S.4°50'E., 15.3 ft. "S1 T32S R2W BT" visible.
Set - 2" x 30" galv. iron pipe with 2 1/2" brass cap marked PLS 866
T31S S36 R3W T31S R2W S31 CC S1 T32S R3W 1980.

234
W.C. for the East 1/4 corner for Section 36 only.
Set - 2" x 36" galv. I.P. with brass cap marked T31S WC 1/4 R3W S36 N.0°14'E., 122.79 ft. R2W PLS 866 1980".
Constructed mound of rocks around pipe.
New BT's -11" D. Fir, S.25°29'W., 62.8 ft.
13" D. Fir, S.41°05'W., 54.6 ft.
Both trees scribed "WC 1/4 S36 BT"
1/4 Corner bears N.0°14'E., 122.79 ft. from witness corner. (See Ren. #3

FD. OK 3/91
M III - 67

235
Section corner for Sections 34 and 35; and 2 & 3 of T.32-3
Found - 1966 County brass cap properly marked, firmly set, projecting 12" above ground on a 1 1/4" I.P. Ren. #169
Orig. 28" Hemlock snag, N.38°E., 12.5 ft. with opened face no marks visible.
Orig. 28" W. Fir stump, S.31°W 14.5 ft. with scribe marks "T32S" visible on decaying blaze.
A 1948 Wenderoth BT, Ren. #12, a roothole, S.36°E., 33.0 ft. with 6" Hemlock alongside with scribe marks "S2 CS BT" visible on partly healed blaze.
1966 BT by Powell, Ren. #169, a 20" Hemlock snag, N.86°E., 25.2 ft. with scribe marks "T31S R3W S35 CS BT" visible on partly healed double blaze.
A 14" Hemlock, S.9°W., 27.0 ft. with healed double blaze.
A 56" D. Fir, West, 66.3 ft. with healed blaze.
New BT's- A 14" Hemlock, N.70°E., 46.0 ft. scribed "T31S R3W S35 CS BT"
7" Hemlock, S.38 1/2°E., 45.2 ft. scribed "T32S R3W S2 CS BT"

Leonard Herzatein
U.S.F.S - Deputy
Doug. Co. Surveyors
Office
Witnesses; Rod Riley
Art Arciniega
August 14, 1980
C.S. 61/11