

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T. 31 S. T. S. R. 3 W. R. W. W. M.

MOORE-CHAPMAN CO., EUGENE, ORE. 97401

242

Leonard Herzstein, USFS  
Deputy, Doug. Co.  
Surveyor  
Tom Wolford, witness  
July 1, 1981  
C.S. 61 / 27

Sec. corner common to Sec's. 31 & 32 and Sec's. 5 & 6 of T.32S.R.3W.  
Found - 1" I.P. with Brass Cap, Renewal #134.  
firmly set, projecting 10" above ground, marked:  
County Surveyors Office T31S S31 S32 R3W S6 S5 T32S 1965,  
and a 1 3/4 " I.P. alongside.  
BT's - 36" D. Fir (Orig. BT) bears S.22°E., 59.4-ft. to face with  
scribe marks BT visible on bark blaze.  
17" D. Fir bears S12°E., 31.3-ft. with Ren. #134.  
healed double blaze.  
9" P. Pine bears S.35°W., 24.1-ft. (REC 24.6-ft.), with  
healed double blaze.  
13" P. Pine bears N.38°W., 16.7-ft. (REC 17.0-ft.), with  
healed double blaze.  
22 D. Fir stump bears N.16°W., 95.0-ft. (REC 94.0-ft.) with  
healed blaze.  
New BT - 10" P. Pine bears N.30°E., 16.6-ft. scribed T31S R3W S32  
CS BT on a double blaze.  
\*NOTE - Corner is 50-ft. East of BLM Snow Creek access Road.  
7/1/81

Larry E. Monrean  
Deputy Douglas County  
Surveyors office  
Greg Quibell and  
Terrie Plouff, witness  
Oct. 20, 1981  
C.S. 61 / 29

NE corner of Sec. 1, T.31-3 only. 243  
Found - Orig. 15" x 10" x 8", now 14" x 7" x 5" stone marked with CC  
on South face & grooves on the South, East, & West faces,  
firmly set with top flush with ground.  
BT's - Orig. 30" now 36" Fir w/good scar bears S.42 1/2 °W., 38.0-ft.,  
(Rec. 38.6-ft.).  
Orig. 10" now 21" Hemlock w/good scar bears N.18 1/2 °W., 22.2-ft.  
Set - At the exact location of the orig. stone, I set a B.C. protruding  
9" out of ground, marked: Douglas County Surveyor CC  
T30S R2W S31 T31S R3W S1 1981 (Replaced stone on So. edge of cap)  
New Accessories - Set PK nail, & scribed BT in base of Orig. 30", now  
36" Fir on downhill side of tree, bears S.39 1/2 °W., 37.1-f  
to nail.  
Set PK nail, & scribed BT in base of Orig. 10" now 21" Hemlock  
on downhill side of tree, bears N.17°W., 21.8-ft., to nail.  
Set PK nail & scribed BT in base of 32" Fir on downhill side of  
tree bears N.81°W., 31.0-ft. to nail.  
Set PK nail, & scribed BT in base of 12" Hemlock on downhill  
side of tree, bears S.19°E., 20.8-ft. to nail.  
Note - All of the BT's for this corner will be cut in future timber sale.  
10/20/81

Leonard Herzstein, USFS  
Deputy Douglas County  
Surveyors Office  
Jim Hamilton, witness  
Nov. 24, 1981  
C.S. 61 / 29

CONDITION REPORT ONLY. 244  
1/4 Corner common to Sec. 34 and Sec. 3 of T. 32-3.  
Found - 1&1/4" I.P., firmly set, projecting 8" above ground w/ properly mrkd.  
B.C. (Ren. #168), w/ 1&1/2" I.P. alongside (outside dia. Ren. #13).  
BT's - 12" Fir, now a root-hole, bears N.39 1/2 °E., 18.9-ft. (Rec.  
N.39°40'E.), with 12" D. Fir log alongside w/ fragmentary  
scribe marks visible on partly healed double blaze.  
10" Fir, now a root-hole, bears S.71 1/2 °E., 12.3-ft. (Rec.  
S.71°24'E.), with rotten log alongside w/ no marks visible.  
18" D. Fir, now 18" D. Fir bears N.28°W., Ren. #168.  
23.8-ft., with healed double blaze.  
7" W. Fir, now 9" W. Fir bears S.71 1/2 °W., 18.8-ft. with  
healed double blaze. 11/24/81

Larry E. Monrean  
Deputy Douglas County  
Surveyors Office  
J.M. Powell, witness  
C.S. 61/30

Sec. Corner common to Secs. 25 & 36 of T.31-<sup>4</sup>, and Secs. 30 & 31 245  
in T.31-3.  
Found - Orig. stone monument & post corner monuments NOT fnd. Also  
NOT fnd. is Wenderoth 1" I.P.  
Brass Cap on a 1" x 36" I.P., properly marked, laying on its  
side in a fill area. Ren. # 141.  
Note - The orig. ground in this area is covered with debris (road fill).  
BTs - As the orig. BT calls do not fit well, a distance intersect is  
used to determine the position from which the following mea-  
surements were made;  
Orig. Fir 12" now 27", bears N.9°W., 19.1-ft. (Rec. N.25°W.)  
Blaze is well healed; we open & find scribing: "S25 R4"  
From Orig. survey renewal of corner a 20" now 30" Fir with well  
healed blaze bears N.16°E., 22.8-ft. We open blaze & find  
scribing: "W 3". (CONTINUED)