

Douglas County Surveyor's Record of
Government Corners Renewed

81 T. S. 4 R. W. W. M.

Recorded by
F. C. Frear
County Sur.
Mar. 7, 1921
F.B. 109
B. 3

Set by
Frank Cain
recorded by
County Sur.
C. G. Stewart
Mar. 7, 1921
Mit. F. B. 109 P. 16
Hervey Q. Brown
Levi Spalding
Oct. 20, 1922.
(1909 - F.B. 109 P. 51)

L. Eppstein Col. Sur.
Mit.
W. S. Crear
Geo. Spain
December 23, 22, 1925.
Vol. 3 Pg 244

Ben B. Irving
Mit.
N. E. Richardson
M. H. Haskell
Ellis Bushman
Nov. 10, 1937.
e. l. 53/99

George Wenderoth
Deputy County Surveyor
Dec. 1947
C. S. File No. s
46/134
40/250B
40/29

- SECTION CORNER BETWEEN 27, 28 & 34. **SEE CORNER NO. #34 38** 1
Set galvanized Iron Pipe 1" in dia. 16" post,
from which
A Fir 60" in dia. bears N. 91° E., 55 lks.) gone
A Fir 36" in dia. bears N. 37° W., 93 lks.)
Renewed in the presence of H. Meranda, Levi Spaulding, Paddy
McGinnis and Jim McGinnis.
January 28, 1921.
- CORNER BETWEEN 28 and 33. **SEE CORNER NO. #40 7.5** 2
Set from O.B.T.s decayed but markings recognized. Set
6" x 8" x 10" boulder marked "X". Below marker is 2"
Iron Pin, also old stake marked 33.
A 38" Fir N. 143° E., 145 1/2 links
A White Fir 40" dia. N. 21 1/2° W., 168 lks. - F.B. 109, P. 16
- SECTION CORNER BETWEEN 26, 27, 34 and 35. **SEE CORNER NO. 10** 3
Set 4" x 4" x 36" Oak stakes from old B.T.s which were
all in good condition. B.T.s are
A Fir 14" dia. N. 75° E., 39 lks.
A Cedar 12" S. 40° E., 35 lks.
A Fir 40" dia. S. 35° W., 51 lks.
A Fir 16" dia. N. 62° W., 36 lks.
- CORNER BETWEEN SECTIONS 27, 28, 34 and 35. **SEE CORNER NO. 14** 4
Set 4" x 4" x 5' stake from three O.B.T.s and marked
B.T. Fir 12" N. 24° E., 20.7 ft.
Old Fir 12" N. 51° W., 9.5 ft. Mark plain on this tree.
Fir 20" dia. S. 76° 30' E., 21.3 ft.
Fir 24" dia. S. 66° 00' W., 26.5 ft.
Two old Laurels were in evidence but marking burns out.
- SECTION CORNER BETWEEN SECTIONS 27, 28, 34 and 35. **SEE CORNER NO. #7-40** 5
Located at fence corner from B.T.s as described by
County Surveyor in 1909. Both tree broken off and in
poor shape. Marked new B.T.s
A Fir 6" dia. N. 28° E., 51 lks. marked 1/4 S. 28 C.S.B.T.
A Fir 10" dia. S. 18° E., 69 lks. marked 1/4 S. 33 C.S.B.T.
- CORNER BETWEEN SECTIONS 21 and 38. 6
Set Yew Wood post 4" diameter and 36" long, 12" in
ground from B.T.s as described in Government Field notes.
One tree borken off and rotten. Post scribed S. C.S.
on E. face--S. 21 on N. face--S. 28 on S. face. New B.T.s
Fir 22" dia. N. 38° W., 51 1/2 lks. marked S. 21 C.S.B.T. 129
Fir 22" dia. S. 67 1/2° E., 58 lks. marked S. 28 C.S.B.T.
- 1/4 COR. BETWEEN 28 & 33 (Check) above #2 ##### 7
Found O. B. T. & set a 3/4" I. Pipe.
40" W. Fir bearing N 21° 30' W 110.9 ft. dist.
38" Fir bearing N 14 1/2° E 96.0 ft. dist.
8" Fir bearing N 30° 34' E 32.9 ft. dist.
10" Fir bearing S 17° 54' E 46.3 ft. dist.
(Original 1/4 cor. set in 1909 by Roberts - F. B. 10
- SEC. COR. 35-36-1-2 8
Found 4 old B. TEs.
24" Fir bearing N 32° 10' E 30.3 ft. dist.
16" Madrona bearing N 24° 54' W 20.9 ft. dist.
14" Fir bearing S 30° 50' W 13.2 ft. dist.
10" Madrona bearing S 5° 45' E 8.6 ft. dist. 121
Drove a 1" I. Pipe for the corner
marked a 14" Fir bearing S 25° E 22.7 ft. dist.
- Sec. COR. 27-28-21-22 9
Found 20" Fir bearing S 14° 30' W 20.5 ft. dist.
Drove a 1 1/2" I. Pipe for the corner with B. T's, marked
8" Yew bearing S 65° 18' E 45.9 ft. dist.
4" Hemlock bearing N 5° 30' E 53.5 ft. dist.
26" Fir bearing N 33° W 60.1 ft. dist. 135