

Douglas County Surveyor's Record of
Government Corners Renewed

31

T. S.

4

R. W. W. M.

SEC. COR. 26-27-34-35

Found B. T.'s. 26" Fir bearing N 62° W 23.7 ft. dist. REN #3
14" Fir bearing N 75° E 25.7 ft. dist.
15" Cedar bearing S 40° E 23.1 ft. dist.
Drove 1 1/4" I. Pipe for the Cor. and marked the following B. T.
10" Fir bearing N 49° 55' E 56.2 ft. dist.
9" Fir bearing S 81° 12' E 49.6 ft. dist.
8" Cedar bearing S 25° 44' W 34.3 ft. dist.

10

SEC. COR. 22-23-26-27

Found B. T. - 18" Fir bearing N 26° 30' E 28.0 ft. dist.
36" Fir bearing S 89° W 12.5 ft. dist. 112
Drove a 1" I. Pipe for the corner and set the following B. T.'s.
8" Fir bearing S 19° 17' W 24.2 ft. dist.
16" Fir bearing S 48° 30' E 14.5 ft. dist.

11

1/4 SEC. COR BETWEEN 26-27

Halfway between the Sec. Cors., Set 1" I. Pipe for the cor. 2/1966 - SEARCHED FOR, NOT FOUND - JMP. J.P.
12" Yew bearing N 66° 52' E 27.5 ft. dist.
12" Yew bearing N 61° 43' W 35.5 ft. dist.

12

1/4 COR. BETWEEN 22-27

Found both trees in good shape, Drove 1" I. Pipe for the cor. 118
20" Fir bearing N 62° E 9.9 ft. dist.
18" Fir bearing S 25° W 4.4 ft. dist.

13

SEC. COR. 27-28-33-34

Found 4 B. T.'s and set a 1" I. Pipe for the cor. REN #4
10" Fir bearing N 21° 45' E 24.7 ft. dist.
16" Fir bearing S 81° 30' E 20.0 ft. dist. 111
16" Fir bearing N 45° 26' W 9.5 ft. dist.
18" Fir bearing S 57° 04' W 35.4 ft. dist.

14

1/4 COR. BETWEEN SECS. 27-28

Set 1" I. Pipe 8" below surface of field halfway between Sec. cor. 39
Marked 30" Cedar bearing N 8° 07' W 211.2 ft. dist.
14" Ash bearing N 85° 20' E 177.5 ft. dist.

15

1/4 COR. BET. SECS. 33-34

Find both old B. T.'s. as set by Cain in 1909, one dead. (F.B. 10 Pg. 51)
40" Fir N 60° 12' W 52.1 ft.
14" Fir S 6° 06' E 54.0 ft.
Drive 1" Iron Pipe for corner. 109
~~MARKED WITH IRON PIPE~~

16

SEC. COR. 28-29-32-33

Found 3 Orig. B. T.'s., could not find trees set by Cain in 1909. (F.B. 10 Pg. 51)
16" Fir N 15° E 22.4 ft.
18" Fir N 42° W 5.8 ft.
18" Fir S 50° W 13.8 ft.
Drive 1 1/4" Iron Pipe 115
Marked 40" Fir S 13° 15' E 32.5 ft.

17

1/4 COR. BET. SECS. 28-29

Found B. T.'s. 40" Fir N 28° W 6.6 ft.
16" Fir S 75° E 32.3 ft. 113
Drove 1 1/2" I. Pipe for Corner.

18

SEC. COR. 20-21-28-29

Found B.T.'s. 20" Chin. N 58° W 9.9 ft. Burned.
36" Fir S 34° 30' E 32.6 ft. Cut.
Other trees gone.
Drive 1 1/4" I. Pipe. 114
Scribe 18" Fir N 31° 45' E 13.1
18" Fir S 53° 23' E 49.0
28" Fir S 30° 40' W 27.4
9" Fir N 58° 00' W 30.0

19

George Wenderoth - Deputy County Surveyor
December 1947
C. S. File No. 40/29.
M 4-75

G. J. Wenderoth
Deputy County Surveyor
F. Loso - Witness
March 1949

G. J. Wenderoth
Deputy County Surveyor
F. Loso - Witness
November, 1949

March 1949

C.S. 40/245