

Douglas County Surveyor's Record of
Government Corners Renewed

31 T. S. 4 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

Surv. - John Markham
Wit. - McAllister

D ec. 1949
C. S. 40/232

1/4 SEC. COR. 30-31
Determined from O. B. T.'s. 13" Fir bearing S 45° W 8.0 ft.,
scribed legible, and a 16" Fir bearing N 23° E 21.0 ft.,
remarked S 30 1/4 S. 142
At corner point set 3/4" x 40" I.P. 24" in ground.

20

Surv. - G. Wenderoth
Wit. - F. Loso
April, 1950

C. S. File No. 40/250B

CORNER 32-33-4-5 (N CORNER 4 & 5, T32S, R4W. & S. corner 32 & 33, T31S, R4W.)
Found B.T.'s. 48" Fir S 51°15' E 84.5
30" B. Oak S 75° W 32.3
Drive 1" I. Pipe for Corner.
Scribe - 14" Fir N 45°15' W 33.1
10" Maple N 39°25' E 50.3

21

Surv. - John Markham
Wit. - Geo. Vaughn
Bill Vaughn
April 14, 1951

C. S. 40/232
FOR STOMAR LBR.

S. E. COR. SEC. 33 (cor. to secs. 33 & 34, T31S, R4W., and secs. 3 & 4, T32S, R4W.)
At corner point set 1" x 24" iron pipe
All of the following are O.B.T.'s which I remarked:
A Fir 20 in. diam. bears N 44° W, 27.0 ft. dist.
An Ash 9 in. diam. bears S 80° E, 19.3 ft. dist.
A Fir 10 in. diam. bears S 48° E, 4.6 ft. dist.
A Fir 40 in. diam. bears East 21.5 ft. dist. This O.B.T. was
already marked S 34, R 4 W, W 31 S, B.T. The notes
call for this tree to bear N 80° E, the distance was correct. #98

22

Eng. - J. H. Markham, Jr.
Wit. - Geo. Vaughn
Bill Vaughn
May 20, 1951

C. S. 40/232

SEC. COR. 9 - 10 - 15 - 16
Determined by O.B.T.
A Fir 12 in. dia. bears N 66° E, 23.0 ft. dist. O.B.T. 148
A Fir 50 in. dia. bears S 57° W, 11.0 ft. dist. O.B.T.
At corner point found two wood stakes together and drove 1" x 30" I.P.

23

Eng. - J. H. Markham
Wit. - Geo. Vaughn
6-6-51

Markham, Eng.
Vaughn, Wit.
8-16-51

C. S. 40/232
For Stomar Lbr. Co.

1/4 SEC. COR. 9 - 16
Determined by O.B.T.
A Fir Stump 40 in. dia. (logged) bears S 11° E, 26.0 ft. dist. O.B.T.
At corner point set 1" x 30" I.P.
I marked no new trees since Sec. 16 is logged and Sec. 9 is being
logged now.

24

1/4 SEC. COR. 8 - 9
Determined by O.B.T.
A Fir 36 in. dia. bears S 43° E 17.0 ft. dist. O.B.T. #139
A Fir 30 in. dia. bears N 53° W 10.0 ft. dist. O.B.T.
At cor. pt. found 24 in. Fir marked on West face.
I remarked all O.B.T.'s

25

1/4 SECTION CORNER BETWEEN 4 and 9.
As set by proportional measurement.
At corner point set 3/4" x 35" Iron Pipe from which:
A Fir 33" diameter bears S. 61° E., 28.5 ft. distant marked #160
1/4 S 9, B.T.
A Fir 36" Diameter bears N. 21° E. 9.5 ft. distant marked
1/4 S. 4, T 31 S, R 4 W, B.T.
Logging road bears West, 206.0 ft. distant.

26

RE-RENEWED, SEE CORNER NO.