

Douglas County Surveyor's Record of
Government Corners Renewed

31

T. S.

4

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

George J.
Wenderoth
1956.
C. S. File
No. 47/138.

$\frac{1}{4}$ corner to secs. 27 and 34. ^{REN #1} **SEE CORNER NO. 38** 34
 $1\frac{1}{2}$ inch iron pipe. (found). Also found old Witness tree.
From which:
16 inch Yew fence corner post, S.85°37'E., 37.2 feet.
12 inch Fir, N.28°W., 64.3 feet.

Geo. J. Wenderoth
1947
C. S. File No.
40/29.

Center $\frac{1}{4}$ corner to section 27. 35
Location for corner established by intersection of the N-S and E-W
centerlines.
Set a 1 inch iron pipe at corner point.
Marked two bearing trees:
18 inch W. Fir, N.37°04'W., 57.8 feet.
14 inch Fir, S. 65°40'W., 49.0 feet.

George J. Wenderoth
1949.
C. S. File No. 40/250B

$\frac{1}{4}$ corner to secs. 32 & 33. 36
Set 1 inch I. Pipe at corner.
From which:
16 inch Fir, S.14°30'E., 4.3 feet.
16 inch Fir, S.85°30'W., 21.2 feet.

Center $\frac{1}{4}$ corner to section 33. 36-A
Found old corner set by Cain. (F.B. 10 Pg 51)
Set $\frac{1}{2}$ inch iron pipe at corner point.
Marked two B. T.s:
6 inch Fir, S.74°10'W., 133.0 feet.
10 inch Pine, N.8°25'W., 76.7 feet.

County Surveyor's Office
April 11, 1957
C. S. File No. 47/175.

Closing corner to sec. 6, T31S, R4W., and sec. 31, T30S, R4W. 37
Found trees to Northeast and Southeast alive and in good condition showing
good scars. The Pine to the Southwest has been cut but stump still in
place. Chopped out pine stump and found old face with traces of scribe
marks. Face is charred and has evidently been burned, destroying most
of the scribe marks. At intersection of distances from B.T.s and stump,
found bearings to agree with Government field notes.
Set a 1 inch iron pipe with brass cap marked:

County Surveyor's

	CC	
T30S	T30S	
R5W	S 31	R4W
S 36	S 6	
	T31S	

Office
1957

Mark one new BT:
10 inch Madrone, N.50°W., 21.2 feet, scribed T 30 S, R 5 W., S 36 CSBT.

James W. Byron
For Douglas County
Cow Creek Rd. No. 36
Dec., 1956, Jan., 1957
Ed. File Dr. 48/ Rd. 36

$\frac{1}{4}$ Section Corner to Sections 27 & 34. 38
Note - This corner renewed by Wenderoth, 1956. ^{REN #34} Corner on fill slope
of new County Road Construction.
Set Brass Cap at corner using Wenderoth's bearings & distances. 119
16" Ewewood Corner Gate Post scribed $\frac{1}{4}$ S CS BT S.87°37'E. 37.2 ft.
12" R. Fir N.28°W. 64.3 ft. scribed $\frac{1}{4}$ S27 CS BT.
Marked Brass Cap $\frac{27}{34}$ $\frac{1}{4}$ Corner T31S R4W. County Surveyor's Office,
1956. Dec. 6, 1956

$\frac{1}{4}$ Section Corner to Sections 27 & 28. 39
Found - 14" Ash as renewed by Wenderoth, 1949, ^{REN #15} N.85°20'E. 177.5 ft.
Good Condition.
The 30" Cedar N.8°07'W. is gone. Also found 1" I.P. 8" Under.
Blazed & Scribed 6.3 ft. W.O. N.34 $\frac{1}{2}$ °W. 408.0 ft. $\frac{1}{4}$ S28 CS BT. 110
Jan. 8, 1957

$\frac{1}{4}$ Section Corner to Sections 28 & 33.