

Douglas County Surveyor's Record of
Government Corners Renewed

31 T. S. 4 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

John H. Markham, Jr.
Stomar Lbr. Co.
Oct. 2, 1958
C. S. File No. 42/391

$\frac{1}{4}$ Section Corner to Sections 13 & 24. 46
As Det. by O.B.T.'s: 30" Fir S.25°E. 13.2 ft. dist. O.B.T.
16" Fir N.18°E. 11.5 ft. dist. O.B.T.
I rescribe $\frac{1}{4}$ S13 B.T.
At Corner Point Found Stone & Set 1"x 30" Iron Pipe from which:
17" Fir bears S.78°E. 9.6 ft. dist. mkd: $\frac{1}{4}$ S24 B.T.
7" Maple bears N.16°E. 54.4 ft. dist. mkd. $\frac{1}{4}$ S13 B.T.
Creek bears West 516.0 ft. distance.

$\frac{1}{4}$ Section Corner to Sections 16 & 21. 47
as determined by O.B.T.:
20" Fir Stump bears N.38 $\frac{1}{2}$ °E. 22.0 ft. O.B.T.
22" Fir Snag bears S.29°W. 29.0 ft. O.B.T.
At Corner Point Set 40" Steel Fence Post, from which:
26" Fir bears N.69°W. 67.0 ft. dist. mkd., $\frac{1}{4}$ S16 B.T.
16" Fir bears N.5°E. 213.0 ft. dist. mkd., $\frac{1}{4}$ S16 B.T.
Road bears N.45°W. 135.0 ft. dist.

$\frac{1}{4}$ Section Corner to Sections 24 & 25, 48
as determined by O.B.T.'s:
10" Fir bears S.11°W. 6.1 ft. O.B.T., fd. scribe.
13" Fir bears N.87°E. 23.5 ft. O.B.T.
At Corner Point found Stone and Set 1" x 30" Iron Pipe, from which:
11" Laurel bears N.51°W. 18.2 ft. dist. mkd., $\frac{1}{4}$ S24 B.T.
12" Cedar bears S.53°E. 37.5 ft. dist. mkd., $\frac{1}{4}$ S25 B.T.
Road bears South 28.0 ft. distance.

Section Corner to Sections 23, 24, 25, & 26. 49
as determined by O.B.T.'s:
24" Fir Snag bears S.32°E. 21.5 ft. O.B.T., found scribe.
36" Fir Snag bears N.80 $\frac{1}{2}$ °E. 26.0 ft. O.B.T.
21" Fir Snag bears S.63°W. 38.3 ft. O.B.T.
30" Fir Snag bears N.71 $\frac{1}{2}$ °W. 45.0 ft. O.B.T.
At Corner Point Set 40" long Steel Fence Post, from which:
6" Fir bears N.50°E. 20.0 ft. dist. mkd., S24 B.T.
8" Maple " S.79°E. 135.0 ft. dist. on slope, mkd. S25 R4W B.T.
6" Fir bears N.65°E. 20.6 ft. dist. mkd., S24 X B.T.
4" Fir bears S.30°E. 10.0 ft. dist. mkd., S25 B.T.
Road bears East 290.0 ft.

$\frac{1}{4}$ Section Corner to Sections 23 & 24. 50
as determined by O.B.T.'s.:
52" Fir bears N.56°E. 23.2 ft. O.B.T.
12" Fir bears N.88°W. 7.3 ft. dist. O.B.T. I rescribed $\frac{1}{4}$ S3X B.T.
At Corner Point found Stone and Set $\frac{1}{2}$ " x 24" Iron Pipe, from which:
22" Maple bears S.57°W. 66.0 ft. dist. mkd. $\frac{1}{4}$ S23 B.T.
32" Fir bears S.72°E. 36.5 ft. dist. mkd. $\frac{1}{4}$ S24 B.T.
Creek bears East 100.0 ft.

Center of Section 24. 51
At Corner Point Set $\frac{3}{4}$ " x 40" Iron Pipe from which:
15" Fir bears N.12°E. 4.6 ft. dist. mkd. $\frac{1}{4}$ S24 C.C. B.T.
6" Yew bears S.47°E. 27.0 ft. dist. mkd. $\frac{1}{4}$ S C.C. B.T.

1/16 Corner S.W. Section 24. 52
At Corner Point Set $\frac{1}{2}$ " x 24" Iron Pipe from which:
40" Fir bears S. 1°#. 35.0 ft. dist. mkd. 1/16 S24 B.T.
40" Fir bears S.29°W. 42.0 ft. dist. mkd. 1/16 S24 B.T.
West $\frac{1}{4}$ Corner Section 24 bears West 1313.0 ft.

John H. Markham, Jr.
Witness R. G. Boyd
For Stomar Lumber Co.
October 16, 1958
C. S. File No. 42/391

John H. Markham, Jr.
Witness: R. G. Boyd
For Stomar Lumber Co.
October 29, 1958
C. S. File No. 42/391