

Douglas County Surveyor's Record of  
Government Corners Renewed

31 T. S. 4 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

53

$\frac{1}{4}$  Section Corner to Sections 13 & 14.

as determined by O.B.T.'s.

20" Cedar bears S.45°W. 15.2 ft. dist. O.B.T., fd. scribe.

20" Fir bears N.21°E. 32.3 ft. dist. O.B.T., I bark scribed  
 $\frac{1}{4}$  S13 B.T.

At Corner Point fd. 10"x 10" Quartz Stone & Set  $\frac{3}{4}$ " x 30" Iron Pipe  
from which:

6" Fir bears S.54°W. 17.2 ft. dist. mkd.  $\frac{1}{4}$  S14 B.T.

9" Fir bears S.38°E. 22.0 ft. dist. mkd.  $\frac{1}{4}$  S14 B.T.

6" La. bears N.22 $\frac{1}{2}$ °E. 27.0 ft. dist. mkd.  $\frac{1}{4}$  S13 B.T.

John H. Markham, Jr.  
For Stomar Lbr. Co.  
Dec. 16, 1958  
C.S. File No. 42/391

54

$\frac{1}{4}$  Corner to Sections 10 - 11.

as determined by O.B.T.'s.

12" Fir Snag bears N.18°E. 14.5 ft. dist. O.B.T., found scribe.

30" Fir Snag bears S.47°W. 15.5 ft. O.B.T.

At Corner Point Set  $\frac{3}{4}$ " x 30" Iron Pipe from which:

7" La. bears S.26°W. 32.0 ft. dist. mkd.  $\frac{1}{4}$  S10 X X B.T.

6" La. bears S.41°E. 33.2 ft. dist. mkd.  $\frac{1}{4}$  S11 T31S R4W B.T.

6" La. bears N.66°W. 32.0 ft. dist. mkd.  $\frac{1}{4}$  S11 X B.T.

Corner Lies on very steep West face or Rock Slide in old burn.

55

Section Corner to Sections 10, 11, 14, & 15.

as determined by O.B.T.'s.

30" Fir bears S.22°E. 18.0 ft. dist. O.B.T.

28" Fir bears S.48°W. 42.6 ft. dist. O.B.T.

At Corner Point found Stone & Set  $\frac{3}{4}$ " x 30" Iron Pipe from which:

16" Yew bears S.57°W. 42.5 ft. dist. mkd. S15 B.T.

16" Fir bears S.72°W. 39.5 ft. dist. mkd. S15 B.T.

8 8" Yew bears East 40.3 ft. distance mkd. S14 B.T.

26" Fir bears N.74°E. 38.0 ft. dist. mkd. X S11 X B.T.

Creek bears East 115.0 ft. distance.

Creek bears North 56.0 ft. distance.

John H. Markham, Jr.  
Witness: R. G. Boyd  
For Stomar Lumber Co.  
February-March, 1959  
C. S. File 42/391

56

$\frac{1}{4}$  Section Corner to Sections 14 & 15.

as determined by O.B.T.'s.

15" Fir bears S.34°E. 32.0 ft. O.B.T.

At Corner Point found Stone & Set  $\frac{3}{4}$ " x 30" Iron Pipe, from which:

13" La. bears N.22°E. 20.0 ft. dist. mkd.  $\frac{1}{4}$  S14 B.T.

16" Cedar " N.48°W. 41.5 ft. dist. mkd.  $\frac{1}{4}$  S15 X B.T.

50" Fir bears S. 6°W. 39.0 ft. dist., bark scribe,  $\frac{1}{4}$  S15 B.T.

57

N.W. Corner Section 1.

as determined by O.B.T.'s.

10" Maple Snag bears S.45°E. 16.1 ft. O. B.T.

36" Fir bears S.72°W. 10.6 ft. O.B.T.

34" Fir bears N.69°E. 34.3 ft. dist. O.B.T.

At Corner Point Set  $\frac{3}{4}$ " x 30" Iron Pipe from which:

9" La. bears N.89°E. 21.5 ft. dist. mkd. S1 T31S R4W B.T.

12" La. bears N.54°E. 34.0 ft. dist. mkd. S35 T30S R4W B.T.

5" La. bears N.69°W. 16.1 ft. dist. mkd. S35 B.T.

C. C. Section 35/36 bears East 344.0 ft.

58

N.W. Corner Section 2.

as determined by O.B.T.'s.

48" Cedar Uproot bears N.47°E. 22.4 ft. dist. O.B.T. #107

18" La. Snag bears S.36°E. 27.7 ft. O.B.T. 108

26" Fir bears S.14°W. 44.2 ft. dist., O.B.T., fd. scribe.

At Corner Point found Stone & Set  $\frac{3}{4}$ " x 30" Iron Rod from which:

9" La. bears N.50°E. 43.0 ft. dist, mkd, S34 T30S R4W B.T.

7" La. bears N.64°E. 38.4 ft. dist. mkd. S34 R4W B.T.

7" Chip. " S.63°E. 43.5 ft. dist. mkd. S 2 X B.T.

14" Chip. " S.73°W. 37.5 ft. mkd. S 3 T31S B.T.

Section Corner 34/35 bears East 198.0 ft.