

Douglas County Surveyor's Record of
Government Corners Renewed

31 T. S. 4 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21001

John H. Markham, Jr.
Witness: R. G. Boyd
For Stomar Lumber Co.
April 28, 1959
C. S. File No. 42/391

N. E. Corner Section 24, as determined by O.B.T.'s.
20" Fir bears N.24°E. 3.6 ft. dist. O.B.T.
36" Fir bears S.58°E. 43.5 ft. dist. O.B.T.
30" Fir S.12°W. 28.0 ft. dist. O.B.T.
30" Fir N.46°W. 15.3 ft. dist. O.B.T.
At Corner Point Set $\frac{3}{4}$ " x 30" Iron Pipe from which:
7" Fir bears S.7°W. 22.7 ft. dist. mkd. S24 R4W B.T.
16" Fir bears North 22.8°E. 22.7 ft. dist. mkd. S13 T31S R4W B.T.
12" Fir bears N.62°E. 22.0 ft. dist. mkd. S18 R3W B.T.

RE-RENEWED CORNER NO. #166

East $\frac{1}{4}$ Corner Section 24.
At MidPoint Set $\frac{5}{8}$ " x 30" Iron Rod from which:
7" La. bears S.45°E. 18.5 ft. dist. mkd. $\frac{1}{4}$ S19 T31S R3W B.T.
10" Fir bears S.75°E. 9.3 ft. dist. mkd. $\frac{1}{4}$ S19 X B.T.
5" Fir bears N.58°W. 12.5 ft. dist. mkd. $\frac{1}{4}$ S24 B.T.
5" La. bears West 20.3 ft. dist. mkd. $\frac{1}{4}$ S24 T31S B.T.
Road bears North 340.0 ft.

S. E. Corner Section 24.
As determined by O. B.T.'s.:
40" Fir Snag bears N.40°E. 6.6 ft. O.B.T., fd. scribe.
25" Cedar bears S.47°W. 15.5 ft. O.B.T., fd. scribe.
At Corner Point found Stone and Set $\frac{3}{4}$ " x 30" Iron Pipe from which:
12" Cedar bears N.24°E. 50.0 ft. dist. mkd. S19 T31S R3W B.T.
4" La. bears S.42°E. 32.0 ft. dist. mkd. S30 T31S R3W B.T.
15" Fir bears S.67°W. 10.8 ft. dist. mkd. S25 X B.T.
12" Yew bears N.85°W. 41.8 ft. dist. mkd. S24 T31S B.T.
Creek bears South 82.0 ft.

Section Corner to Sections 1, 2, 11, & 12.
as determined by O. B. T.'s:
40" Fir N.27°E. 41.0 ft. O.B.T., fd. scribe.
Laurel Stump S.84°E. 12.5 ft. O.B.T.
Laurel Stump S.20°W. 6.3 ft. O.B.T.
At Corner Point Found Stone & Set $\frac{1}{4}$ " x 36" Truck Axle from which:
3" Laurel bears N.17°E. 12.7 ft. dist. mkd. S1 T31S R4W B.T.
4" Laurel bears S.77°E. 11.5 ft. dist. mkd. S12 T31S R4W B.T.
3" Laurel bears S.17°W. 6.8 ft. dist. mkd. S11 T31S R4W B.T.
5" Laurel bears N.83°W. 16.2 ft. dist. mkd. S2 T31S R4W B.T.
Small Draw bears East 50.0 feet.

$\frac{1}{4}$ Section Corner to Sections 2 & 11.
as determined by O.B.T.'s:
16" Fir S.69°W. 11.6 ft. O.B.T., fd. scribe.
At Corner Point found Stone & Set $\frac{1}{4}$ " x 36" Truck Axle from which:
7" Laurel bears N.56°E. 17.5 ft. dist. mkd. $\frac{1}{4}$ S2 R4W B.T.
5" Laurel bears N.28°W. 8.3 ft. dist. mkd. $\frac{1}{4}$ S2 T31S B.T.
14" Live Oak " N.67°W. 25.0 ft. dist. mkd. $\frac{1}{4}$ S2 B.T.
11" Laurel bears S.33°W. 24.1 ft. dist. mkd. $\frac{1}{4}$ S11 R4W B.T.

$\frac{1}{4}$ Section Corner to Sections 1 & 2.
as determined by O.B.T.'s:
10" Maple S.88°W. 51.5 ft. O.B.T., fd. scribe.
10" Maple N.47°E. 19.2 ft. O.B.T., fd. scribe.
At Corner Found 60" Fir mkd. on West Face & Set $\frac{2}{4}$ " x 30" Iron Pipe from which:
3" Hemlock bears S.44°E. 33.1 ft. dist. mkd. $\frac{1}{4}$ S1 B.T.
48" Fir bears S.41°E. 35.2 ft. dist. mkd. $\frac{1}{4}$ S1 R4W B.T.
6" Hemlock bears S.63°E. 44.0 ft. dist. mkd. $\frac{1}{4}$ S1 B.T.
12" Maple bears N.39°W. 43.0 ft. dist. mkd. $\frac{1}{4}$ S2 B.T.
Creek bears North 60.0 feet, distance.

John H. Markham, Jr.
Witness: R. G. Boyd
For Stomar Lumber Co.
May 13, 1959
C.S File No. 42/391

59

60

61

62

63

64