

Douglas County Surveyor's Record of  
Government Corners Renewed

31

T. S.

4

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

(continued)

3" Hemlock bears S.62°W. 14.2 ft. dist. mkd. S17 B.T.  
3" Maple bears S.37°E. 8.5 ft. dist. mkd. S16 B.T.  
Creek bears North 95.0 feet distance.

1/4 Section Corner to Sections 10 and 15, as determined by O. B.T.'s: 74

30" Fir bears N.17°E. 27.0 ft., O. B. T.  
24" Fir bears S.82°W. 30.2 ft., O. B. T.

At Corner Point Set Stone & Iron Bolt 1/2" x 20" from which:

20" Fir bears S.10°W. 60.0 ft. dist. mkd. 1/4 S15 B.T.  
8" La. bears N.55°W. 23.5 ft. dist. mkd. 1/4 S10 B.T.  
7" La. bears N.45°W. 40.6 ft. dist. mkd. 1/4 S10 T31S R4W B.T.  
5" La. bears N. 9°E. 24.3 ft. dist. mkd. 1/4 S B.T.

Top of Ridge bears East 165.0 feet.

1/4 Section Corner to Sections 9 and 10, as determined by O. B. T.'s: 75

18" La. bears N.16°E. 26.4 ft. dist., O. B.T., fd. scribe.  
9" La. bears N.47°W. 17.8 ft. dist., O. B.T., I rescribed  
1/4 S 9 B.T.

At Corner Point found Stone & Set 3" x 24" Iron Pipe from which:

18" Laurel bears N.79°W. 35.0 ft. dist. mkd. 1/4 S 9 X B.T.  
14" Laurel bears N.15°W. 32.5 ft. dist. mkd. 1/4 S 9 B.T.  
12" Laurel bears N.76°E. 30.0 ft. dist. mkd. 1/4 S10 B.T.  
9" Laurel bears S.26°W. 8.0 ft. dist. mkd. 1/4 S 9 T31S R4W B.T.

S. W. Corner of Section 6, as determined by O. B. T.'s: 76

34" Fir bears N.86°E. 168.3 ft., O. B. T.

At Corner Point found Stone & Set 1" x 50" Drill Steel from which:

5" Laurel bears S.15°W. 5.8 ft. mkd. S 7 T31S R4W B.T.  
4" Laurel bears N.22°E. 12.2 ft. mkd. S 6 T31S B.T.  
4" Fir bears N. 1°E. 16.9 ft. mkd. S 6 B.T.  
4" Laurel bears N.44°W. 8.8 ft. mkd. S 1 T31S R5W.B.T.

1/4 Section Corner to Sections 6 and 7, as determined by O.B.T. 77

18" Fir bears N.51°W. 21.1 ft. dist., O.B.T., fd. scribe.

At Corner Point, Set 1 1/4" x 30" Truck Axle with flange up, from which:

3" Fir bears S.64°E. 21.0 ft. dist. mkd. 1/4 S 7 B.T.  
14" La. bears S.51°E. 64.0 ft. dist. mkd. 1/4 S 7 T31S R4W B.T.  
9" La. bears S.14°W. 74.0 ft. dist. mkd. 1/4 S T31S B.T.  
7" Chip. " S.31°W. 75.0 ft. dist. mkd. 1/4 S 7 B.T.

Road on top of Main Ridge bears West 52.0 feet distance.

1 Corner Sections 12 and 13, as det. by O. B. T.: 78

15" Fir bears N.53°W. 25.0 ft., found scribe O.B.T.

At Corner Point Set 3" x 30" Iron Pipe from which:

5" Laurel bears N.67°E. 23.0 ft. dist. mkd. 1/4 S12 B.T.  
14" Laurel bears S.17°W. 27.0 ft. dist. mkd. 1/4 S13 T31S R4W B.T.  
16" Fir bears S.45°W. 44.0 ft. dist. mkd. 1/4 S13 B.T.

Corner lies in Small Draw.

N. E. Corner Section 13, as det. by O.B.T.'s.: 79

32" Fir S.32°W. 70.3 ft. O.B.T., found scribe.  
36" Fir S.8°E. 90.0 ft. O.B.T.  
44" Fir N.26°E. 47.5 ft. O.B.T.  
32" Fir N.84°W. 46.0 ft. O.B.T.

At Corner Point Found Stone and Set 3" x 30" Iron Pipe from which:

7" Fir bears N. 6°E. 14.9 ft. dist. mkd. S12 B.T.  
7" Cedar bears N.40°E. 22.2 ft. dist. mkd. S 7 T31S R3W B.T.  
15" Fir bears S.70°E. 7.0 ft. dist. mkd. S18 R3W B.T.  
6" Laurel " S.14°W. 30.0 ft. dist. mkd. S13 T31S R4W B.T.

John H. Markham, Jr. August 18, 1959  
 For Stomar Lumber Co.  
 Witnesses: R. G. Boyd & O. A. Keatley  
 J. L. Markham  
 C. S. File No. 42/391

October 7, 1959  
 C. S. File No. 42/391

RE-RENEWED, SEE CORNER NO. #157

RE-RENEWED, SEE CORNER NO. #165

REF. FOR R.O. 4/19/24 - G. L. MENTZ  
CO. SURVEYOR'S OFFICE  
C. S. 59/30