

Douglas County Surveyor's Record of  
Government Corners Renewed

31

T. S.

4

R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

80

$\frac{1}{4}$  Corner to Sections 11 and 12.

At Midpoint Set  $\frac{3}{4}$ " x 30" Iron Pipe from which:

- 5" Laurel bears N.83°E. 32.0 ft. dist. mkd.  $\frac{1}{4}$ " S12 T31S B.T.
- 5" Laurel bears S.37°W. 8.3 ft. dist. mkd.  $\frac{1}{4}$ " S11 T31S R4W B.T.
- 5" Laurel bears S.67°W. 7.1 ft. dist. mkd.  $\frac{1}{4}$ " S11 B.T.

S. W. Corner 12 bears South 2596 feet.

N. W. Corner 12 bears North 2596 feet.

East  $\frac{1}{4}$  Corner of Section 13, as det. by O.B.T.'s:

40" Fir S.66°E. 33.0 ft. O.B.T.

36" Fir S.48°W. 17.4 ft. O.B.T.

At Corner Point set  $1\frac{1}{2}$ " x 20" Iron Pipe from which:

8" Fir bears S.20°E. 26.0 ft. dist. mkd.  $\frac{1}{4}$ " S13 B.T.

7" Fir bears N.84°E. 23.6 ft. dist. mkd.  $\frac{1}{4}$ " S18 B.T.

11" Fir bears N.29°E. 24.0 ft. dist. mkd.  $\frac{1}{4}$ " S18 B.T.

Shively Creek bears South 100.0 feet.

**RE-RENEWED CORNER NO. # 168**  
FD 1/18/81  
H. JOHNSONS  
M 86 - 42

82

Section Corner to Sections 19, 20, 29, and 30, as det. by O.B.T.'s:

40" Fir S. 3 $\frac{1}{2}$ °E. 49.5 ft. O.B.T.

24" Fir N.83°W. 92.4 ft. O.B.T.

At Corner Point found Stone & Set 1" x 48" Iron Pipe from which:

9" Fir S. 5°W. 7.9 ft. mkd. S29 B.T.

9" Fir N.85°E. 8.4 ft. mkd. S20 T31S B.T.

6" Fir N.28°W. 2.7 ft. mkd. S19 B.T.

7" Fir S.85°W. 5.7 ft. mkd. S30 B.T.

Road bears South 265.0 feet.

Road bears East 265.0 feet.

83

$\frac{1}{4}$  Section Corner Sections 19 - 20, as det. by O.B.T.'s:

At Corner Point found:

7" Cedar, uproot, scribed  $\frac{1}{4}$ " S on West face &

Set  $\frac{3}{4}$ " x 40" Iron Rod from which:

10" Cedar bears S.48°W. 11.8 ft. dist. mkd.  $\frac{1}{4}$ " S19 B.T.

10" Fir bears N.61°E. 26.8 ft. dist. mkd.  $\frac{1}{4}$ " S20 B.T.

10" Fir bears N. 6°W. 61.0 ft. dist. mkd.  $\frac{1}{4}$ " S19 B.T.

Corner lies on South Edge of Road on top of Main Ridge.

**RE-RENEWED CORNER NO. 123**

84

$\frac{1}{4}$  Section Corner Sections 29 - 30, as det. by O.B.T.'s:

38" Fir N.66 $\frac{1}{2}$ °W. 28.0 ft. O.B.T.

36" Fir N.15°E. 23.7 ft. O.B.T.

At Corner Point found Stone and Set 2 $\frac{1}{2}$ " x 36" Iron Pipe from which:

7" Fir bears N.17°E. 88.0 ft. dist. mkd.  $\frac{1}{4}$ " S29 B.T.

8" Alder " S.20°E. 141.0 ft. dist. mks.  $\frac{1}{4}$ " S29 T31S R4W B.T.

Road bears East 45.0 feet.

85

$\frac{1}{4}$  Corner Sections 18 - 19, as det. by O. B.T.'s:

11" Fir S.19°W. 6.6 ft. O. B. T.

16" Fir N.34°W. 11.0 ft. O. B. T.

At Corner Point found 6" Fir, dead & down, scribed  $\frac{1}{8}$ " S on North

face and Set  $\frac{1}{2}$ " x 40" Iron Rod from which:

8" Cedar bears N.87°W. 35.0 ft. dist. mkd.  $\frac{1}{4}$ " S19 B.T.

14" Laurel " S.46°W. 19.0 ft. dist. mkd.  $\frac{1}{4}$ " S19 B.T.

8" Cedar bears N.68°E. 22.0 ft. dist. mkd.  $\frac{1}{4}$ " S18 B.T.

Road and Top of Main Ridge bears North 200.0 ft.

**RE-RENEWED CORNER NO. 122**

86

$\frac{1}{4}$  Corner Sections 20 - 21, as det. by O.B.T.:

40" Fir bears N.63°E. 56.1 ft. dist. O.B.T. found scribe.

At Corner Point Set Stake from which:

4" Chip bears N.27°E. 13.2 ft. dist. mkd.  $\frac{1}{4}$ " S21 B.T.

5" Fir bears N.40°W. 15.2 ft. dist. mkd.  $\frac{1}{4}$ " S20 B.T.

5" Fir bears S.82°W. 8.2 ft. dist. mkd.  $\frac{1}{4}$ " S20 B.T.

Top of Ridge bears North 75.0 feet.

**RE-RENEWED CORNER NO. # 145**

John H. Markham, Jr.  
For Stomar Lumber Co.  
Witnesses: J. R. Markham  
R. G. Boyd  
October 7, 1959  
C. S. File No. 42/391