

Douglas County Surveyor's Record of
Government Corners Renewed

31 T. S. 4 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

John H. Markham, Jr.
Witness: R. G. Boyd
For Stomar Lumber Co.
Nov. 17, 1959
C. S. File No. 42/391

1/4 Corner to Sections 14 and 23, as det. by O.B.T.s:
36" Fir S.60°E. 30.0 ft. O.B.T.
24" Fir Snag N.25°W. 17.8 ft. O.B.T.
At Corner Point Set 2" x 40" Iron Pipe from which:
36" Fir bears S. 1°E. 61.6 ft. dist. mkd. 1/4 S23 B.T.
40" Fir bears S.3°E. 30.6 ft. dist. mkd. 1/4 S23 T31S R4W B.T.
24" Fir bears S.82°E. 29.7 ft. dist. mkd. 1/4 S23 X B.T.
Sec. Corner bears West 2664.0 feet.
Sec. Corner bears East 2408.0 feet.
Corner lies on South End of Cat. Road.

87

1/4 Corner to Sections 11 and 14.
At Midpoint Set 1 1/2" x 30" Iron Pipe from which:
7" Cedar bears N. 1°E. 55.0 ft. dist. mkd. 1/4 S11 R4W B.T.
10" Fir bears N.70°E. 34.4 ft. dist. mkd. 1/4 S11 X B.T.
8" Yew bears N.76°E. 32.0 ft. dist. mkd. 1/4 S11 X B.T.
28" Fir bears N.16°W. 25.8 ft. dist. mkd. 1/4 S11 R4W B.T.
Small draw bears North 28.0 feet.
Section Corner bears East 2510.0 feet.
Section Corner bears West 2582.0 feet.

88

N. E. Corner Section 4, as det. by O.B.T.'s:
24" Fir bears N.47°W. 19.1 ft. O.B.T.
At Corner Point Set 1/2" x 1/2" x 30" Angle Iron from which:
3" Laurel bears S.7°E. 26.0 ft. dist. mkd. S3 T31S B.T.
24" Fir bears S.41°E. 56.0 ft. dist., bark scribed S3 T31S R4W B.T.
30" Fir bears S.75°E. 57.0 ft. dist. mkd. S3 T31S R4W BT on bark.

89

John H. Markham, Jr.
Wit: R. G. Boyd
For Stomar Lumber Co.
November 1959
C. S. File No. 42/391

East 1/4 Corner Section 12, as det. by O.B.T.:
28" Fir N.19°E. 40.3 ft. O.B.T. I rescribed S7 T31S R3W B.T.
At Corner Point Found 24" Fir mkd. 1/4 S on West face O.B.T.
Set 1 1/2" x 48" Iron Pipe from which:
6" Fir S.84°E. 42.0 ft. mkd. 1/4 S7 R3W B.T.
7" Fir S.75°E. 35.0 ft. mkd. 1/4 S7 R3W B.T.
12" Fir N.29°W. 31.0 ft. mkd. 1/4 S12 B. T.
Road bears South 290.0 ft. dist.

90

126

Section Corner to 14 - 15 - 22 - 23, as det. by O.B.T.'s:
40" Fir N.49°W. 21.2 ft. O.B.T. rescribed S15 X B.T.
24" Fir S.32°E. 17.8 ft. O.B.T.
At Corner Point Set 2" x 36" Iron Pipe from which:
6" Hemlock bears S.35°W. 22.8 ft. dist. mkd. S23 R4W B.T.
8" Maple S.10°W. 22.8 ft. S22 X B.T.
8" Cedar S.11°E. 43.5 ft. S23 R4W B.T.

91

John H. Markham, Jr.
Witness: R. G. Boyd
For: Stomar Lumber Co.
March 9, 1960
C. S. File No. 42/391

1/4 Corner to Sections 4 - 5.
14" La. bears N.53°E. 12.2 ft., fd. scribe.
At Corner Point found Stone & Set 2" x 30" Iron Pipe from which:
24" Laurel bears N.30°W. 31.3 ft. dist. mkd. 1/4 S5 T31S R4W B.T.
18" Laurel bears S.82°W. 6.2 ft. dist. mkd. 1/4 S5 T31S R4W B.T.
30" Laurel bears S.66°E. 16.0 ft. dist. mkd. 1/4 S4 T31S R4W B.T.
15" Cedar bears S.30°E. 44.0 ft. dist. mkd. 1/4 S4 B.T.

92

Section Corner to Sections 3 - 4 - 9 - 10.
33" Fir N.15°E. 33.6 ft. O. B. T.
40" Fir S.20°W. 54.0 ft. found scribe, O. B. T.
26" Fir N.79°W. 60.0 ft. found scribe, O. B. T.
At Corner Point found Stone & Set 2" x 30" Iron Pipe from which:
7" Laurel bears N.19°W. 23.5 ft. S4 T31S R4W B.T.
8" Laurel bears N.67°E. 28.6 ft. S3 T31S R4W B.T.
6" Chip. bears S.38°E. 16.0 ft. mkd. S10 R4W B.T.

93

RE-RENEWED, SEE CORNER NO. #163