

Douglas County Surveyor's Record of
Government Corners Renewed

31 T. S. 4 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

94
 $\frac{1}{4}$ Section Corner to Sections 3 - 4, as det. by O. B. T's:
6" Fir Snag N.43°E. 11.9 ft., found scribe.
26" Cedar Snag bears S.32°W. 29.7 ft. dist., found scribe, O.B.T.
At Corner Point found 6" Fir Snag mkd. on West face and
Set $\frac{3}{4}$ " x 30" Iron Pipe from which:
4" Fir S.18°E. 21.3 ft. mkd. $\frac{1}{4}$ S3 B.T.
4" Alder S.40°E. 21.5 ft. mkd. $\frac{1}{4}$ S3 R4W B.T.
3" Fir S.54°E. 24.0 ft. mkd. $\frac{1}{4}$ S3 B.T.
3" Alder S.83°W. 3.5 ft. mkd. $\frac{1}{4}$ S4 B.T.
Creek bears South 190.0 feet distance.

John H. Markham, Jr.
Wlt: R. G. Boyd
For: Stomar Lumber Co.
March 9, 1960
C. S. File No. 42/391

88
+ $\frac{1}{4}$ Section Corner to Sec. 1, T31S R4W & Sec. 6, T31S R3W.
as determined by O. B. T's:
40" Fir Snag S.57°W. 16.8 ft. O.B.T.
22" Fir N.61°E. 15.2 ft. O.B.T.
At Corner Point found Stone Mkd: $\frac{1}{4}$ & Set $\frac{3}{4}$ " x 30" I.P. from which:
12" Maple N.44°E. 10.0 ft. mkd. $\frac{1}{4}$ S 6 B.T.
4" Fir N.75°E. 11.8 ft. mkd. $\frac{1}{4}$ S 6 B.T.
7" Fir S.58°E. 19.0 ft. mkd. $\frac{1}{4}$ S 6 B.T.
10" La. S.58°W. 18.5 ft. mkd. $\frac{1}{4}$ S 1 R4W B.T.
2" Fir N.49°W. 6.2 ft. mkd. $\frac{1}{4}$ S 1 B.T.

95

John H. Markham, Jr.
For Stomar Lumber Co.
Wlt. R. G. Boyd
August 2, 1960
C. S. File No. 42/392

88
+ Section Corner Sec. 1 & 12, T31S R4W & Secs. 6 & 7, T31S R3W.
as determined by O. B. T's:
40" Fir S.73°E. 57.4 ft. O.B.T.
22" Fir Snag S.68°W. 23.1 ft. O.B.T.
40" Fir N.85°W. 40.2 ft. O.B.T.
At Corner Point found Stone & Set $\frac{3}{4}$ " x 30" I. P. from which:
4" La. S.87°W. 11.3 ft. mkd. S12 T31S R4W B.T.
5" La. N.53°W. 7.7 ft. mkd. S 1 T31S R4W B.T.
5" La. N.12°E. 7.1 ft. mkd. S 6 T31S R3W B.T.
5" La. East 17.2 ft. mkd. S 7 T31S R3W B.T.
5" La. S.10°W. 11.0 ft. mkd. S12 T31S R4W B.T.
 $\frac{1}{4}$ Corner 6/7 bears N.82 $\frac{1}{2}$ °E.

96

88
 $\frac{1}{4}$ Section Corner to Sections 1 and 12.
as determined by O. B. T's:
50" Fir N. 4°E. 12.7 ft. O.B.T., I bark scribe $\frac{1}{4}$ S1 B.T.
36" Fir S.26°E. 9.8 ft. O.B.T.
At Corner Point Set $\frac{1}{2}$ " x 24" I. R. from which:
12" Fir bears N.43°E. 15.7 ft. dist. mkd. $\frac{1}{4}$ S1 B.T.
14" La. bears N.88°E. 20.0 ft. dist. mkd. $\frac{1}{4}$ S1 T31SR4WBT
14" La. bears S.15°E. 22.0 ft. dist. mkd. $\frac{1}{4}$ S12 B.T.
9" Fir bears S.74°W. 14.0 ft. dist. mkd. $\frac{1}{4}$ S12 B.T.

97

Sept. 1960
C.S. 42/391

88
Sec. Cor. to Secs. 33 & 34, T31-4W. & Secs. 3 & 4, T32-4W.
Found - 1" I. P. with Brass Cap. *Ren. # 22*
20" Fir S.46°30'E. good 4.6
14" Ash S.81°20'W. good 29.3
24" Fir N.39°45'W. blown down, no tree available, 27.0.
40" Fir N.89°15'E. 21.5. Orig., now stump.
Scribed One New BT: 12" Cedar N.48°50'E. 15.9 ft.

98

Geor. J. Wenderoth
Dec. 5, 1962
C.S. File
No. 52/29