

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 4 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

105

Sec. Cor. to Secs. 25, T31-4; Sec. 30, T31-3; Sec. 31, T31-3 and
Sec. 36, T31-4 #172

Found - 24" Cedar, now dead Snag, S. 7° W. 20.6 ft., scribe
visible "CS BT". See Ren. #19, T31-3W.

18" D. Fir S. 19° E. 47.5 ft., gone.

20" D. Fir, now 25", N. 13 1/2° E. 22.7 ft. This tree in
slope bank of road.

14" D. Fir, now 17", N. 13° W. 19.4 ft., shows good scar.

Set - Brass Cap at Sec. Cor. Mkd: T 31 S
County Surveyor's Office, 1966

R S 25	S 30 R
4 S 36	S 31 3
W T 31 S	W

New BT's: 19" D. Fir S. 16° E. 80.1 ft. Mkd: T31S R3W S31 CS BT.
8" D. Fir S. 83° W. 17.5 ft. Mkd: T31S R4W CS BT.

Note - This corner is on edge of new road.

John M. Powell
F. Jones & J. Brady
January 14, 1966
C. S. File No. 52/63

106

Wit. Cor. 1/4 Corner to Sec. 36, T31-4 and Sec. 1, T32-4W.

Found - No trace of I. Rod, See Ren. #28A. This corner is
horse lot, owner wanted corner moved.

48" Cedar, now 50", S. 57° W. 170.0 ft., scribe vis. "BT".

18" Fir, Dead, N. 48° E. 130.4 ft., shows good pitched
over scars. T 31 S

Set - Brass Cap for Wit. Cor. Mkd: W.C. 8' S. to R S 36 1/4
County Surveyor's Office, 1966 (Wood) 4 S 1 1/4
(Cor. in E-W Fence) W T32 S

New BT: 7" Cedar N. 79 1/2° E. 37.0 ft., Mkd: T 1/4 S 36 CS BT.

Powell &
Crew
Jan. 1966
C.S. File
No. 54/20

107

Sec. Cor. to Secs. 3 & 2, T31-4W only.

Found - I. Rod at Corner, See Ren. #58.

20" Fir, now 25", S. 14° W. 44.2 ft., O.B.T., shows scar.

9" Laurel, down. N. 50° E. 43.0 ft.

7" Laurel, now 9", N. 64° E. 38.4 ft., bark scribed.

7" Chinq., down, S. 63° E. 43.5 ft.

14" Chinq., now 16", S. 73° W. 37.5 ft., scribe visible.

Set - Brass Cap at Sec. Cor. Mkd: County Surveyor's S 34 T30S
(Alongside Iron Rod) Office, 1966 R4W S 3/S 2 T31S

Reblazed & Rescribed: 9" Laurel N. 64° E. 38.4 ft. scribed T30S R4W S34 CS BT.

108

Sec. Cor. to Secs. 34 & 35 only, T30S-R4W.

Found - Iron Pipe at Corner, See Ren. #146, T30-4W

7" Fir N. 21° E. 13.7 ft., shows good scars.

27" Cedar S. 40° W. 18.4 ft., scribe visible "S2".

9" Laurel S. 61° E. 28.2 ft., bark scribed "S2 R31SR4W BT".

Set - Brass Cap at Cor. Mkd: County Surveyor's S 34 / S 35 T30S
(Alongside I. Pipe) Office, 1966 R4W S 2 T31S

Reblazed & Rescribed: 9" Laurel S. 61° E. 28.2 ft. scribed
"T31S R4W S 2 CS BT".

John M. Powell
Frank Jones & J. Brady
February 1966
C. S. File No. 54/20

109

1/4 Corner to Sections 33 and 34.

Found - No trace of Iron Pipe, as recorded in Ren. #16.

40" Fir, now Snag, N. 60° W. 52.1 ft. Tree badly burned
but some scribe marks still visible.

14" Fir S. 6° E. 54.0 ft., No trace found.

Set - Brass Cap at 1/4 Cor. Mkd: County Surveyor's Office, 1966
T31S R4W S 33/S 34

New BT's: 17" Fir S. 42° W. 33.4 ft. scribed 1/4 S33 CS BT.
8" Fir N. 37° E. 67.4 ft. scribed 1/4 S34 CS BT.

Note - This corner falls in skid road.

110

1/4 Corner to Sections 27 and 28.

Found - Iron Pipe, as noted in Ren. #39, 8" underground.

6.3 ft. W.O. N. 34 1/2° W. 408.0 ft., good condition, scribe visible.

14" Ash N. 85° 20' E. 177.5 ft., scribe visible "1/4 CS BT".
(Creek bank badly washed, probably lose this tree)

New BT: D. Fir S. 69° E. 508.5 ft. scribed 1/4 S27 CS BT.
Power Pole #E1510 West 20.3 feet.

FD OK
BY R. BROWN
4-93 1112-12

