

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 4 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

John M. Powell
Frank Jones & Joe Brady
January & February 1966
C. S. File No. 54/20

111

Sec. Corner to Sections 27 - 28 - 33 - 34.
Found - Iron Pipe & Scribed Stake at Corner, See Ren. #14.
10" Fir, now 12", N. 21°45'E. 24.7 ft., shows good scar.
(Dist. S.B. 21.5 ft.)
16" Fir, now 17", S. 81°35'E. 20.0 ft., shows good scar.
Orig. 16" Fir N. 45° 26' W. 9.5 ft., shows scar.
18" Fir, now 20", S. 57°04'W. 35.4 ft., shows scar.
Set - Brass Cap for Cor. Mkd: County Surveyor's Office, 1966
(alongside I. Pipe) T31S S 28 | S 27
R4W S 33 | S 34

All Bearing Trees in good condition. No New BT's.

112

Sec. Cor. to Sections 22 - 23 - 26 - 27.
Found - I. Rod at Sec. Cor., See Ren. #11.
8" Fir, now dead, S. 19° W. 24.2 ft., scribe visible, "27 CS",
(Dist. S. B. 32.0 ft.)
16" D. Fir, now 18", S. 48½° E. 14.5 ft., shows good scars.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966
(Alongside I. Rod) T31S S 22 | S 23
R4W S 27 | S 26
New BT: 14" D. Fir S. 78° E. 96.6 ft. scribed T31S R4W S CS BT.
32" Fir Stump N. 67° W. 58.0 ft. scribed T31S R4W S CS BT.

113

¼ Corner to Sections 28 and 29.
Found - I. Pipe & Scribed Stake at Cor. scribed "CS", See Ren. #18.
40" Fir, now 48", N. 28° W. 6.6 ft., shows good scar.
16" Fir, now 23", S. 75° E. 32.3 ft., Tree has been opened.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966
T31S R4W ¼ S 29/S 28
Reblazed & Rescribed: 23" Fir S. 75° E. 32.3 ft. scribed ¼ S28 CS BT.

114

Sec. Cor. to Sections 20 - 21 - 28 - 29.
Found - I. Pipe at Sec. Cor., See Ren. #19.
18" Fir, now 24", N. 31½° E. 13.1 ft., shows good scars.
18" Fir, now 24", S. 53½° E. 49.0 ft., shows good scars, pitched
over scribing visible "2".
28" Fir, now 31", S. 30½° W. 27.4 ft., shows good scars.
9" Fir, now 16", N. 58° W. 30.0 ft., shows good scars.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966
(alongside Iron Pipe) S 20 | S 21 T31S R4W
S 29 | S 28
All BT's. in good condition - This corner lies North of Ridge Top
about 100 feet.

115

Sec. Cor. to Sections 28 - 29 - 32 - 33.
Found - Iron Pipe at Sec. Cor., See Ren. #17.
16" Fir N. 15° E. 22.4 ft., shows good scar.
18" Fir N. 42° W. 5.8 ft., scribe visible "T31S R4W".
18" Fir, now Stump, S. 50° W. 13.8 ft..
40" Fir S. 13° E. 32.5 ft., shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966
S 29 | S 28 T31S R4W
S 32 | S 33
New BT: 13" D. Fir S. 66° W. 10.3 ft. scribed T31S R4W S32 CS BT.

116

Sec. Cor. to Sections 26 - 27 - 34 - 35.
Found - I. Pipe at Sec. Cor., See Wenderoth's Ren. #10.
26" Fir, now 28", N. 62° W. 23.7 ft., good scar.
14" Fir N. 75° E. 25.7 ft., face rotten.
15" Cedar, now 17", S. 40° E. 23.1 ft., good scar.
10", now 14" Fir N. 55° E. 56.2 ft., good scar. (Bearng. S.B.N. 51°E.)
9", now 15" Fir S. 81° E. 49.6 ft., good scar.
8", now 14" Cedar S. 26° W. 34.3 ft., scribe vis. (Brng. S.B. S. 62°W.)
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966
(Alongside I. P.) S 27 | S 26 T31S R4W
S 34 | S 35
All Bearing Trees in good condition.