

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 31 S. T. S. R. 4 W. R.W.W.M.

HOKE-CHAPMAN CO., EUGENE, ORE. 21881

117

$\frac{1}{4}$  Corner to Sections 31 and 32.  
Found - 8" Fir Stump for Corner Tree.  
30" Fir, down, N.  $33\frac{1}{2}^{\circ}$  W. 25.1 ft., opened for scribe "S".  
30", now 37" Fir N.  $35\frac{1}{4}^{\circ}$  E. 26.4 ft., shows good scar.  
Set - Brass Cap at  $\frac{1}{4}$  Cor. Mkd: County Surveyor's Office, 1966  
T31S R4W  $\frac{1}{4}$  S 31/S 32  
New BT: 13" Laurel N.  $2^{\circ}$  E. 47.7 ft. scribed  $\frac{1}{4}$  S32 CS BT.  
Note - Cap is 1.0 ft. north of Corner Tree Stump because of roots.

118

$\frac{1}{4}$  Corner to Sections 22 and 27.  
Found - I. Pipe at  $\frac{1}{4}$  Corner, See Ren. #13.  
Orig. 10", now 26" Fir N.  $62^{\circ}$  E. 9.9 ft., shows good scar.  
Orig. 8", now 22" Fir S.  $25^{\circ}$  W. 4.0 ft., Tree has been opened,  
shows scribe "S".  
Set - Brass Cap at  $\frac{1}{4}$  Cor. Mkd: County Surveyor's Office, 1966  

$\frac{1}{4}$	S 22	T31S
	S 27	R4W

  
Both BT's. in good condition. No New BT's.

119

$\frac{1}{4}$  Corner to Sections 27 and 34.  
Found - Brass Cap at  $\frac{1}{4}$  Corner set by County Surveyor's Office, 1956.  
(See Ren. #38)  
16" Yewood Post S.  $87^{\circ}$  37' E. 37.2 ft., scribe visible.  
12" R. Fir, now 18", N.  $28^{\circ}$  W. 46.3 ft., shows good scar.  
New BT: 8" Fir N.  $28^{\circ}$  E. 88.6 ft. scribed.

120

$\frac{1}{4}$  Corner to Sec. 32, T31-4W. & Sec. 5, T32-4W.  
Found - I. Pipe at  $\frac{1}{4}$  Corner, See Map RM 1 - 37.  
5" Oak, now 8", S.  $53^{\circ}$  E. (not S.  $30^{\circ}$  E) 7.9 ft., scribe visible.  
10" Pine, now 12", N.  $66^{\circ}$  W. 19.4 ft. (Not N.  $54\frac{1}{2}^{\circ}$  W.) Tree had  
been opened & pitched over.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966  

$\frac{1}{4}$	S 32	T31S	R4W
	S 5	T32S	

  
(Alongside I. Pipe).  
Set this corner by Iron Pipe & 2 correct distances.  
New BT's: 14" D. Fir N.  $25^{\circ}$  W. 26.8 ft. scribed  $\frac{1}{4}$  S32 CS BT.  
15" Pine S.  $41^{\circ}$  W. 46.6 ft. scribed  $\frac{1}{4}$  S 5 CS BT.

121

Sec. Cor. to Secs. 35 & 36, T31-4W & Secs. 2 & 1, T32-4W.  
Found - Iron Pipe at Corner, See Ren. #8.  
Orig. 24" Fir N.  $32^{\circ}$  10' E. 30.3 ft., shows good scar.  
Orig. 16", now 19" Laurel N.  $24^{\circ}$  54' W. 20.9 ft., scribe visible.  
Orig. 14", now 17" Fir S.  $30^{\circ}$  50' W. 13.2 ft. Open, no scribe.  
Orig. 10" Laurel S.  $5^{\circ}$  45' E. 8.6 ft., very rotten.  
14" Fir, down, S.  $25^{\circ}$  E. 22.7 ft.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966  

T31S	S 35	S 36	R4W
T32S	S 2	S 1	

  
(Alongside I.P.)  
Rescribed 19" Laurel N.  $24^{\circ}$  54' W. 20.9 ft. scribed T31SR4WS35 CS BT.  
New BT's: 8" Fir S.  $46^{\circ}$  W. 18.7 ft. scribed T32S R4W S 2 CS BT.  
8" Laurel S.  $27^{\circ}$  E. 29.9 ft. scribed T32S R4W S 1 CS BT.

122

$\frac{1}{4}$  Corner to Sections 18 and 19.  
Found - I. Rod, out of the ground, See Ren. #85.  
Orig. 16" Fir, down, N.  $34^{\circ}$  W. 11.0 ft.  
Orig. 11" Fir, dead, S.  $19^{\circ}$  W. 6.0 ft., shows good scar.  
8" Cedar N.  $87^{\circ}$  W. 35.0 ft., gone.  
14" Laurel S.  $46^{\circ}$  W. 19.0 ft., gone.  
Set - Brass Cap at  $\frac{1}{4}$  Cor. Mkd: County Surveyor's Office, 1966  

$\frac{1}{4}$	S 18
	S 19

  
(Set I.R. alongside)  
New BT: 40" D. Fir West 80.0 ft. scribed  $\frac{1}{4}$  S19 CS BT.  
(Corner Reference 1/30/79 see Co. Sub. File C.S. 59/20)

John M. Powell  
Frank Jones and Joe Brady  
February 1966  
C. S. File No. 54/20

RE-RENEWED CORNER NO. #167