

Douglas County Surveyor's Record of  
Government Corners Renewed

T 31 S. T. S. R. 4 W. R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORE. 21881

**RENEWED CORNER NO. #170 123**

$\frac{1}{4}$  Corner to Sections 19 and 20.  
Found - No trace of Iron Rod as recorded in Ren. #83.  
10" Cedar, now snag, S. 48° W. 11.8 ft., scribing visible.  
10" Fir, now 13" N. 61° E. 26.8 ft., shows good scar.  
10" Fir, now 12" N. 6° W. 61.0 ft., shows good scar.  
Set - Brass Cap at  $\frac{1}{4}$  Cor. Mkd: County Surveyor's Office T31S R4W  
(Cedar Post alongside) 1966  $\frac{1}{4}$  S 19/S 20  
All BT's in good condition. - Corner lies on South edge of Jeep Road.

Sec. Cor. to Sections 29 - 30 - 31 - 32. **124**  
Found - No sign of Stone, but found Iron Pipe, unrecorded.  
Orig. 12" Laurel, now rotten stump, N. 69° E. 17.5 ft.  
Orig. 10" Fir, now rotten stump, S. 16 $\frac{1}{2}$ ° E. 12.5 ft.  
Orig. 15" Fir, now 27", S. 12 $\frac{3}{4}$ ° W. 9.2 ft., shows good scar.  
Orig. 15" Fir, now 31", N. 74° W. 17.5 ft., shows good scar.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966 T31S S 30 | S 29  
RAW S 31 | S 32  
New BT's: 37" D. Fir N. 86° E. 6.0 ft. scribed T31S RAW S29 CS BT.  
38" D. Fir S. 48° E. 27.2 ft. scribed T31S RAW S32 CS BT.  
MARCH 1966

**125**  
 $\frac{1}{4}$  Corner to Sec. 25, T31-4W. & Sec. 30, T31-3W.  
Found - Iron Pipe at  $\frac{1}{4}$  Corner, See Ren. #17, T31-3W.  
Orig. 40" Fir S. 50 $\frac{1}{2}$ ° E. 47.8 ft., shows good scar, opened  
for scribing.  
20", now 23" Laurel N. 29° 49' W. 21.7 ft., (bear. S.B. N. 32°W.)  
Scribing visible " $\frac{1}{4}$  S CS BT".  
Set - Brass Cap at  $\frac{1}{4}$  Cor. Mkd: County Surveyor's Office, 1966 T31S  
RAW S 25/ S 30 R3W  
New BT: 7" Laurel S. 53° E. 4.7 ft. scribed  $\frac{1}{4}$  S30 CS BT.

**126**  
 $\frac{1}{4}$  Corner to Sec. 12, R4W. and Sec. 7, R3W.  
Found - No trace of Iron Pipe at Corner as recorded Ren. #90.  
28" D. Fir N. 19° E. 40.3 ft., had been opened for scribe,  
" $\frac{1}{4}$ " on West face.  
6" Fir, down, S. 84° E. 42.0 ft.  
7" D. Fir, now 8", S. 75° E. 35.0 ft., shows good scar.  
12", now 13", D. Fir N. 29° W. 31.0 ft., "BT" scribe visible.  
Set - Brass Cap at  $\frac{1}{4}$  Cor. Mkd: County Surveyor's Office, 1966 T 31 S  
RAW S 12 / S 7R3W  
As notes Road bears North 290.0 ft.

**127**  
 $\frac{1}{4}$  Corner to Sections 35 and 36.  
Found - No Trace of Corner Stone.  
Orig. 6", now 10", B. Oak S. 80 $\frac{3}{4}$ ° W. 29.7 ft., very rotten,  
scribe visible " $\frac{1}{4}$ S".  
Orig. 10", now 13", B. Oak N. 40 $\frac{1}{4}$ ° E. 13.2 ft. Opened for  
scribe "B". Center of tree rotted out.  
Set - Brass Cap at  $\frac{1}{4}$  Cor. Mkd: County Surveyor's Office, 1966 T31S R4W  
 $\frac{1}{4}$  S 35/S 36  
New BT's: 5" Pine West 32.1 ft. scribed  $\frac{1}{4}$  S CS BT.  
9" Pine N. 46° E. 19.1 ft. scribed  $\frac{1}{4}$  S36 CS BT.  
FD OK BY R. BROWN 4-93 4112-72

**128**  
 $\frac{1}{4}$  Corner to Sections 21 and 22.  
Found - Squared Stake at  $\frac{1}{4}$  Corner scribed " $\frac{1}{4}$ S", See Ren. #27.  
16", now 19", Fir S. 66° 26' E. 35.1 ft., shows good scar.  
30" Fir S. 85° W. 25.2 ft. scribed visible " $\frac{1}{4}$  S BT".  
Set - Brass Cap at  $\frac{1}{4}$  Corner Mkd: County Surveyor's Office, 1966 T31S R4W  
S 21 / S 22  
Bearing Trees are all in good condition.

John M. Powell  
Frank Jones and Joe Brady  
February and March 1966  
C. S. File No. 54/20