

**Douglas County Surveyor's Record of
Government Corners Renewed**

T. 31 S. T. S. R. 4 W. R.W.W.M.

ROKE-CHAPMAN CO., EUGENE, ORE. 21881

129

$\frac{1}{4}$ Corner to Sections 21 and 28.
 Found - 22", now 27" Fir N. 38° W. 34.0 ft., bark scribed " $\frac{1}{4}$ " S" visible.
 32", now 38" Fir S. $67\frac{1}{2}^\circ$ E. 38.2 ft., bark scribed "CS BT" "
 Yewwood Post at $\frac{1}{4}$ Corner, See Ren. #6.
 Set - Brass Cap at $\frac{1}{4}$ Cor. Mkd: County Surveyor's Office, 1966

T31S	RAW
$\frac{1}{4}$	$\frac{1}{4}$
S 21	S 28

Rescribed & Reblazed: 27" D. Fir N. 38° W. 34.0 ft. mkd: $\frac{1}{4}$ S21 CS BT.
 38" D. Fir S. $67\frac{1}{2}^\circ$ E. 38.2 ft. Mkd: $\frac{1}{4}$ S28 CS BT.

130

$\frac{1}{4}$ Corner to Sections 22 and 23.
 Found - Orig. 16" Fir Corner Tree, now stump, shows scar on W. face.
 Orig. 14" Fir, now snag, S. 87° W. 11.5 ft., shows good scar.
 Orig. 13" Fir, now stump, S. $60\frac{1}{2}^\circ$ E. 7.9 ft., scribe visible.
 Set - Brass Cap at $\frac{1}{4}$ Corner Mkd: County Surveyor's Office, 1966

T31S	RAW
$\frac{1}{4}$	$\frac{1}{4}$
S 22	S 23

(West Face of Cor. Tree Stump)
 New BT's: 24" D. Fir S. 11° W. 42.2 ft. scribed $\frac{1}{4}$ S22 CS BT.
 35" D. Fir N. 70° W. 35.5 ft. scribed $\frac{1}{4}$ S22 CS BT.

131

$\frac{1}{4}$ Corner to Sections 23 and 26.
 Found - Orig. 30" D. Fir Stump S. 44° W. 17.2 ft. Opened for (dist. S.B. 16.0') scribe " $\frac{1}{4}$ " S".
 Orig. 12" Maple, now 17", N. 28° W. 22.1 ft., shows scar.
 Set - Brass Cap at $\frac{1}{4}$ Cor. Mkd: County Surveyor's Office, 1966

T31S	RAW
$\frac{1}{4}$	$\frac{1}{4}$
S 23	S 26

Reblaze & Rescribe: 17" Maple N. 28° W. 22.1 ft. $\frac{1}{4}$ S 23 / S 26
 New BT: 4" D. Fir S. $16\frac{1}{2}^\circ$ E. 22.0 ft. scribed $\frac{1}{4}$ S CS BT.
 Note - This corner is approx. south of Creek.

132

Corner to Sections 18 & 19 only, T31-4W.
 Found - 14x10x5' Stone, 3 notches on N. & S. Edge.
 Orig. 10", now 26", Laurel N. 65° E. 66.0 ft., rotten but parts of scribe visible.
 Orig. 9", now 34" Cedar S. 54° E. 40.9, shows scar.
 Orig. 30" D. Fir S. $14\frac{1}{2}^\circ$ W. 21.8 ft., down & rotten.
 Set - Brass Cap at Sec. Cor. Mkd: County Surveyor's Office, 1966

T31S	R
5	4
S 18	S 19
W	W

New BT: 10" D. Fir N. 69° E. 23.6 ft. scribed T31S RAW S18 CS BT. R5W

133

Corner to Sections 13 & 24, T31-5W only.
 Found - 24" Orig. D. Fir, now Snag, S. 58° W. 13.2 ft., opened for scribe.
 Orig. 24" D. Fir, now Snag, N. 81° W. 38.3 ft.
 Set - Brass Cap at Sec. Cor. Mkd: County Surveyor's Office, 1966

R	T31S	R
5	S 13	4
W	S 24	W

New BT's: 6" Cedar N. 70° E. 20.8 ft. scribed T31S S19 CS BT.
 5" D. Fir N. 36° W. 20.2 ft. scribed S13 CS BT.
 Note - See Sketch in margin for distance between last 2 corners.

134

Wit. Cor. $\frac{1}{4}$ Corner to Sec. 33, T31-4W. & Sec. 4, T32-4W.
 Found - Did not find Brass Cap set by Gov't.
 22" Fir, now 19", N. 9° E. 85.1 ft., shows good scar. (bearing S.B. N. 4° E.)
 18", now 22" S. $42\frac{1}{2}^\circ$ W. 34.3 ft., scribe visible, $\frac{1}{4}$ S4 BT.
 Set - $\frac{3}{4}$ " Iron Rod at $\frac{1}{4}$ Corner in Creek Bed.
 Brass Cap for Wit. Cor. Mkd: County Surveyor's Office, 1966

T31S	
$\frac{1}{4}$	$\frac{1}{4}$
S 33	S 4

Wit. Cor. $\frac{1}{4}$ R4W
 T32S

New BT's: 9" D. Fir N. 29° W. 30.2 ft. scribed W.C. $\frac{1}{4}$ S33 CS BT.
 23" D. Fir S. $45\frac{1}{2}^\circ$ E. 6.0 ft. scribed W.C. $\frac{1}{4}$ S 4 CS BT.

John M. Powell
 Frank Jones & J. Brady
 March 1966
 C. S. File No. 54/20

S 18 RAW
 S 19
 S 13
 S 24
 5.70 CHS.

SEE ALSO
 1709 Notes (C.A.M.)
 F.B. 10 Pg 51