

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T. 31 S. T. S. R. 4 W. R.W.W.M.

MOKE-CHAPMAN CO., EUGENE, ORE. 21881

**141**

Sec. Cor. to Secs. 7 & 18, only, T31-4W.

Found - No trace of Iron Pipe, as recorded in notes.

7" Laurel N.  $44\frac{1}{2}^\circ$  E. 4.4 ft. with alum. tag, not scribed.

Orig. 24" D. Fir N.  $84^\circ$  W. 21.8 ft. Opened tree for scribe, found marks but could not make out. Ren. #65.

Set - Brass Cap at Sec. Cor. Mkd: County Surv. R T31S R  
Office, 5 S12 S 7 4  
1966 W S18 W

New BT's: 7" Laurel N.  $44\frac{1}{2}^\circ$  E. 4.4 ft. scribed T31S R4W S7 CS BT.  
8" Laurel S.  $56^\circ$  E. 23.6 ft. scribed T31S R4W S18 CS BT.

March 10, 1966

$\frac{1}{4}$  Corner to Sections 30 and 31.

**142**

Found - No trace of Iron Pipe,  $\frac{3}{4}$ " as recorded Ren. #20.

Orig. 13" Fir, now 15", dead snag, S.  $45^\circ$  W. 8.0 ft., faint scribing visible.

Orig. 16" Fir, now 20", N.  $23^\circ$  E. 21.0 ft., shows good scar,  $\frac{1}{2}$ " bark scribed above old face.

Set - Brass Cap at  $\frac{1}{4}$  Cor. Mkd: County Surveyor's T31S R4W  
Office  $\frac{1}{4}$  S 30  
1966 S 31

New BT: 24" D. Fir S.  $33^\circ$  E. 38.0 ft. scribed  $\frac{1}{4}$  S31 CS BT.

Sec. Cor. to Sections 15 - 16 - 21 - 22.

**143**

Found - No trace of Stone at Corner.

36", now 46" D. Fir N.  $75^\circ$  W. 73.9 ft. (S.B. 75.9), shows good scar.

36", now 47" D. Fir S.  $57^\circ$  W. 18.1 ft., Opened & scribing visible.

14", now 27" D. Fir N.  $34\frac{1}{2}^\circ$  E. 27.1 ft., shows good scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's T31S R4W  
Office S 16 S 15  
1966 S 21 S 22

Set Corner by 3 bearings & 1 distance.

New BT: 40" D. Fir N.  $88^\circ$  E. 18.0 ft. scribed T31S R4W S15 CS BT.

$\frac{1}{4}$  Corner to Sections 24 & 25.

**144**

Found - Iron Pipe at  $\frac{1}{4}$  Corner, See Ren. #48.

Orig. 10" Fir S.  $11^\circ$  W. 6.1 ft., scribe visible. Tree almost gone.

Orig. 13" Fir N.  $87^\circ$  E. 23.5 ft., good scar, poor condition.

11" Laurel, now 12", N.  $51^\circ$  W. 18.2 ft. scribing visible.

12" Cedar S.  $53^\circ$  E. 37.5 ft., Tree down.

Set - Brass Cap at Sec. Cor. Mkd: County Surveyor's T31S R4W  
Office  $\frac{1}{4}$  S 24  
(Set alongside I. Pipe) 1966 S 25

New BT: 52" D. Fir N.  $51^\circ$  E. 27.0 ft. scribed  $\frac{1}{4}$  S24 CS BT.

$\frac{1}{4}$  Corner to Sections 20 and 21.

**145**

Found - Orig. 40" D. Fir, now 40", N.  $63^\circ$  E. 56.1 ft. Tree had been opened, faint scribe visible.

4", now 6" Chinq. N.  $27^\circ$  E. 13.2 ft., scribed, " $\frac{1}{4}$  S21 BT".

5", now 8" D. Fir N.  $40^\circ$  W. 15.4 ft., shows good scar.

5", now 7" D. Fir S.  $82^\circ$  W. 8.2 ft., some scribe mks. visible.

See Ren. #86 for BT's. above.

Set - Brass Cap at  $\frac{1}{4}$  Cor. Mkd: County Surveyor's T31S R4W  
Office, 1966  $\frac{1}{4}$  S 20/S 21

All Bearing Trees in good condition.

As notes, corner lies 75.0 ft. south of ridge top.

$\frac{1}{4}$  Corner to Sections 25 and 36.

**146**

Found - 10" Fir, now 18" N.  $6\frac{1}{2}^\circ$  W. 23.8 ft., Tree opened for scribe.

Set - Brass Cap at  $\frac{1}{4}$  Cor. Mkd: County Surveyor's T31S R4W  $\frac{1}{4}$  S 25  
Office, 1966 S 36

This corner lies on S. slope of ridge, running about E & W., 50 ft.

N. of small draw. It is now on edge of cut unit.

New BT's: 22" D. Fir N.  $12\frac{1}{2}^\circ$  E. 31.5 ft. scribed  $\frac{1}{4}$  S25 CS BT.

7" Cedar S.  $61^\circ$  W. 28.4 ft. scribed  $\frac{1}{4}$  S36 CS BT.

John M. Powell  
Frank Jones & Joe Brady  
April 1966  
C. S. File No. 54/20

FD ok  
By R. Brown  
4-23-1966-1112-72