

Douglas County Surveyor's Record of
Government Corners Renewed

T. 31 S. T. S. R. 4 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 31881

147

Sec. Corner to Sections 16 - 17 - 20 - 21.
Found - 10" D. Fir, now 24", S. $71\frac{1}{2}^\circ$ E. 15.5 ft. Tree has been
opened & face burned, opened for scribe marks.

No trace of other BT's.

Note - This corner lies on East Side of ridge about 75 ft. west
of spring branch.

Set - Brass Cap at Sec. Cor. Mkd: County Surveyor's Office 1966

T31S R4W	
S 17	S 16
S 20	S 21

New BT's: 9" Hemlock S. $62\frac{1}{2}^\circ$ W. 11.3 ft. scribed T31S R4W S20 CS BT.
4" Fir N. $69\frac{1}{2}^\circ$ W. 20.2 ft. scribed S17 CS BT.

Reblazed & Rescribed: 24" D. Fir S. $71\frac{1}{2}^\circ$ E. 15.5 ft. scribed T31S R4WS21CS BT.

148

Sec. Cor. to Sections 9 - 10 - 15 - 16.
Found - Iron Pipe & Stone with notches, See Ren. #23.

50" Fir S. 57° W. 11.0 ft., shows good scar.

12" Fir, down & rotten, N. $77\frac{1}{2}^\circ$ W. 46.2 ft.

12" Fir, now 18", N. 66° E. 23.0 ft., shows good scar.

No trace of Laurel BT.

Set - Brass Cap at Sec. Cor. Mkd: County Surveyor's Office 1966

T31S R4W	
S 9	S 10
S 16	S 15

New BT's: 23" Cedar S. 49° E. 17.0 ft. scribed T31S R4W S15 CS BT.

Reblaze. & Rescribe: 18" D. Fir N. 66° E. 23.0 ft. scribed T31SR4W S10 CS BT.

149

$\frac{1}{4}$ Corner to Sections 5 and 8.

Found - 13" Laurel, now down, N. $64\frac{1}{2}^\circ$ W. 14.8 ft., scribe visible.

24" D. Fir, now 38", S. $56\frac{1}{2}^\circ$ W. 24.4 ft., tree opened for scribing,
"S4" visible.

Set - Brass Cap at $\frac{1}{4}$ Cor. Mkd: County Surveyor's Office 1966

T31S R4W	
$\frac{1}{4}$ S 5	
S 8	S 5

New BT's: 14" Cedar S. $44\frac{1}{2}^\circ$ W. 11.7 ft. scribed $\frac{1}{4}$ S 8 CS BT.

8" Cedar N. $53\frac{1}{2}^\circ$ E. 6.3 ft. scribed $\frac{1}{4}$ S 5 CS BT.

150

Sec. Cor. to Secs. 30 and 31 only, T31-4W.

Found - 36" Fir, now dead snag, N. 74° E. 48.2 ft., shows scar.

20" Fir, now blow down, S. $81\frac{1}{2}^\circ$ E. 40.3 ft.

33" Fir, now stump, S. $39\frac{1}{4}^\circ$ W. 19.1 ft. scribe visible "S3".

No trace of Stone at Corner.

Set - Brass Cap at Sec. Cor. Mkd: County Surveyor's R Office 1966

T 31 S	R
5	S 30
W S 25	S 31
S 36	W

New BT: 3" Fir N. $79\frac{1}{2}^\circ$ E. 19.4 ft. scribed S30 BT.

Reblazed & Rescribed: 39" Fir Stump S. $39\frac{1}{4}^\circ$ W. 19.1 ft. scribed T31S R5W
(This corner lies in large cut unit) S25 CS BT.

151

Sec. Cor. to Secs. 25 & 36 only, T31-5W.

Found - 24" Fir, now stump, N. 54° W. 20.5 ft., "BT" scribe visible.

24" Fir, now dead snag, S. 36° W. 23.1 ft., shows good scar.

30" Fir, now 38", S. 32° E. 27.1 ft., shows scar.

24" Fir, now dead snag, N. 50° E. 29.7 ft., shows scar.

No trace of stone at Sec. Cor.

Set - Brass Cap at Sec. Cor. Mkd: County Surveyor's R Office 1966

T31S R	
5	S 25
W S 36	W

New BT's: 51" D. Fir N. 60° E. 49.0 ft. scribed T31S R4W S31 CS BT.

12" Cedar S. 51° E. 51.5 ft. scribed T31S R4W S31 CS BT.

Note - This corner lies in large cut unit.

John M. Powell
Frank Jones & Joe Brady
April 1966
C. S. File No. 54/20