Douglas County Surveyor's Record of Government Corners Renewed

T. 31 S. T. S. R. 4 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

152

Sec. Cor. to Secs. 24 & 25 only, T31-5W.
Found - No trace of Stone at Corner.
8" D. Fir, now down & rotten, N. 60° W. 7.3 ft., opened for scribing "31S B".
12" D. Fir, now stump S. 68° W. 27.1 ft.
10" D. Fir, now 13", S. 10° E. 41.0 ft., shows good scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1966 — R 5 W | T 31 S | S 24 S 25 | S 30 | R 4 W
New BT's: 24" D. Fir N. 5° E. 15.1 ft. scribed T31S R4W S30 CS BT.
10" D. Fir S. 24° W. 4.5 ft. scribed T31S R5W S25 CS BT.
Note - This corner lies on the west edge of power line R/W.

- - - - - - - - - - - - - -

153

Sec. Cor. to Sections 6 and 7 only, T31-4W.
Found - 1" Steel Drill at Corner, See Ren. #76.
Orig. 34" Fir, now 37", N. 86° E. 168.3 ft., shows good scar.
5", now 7" Laurel S. 15° W. 5.8 ft., bark scribed "BT".
4", now 6" Laurel N. 44° W. 8.8 ft., bar scribed "S1 T31SR5W".
4", now 6" Laurel N. 22° E. 12.5 ft., bark scribed
4", now 6", D.Fir N. 1° E. 16.9 ft., shows good scar.
Reblazed & Rescribed: 7" Laurel S15°W. 5.8 ft. scribed T31S R5W S1 CS BT.
6" Laurel N.44°W. 8.8 ft. scribed T31SR5W S1 CSBT.



- - - - - - - - - - - - - - -

154

Sec. Cor. to Sections 1 and 12, T31-5W.
Found - 32" Fir, now 36", S. 13° W. 72.2 ft., opened tree for scribe "BT".
No trace of N.W. BT.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1966 — R 5 W | T 31 S | S 1 S 12 | S 7 | R 4 W
New BT's: 8" D. Fir S. 17½° W. 9.0 ft. scribed T31S R5W S12 CS BT.
12" D. Fir N. 50° W. 11.0 ft. scribed T31S R5W S1 CS BT.

John M. Powell
Frank Jones & Joe Brady
April 1966
C. S. File No. 54/20

- - - - - - - - - - - - - - -

155

¼ Corner to Sections 29 and 32.
Found - 24" D. Fir, now burnt Stob, N. 61½° W. 19.1 ft., scribe visible "¼S".
36" D. Fir, now Snag, S. 12° W. 25.1 ft., shows good scars.
No trace of corner stone.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1967 — T 31 S R 4 W | ¼ | S 29 S 32
New BT's: 10" Laurel N. 14° W. 7.4 ft. mkd. ¼ S29 CS BT.
6" D. Fir S. 46° E. 14.0 ft. mkd. ¼ S32 CS BT.
March 8, 1967

MICROFILM TO HERE 10/67

156

¼ Corner to Sections 3 and 10.
Found - Bearing Trees, as follows, See Ren. #29.
17",now 21" Fir, N.66¼°W. 21.3 ft., alive, scribe visible. We Tag.
17",now 20" Fir, Alive, S.39°50'W. 13.3 ft., blaze healed, We Tag.
Orig. Cedar, Alive, N.55¼°E. 56.1 ft., axe marks visible.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1970 — T 31 S R 4 W | ¼ | S 3 S 10
This corner lies on steep, S. E. slope.
7/20/70

V. "Ray" Tracy
V. Perron
C.S. 54/20

MARCH 71