

Douglas County Surveyor's Record of
Government Corners Renewed

T 31 T. S. R 4 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21981

167

(1/4 Cor. Secs. 18 and 19)
C O N T - - - Found - A D. Fir, 40" bears N.88°W., 78.3 ft. (Rec. West 80.0 ft.) Tree has well healed double blaze. Ren. #122
SET - As the corner position now falls on north cutbank of road, We build stone wall around base of corner position 5 1/2 ft. long, 3 feet high. Also the bank above corner is terraced and rocks set in to stop erosion. Set found brass cap at corner position and stamp "Reset 1981".
New BT's-8" I. Cedar bears N.40°W 17.8 ft. double blazed scribed "1/4 S18 CS BT".
11" D. Fir bears N. 1 1/2°E., 39.8 ft. double blazed scribed "1/4 S18 CS BT".
12" I. Cedar bears S.61 1/2°E., 117.9 ft. double blazed scribed "1/4 S19 CS BT"
No other trees available in Section 19 for scribing.

L.E. Monrean
Deputy, Douglas Co.
Surveyors Office
T. Plouff, witness
March 30, 1981
C.S. 61/19

168

1/4 Corner for Section 13; and Sec. 18 of T.31-3
Found - 1 1/2" x 30" pipe firmly set. Ren. 81
Orig. 34" now 40" fir with BLM BT tag & well healed blaze lying downhill approx. 30 ft. from its orig. location. Remains of stump hole & root bears S.66°E., 33.0 ft.
Orig. 18" now 35" fir with well healed blaze, BLM tag & large "X" in bark bears S.48°W., 17.4 ft.
8" now 9" fir with well healed blaze bears S.20°W., 24.8 ft. (Rec. 26.0 ft.) Ren.#81
11" now 12" fir with well healed blaze bears N.29°E., 24.0 ft.
Remains of 7" fir scribed 1/4 S18 BT visible. Tree is down & rotten
Exact orig. location of tree is ~~not~~ ^{now} apparent. Ren. #81
New BT's- 9" madrone scribed 1/4 S18 CS BT in double blaze bears N.51°E., 42.3 ft.
13" yew scribed 1/4 S13 CS BT in double blaze bears N.14°W., 36.0 ft.
Did not set brass cap since area will possibly be destroyed in road construction.
Found no trace of original stone.

Gregory Quibell,
Deputy, Douglas Co.
Surveyors Office
Debbie Stewart
April 27, 1981
C.S. 61/19

4/27/81
169

1/4 Corner common to Sec's. 17, & 20. (ADMINISTRATIVE cor. only).
Found - 7/8" I.P. leaning slightly Southwest, firmly set & protruding 8" above ground. M 81 - 17.
6" Madrone, now 9", bears N.87°W., 8.3-ft. (Rec. N87°W, 10.4-ft. was apparently a measurement to the tree trunk, & not to the root crown. Tree is unscribed and is tagged with a BLM bearing tree tag.
36" D. Fir snag, now a 34" (dbh), approx 45-ft. tall D. Fir snag bears N.22 1/2°W., 16.7-ft. (Rec. N.18°W, 15.4-ft., apparently a face measurement), tree is not scribed & has a BLM tag.
* NOTE: This 1/4 cor. from a U.S. BLM Administrative survey filed in Doug. Cou. Surveyors records as M 81 - 17.
New BT - 10" Madrone bears S.38°E., 38.3-ft., & bark-scribed 1/4 S20 CS BT.

Stephen J. Flause
Deputy, Douglas Co.
Surveyors Office
Karen Mosley
June 9, 1981
C.S. 61 / 24

170

1/4 corner for Sec's. 19, & 20. Ren.#123.
Found - Brass Cap on 1" I.P. which protrudes 9" above the ground & leans slightly to the South. The cap is marked County Surveyors Office 1/4 19 20 1966. (The line on the cap, between 19 & 20, points N.80°E rather than North. No other monument was found.)
11" Cedar (Orig. 10") snag, 7-ft. tall, with scribed 1/4 S19 visible, bears S.64°W., 11.1-ft. (REC S.48°W., 11.8-ft.) per Ren. # 83.
14" Fir (Orig. 10") bears N.52°E., 28.1-ft., (REC N.61°E., 26.8-ft.), with well healed blaze, per Ren. # 83.
15" Fir (Orig. 10") bears N.8°W., 65.2-ft., (REC N.6°W., 61.0-ft.) with well healed blaze.

Gregory E. Quibell
Deputy, Doug. Co.
Surveyor Office
Debbie Stewart,
witness
July 14, 1981
C.S. 61 / 27