

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T. 31 S. T. S. R. 4 S. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

(CONT.)  
Larry E. Monrean  
Deputy Douglas County  
Surveyors Office  
J.M. Powell, witness  
Dec. 30, 1981  
C.S. 61/30

BTs - A D. Fir 19" now 21" with well healed dble.blaze,bears 172  
S.16°E.,80.1-ft. Ren.# 105.  
A D. Fir 8" now 14" with well healed dble.blaze bears S.86°W.,  
17.2-ft. (Rec. S.83°W.,17.5-ft.). Ren.# 105.  
A not of record D. Fir, 22" dia., bears North, 23.9-ft. has a  
yellow tag marked "31S 3W KB 8/20/39".  
Set - The found monument is set at position as determined by the  
previous note.  
Note - For sketch, see C.S. 61/30. 12/30/81

1/4 Corner for Sec. 36; and section 31 of T.31-3  
Found - Original post not found.

Larry E. Monrean,  
Doug. Co. Surveyors  
Office  
John Powell  
Dec. 30, 1981  
C.S. 61/30

1" diam. Iron pipe with 1957 County brass cap attached properly  
marked. Monument is firmly set 10" above ground. Ren. #41  
Orig. 16" fir now a stump 28" diam. with fragmentary scribing  
visible bears N.50°E., 20.5 ft. to face.  
An 18" orig. fir now a stump 28" diam., with scribing "1/4 S"  
visible bears S.43°W., 12.5 ft. to face. (Rec. S.32°W.)  
A W. fir, 16" now 18" with well healed double blaze bears  
N.21°E., 79.5 ft. Ren. #41  
A W. fir 12" now 18" with well healed double blaze bears  
N.83 1/2°W., 53.2 ft. Ren. #41  
New BTs- A 21" D. fir scribed "1/4 S36 CS BT" on a double blaze bears  
N.10°W., 74.8 ft.  
A 10" W. fir scribed "1/4 S31 CS BT" on a double blaze bears  
S.43°E., 15.1 ft. to bottom of lower blaze.  
Sketch in C.S. file.

12/30/81  
174

Center 1/4 Corner for Section 28

C.S. 62/9

Found - 1972 BLM brass cap on 2 1/2" iron pipe firmly set, protrudes  
3" above ground. Cap properly marked.  
A 22" now 24" windfall D. fir with well healed blaze bears  
N.73°E., 8.6 ft. to root hole.  
A 21" fir, now a stump disturbed by fire trail construction bears  
S.18°W., 38.0 ft. (Rec. S.16°W., 37.8 ft.)

No new monument set.

New BTs - 6" madrone double blazed and scribed "C 1/4 S28 CS BT" bears  
S.61°E., 30.8 ft.  
5" W. fir, double blazed and scribed "C 1/4 S28 CS BT" bears  
S.35 1/2°W., 32.9 ft.  
9" D. fir double blazed and scribed "C 1/4 S28 CS BT" bears  
N.19 1/2°E., 65.4 ft.

Monument is located along east edge of fire trail and about 28 ft.  
west of N-S cutting line (clear cut on east.)

8/19/83

CN 1/16 Section 27.

175

REFERENCED CORNER ONLY.

Found - 1972 BLM 2 1/2" iron pipe with properly mkd. brass cap.  
1" diam. iron pipe set by Wenderoth (M4-75) bears S.55 3/4°W.,  
5.8 ft.  
12" now 13" D. fir scribed by Wenderoth and tied to 1972 mon-  
ument by BLM bears N.63 3/4°W., 19.5 ft. has partially healed  
blaze. Tree will be destroyed by future construction of road  
1972 BT, a 12" now 17" D. fir with well healed blaze bears  
N.82°E., 171.4 ft. (Rec. 171.9 ft.)

New Accessories:

8" D. fir double blazed and scribed "S27 CN 1/16 CS BT" bears  
S.31°E., 135.9 ft.  
20" D. fir N.68 3/4°E., 185.68 ft. not scribed.

See sketch in file C.S. 59/30, for references set on new BT lines.

Note: This cor. referenced for future road construction. The monument is  
located along south easterly top of cut line of future road.

8/18/83

**RE-RENEWED, SEE CORNER NO. 177**