

Douglas County Surveyor's Record of  
Government Corners Renewed

31

T. S.

4

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97501

179

Thomas H. Mehl III  
LS # 749  
For: Gregory Timber  
September 27, 1990  
C.S. 63/104

1/4 Corner for Secs. 25 and 26  
Found - Iron post, 2 1/2" diam. with 1980 BLM brass cap.  
Orig. BT, 40.6" DBH D. fir bears S.67 3/4°E., 7 1/2 lks. dist.  
with healed blaze.  
Rotten stump of orig. BT, bears N.25 3/4°W., 17 lks., old slat  
is now detached from stump, but scribing is evident.  
1980 BLM BT, 6" D. fir, bears N.27°W., 21 lks. dist. mkd. 1/4  
S 26 BT, now laying approx. N.10°W.  
New BT - 8.2" DBH D. fir bears N.45°30'E., 23.0 ft. with blaze scribed  
1/4 LS 749 BT.  
No acceptable bearing trees found in section 26. Corner lies on W facin  
slope approx. 100' W of road (31-4-27).

9/27/90

180

Raymond Brown  
LS# 2391  
For: Superior Lumber  
April, 1993  
M 112-72

C 1/4 Section 36.  
Set - 3" brass cap, Mkd: "PLS 2391, T31S, R4W, C 1/4, S 36 1993."  
BT's - 5" D. Fir, bears S.35°43'W., 16.0'.  
8" Cedar, bears N.45°05'W., 23.5'.  
10" Cedar, bears N.49°49'E., 12.0'.  
18" Madrona, bears S.35°20'E., 14.6'.  
All marked "C 1/4, S 36, BT".

4/93

181

Richard Templin  
For: Superior Lumber  
July 1994  
M120-58;CS 63/130

1/4 Corner for Section 6 & Section 31 of T.31-4.  
Set - At proportionate distance, 5/8" iron rod with yellow plastic  
cap marked "TEMPLIN LS 2359"  
BT's - D.Fir, 4" dia. bears N.50°E., 13.2 ft. scribed "1/4 S31" "BT"  
Cedar, 12" dia. bears S.69°E., 35.2 ft. scribed "1/4 S6" "BT"  
D.Fir, 8" dia. bears S.42°W., 17.1 ft. scribed "1/4 S6" "BT"  
D.Fir, 10" dia bears N.61°W., 24.7 ft. scribed "1/4 S31" "BT"

Closing Corner for sections 5 & 6 only

182

Ken Hoffine  
For: Lone Rock Timber Co.  
April 1996  
M 123-69

Found - 3/4" iron rod  
19" Fir snag, bears S.80°W., 11.8', (Rec. S.78°W.,  
12.54') scribing visible. (Ren# 42)  
17" Fir snag, bears S.55 1/2°E., 28.1' (Rec. S.54 1/2°E.,  
28.71') well healed, healed high face.  
45" D.Fir stump, bears S.30 3/4°W., 12.4' (S.31 1/2°W.,  
12.6') bark scribing visible & location tag.  
38" D.Fir bears N.63°W., 6.6' (Rec. N.68°W., 6.93')  
healed face & old tag.  
10" madrone bears S.73 1/4°E., 19.05' (Rec. S.71°E.,  
18.9') high scar & grown over tag.  
Corner sits on a steep south slope.